

# IPC-E1A2W-I50

## 2MP HD IR VF Bullet Network Camera



### قابلیت های کلیدی

- OSD قابل تنظیم
- قابلیت شب و روز
- IR هوشمند 50 تا 80 متر
- کاهنده نویز دیجیتال 3D
- Ultra H.265, H.264, MJPEG
- دارای میکروفون داخلی
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

## Specifications

Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS				
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	42	168	8.4	4.2
	12	108	72	36	18
Angle of View (H)	108.05°-32.59°				
Angle of View (V)	56.81°-18.36°				
Angle of View (O)	111.91°-36.53°				
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 90°	Rotate: 0° - 360°	
Shutter	Auto/Manual, 1 - 1/100000s				
Minimum Illumination	Colour: 0.005Lux (F1.6, AGC ON) 0Lux with IR on				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	> 52dB				
IR Range	50-80m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	120dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main profile, High profile, MJPEG				
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps				
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;				
Video Bit Rate	128 Kbps-16 Mbps				
9:16 Corridor Mode	Supported				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Motion DetectionSmart	Up to 4 areas				
Smart Features	Tampering detection, Audio detection, Human body detection				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Supported				
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise				
Dewarping	N/A				
HLC	Supported				
BLC	Supported				
Audio Compression	G.711				
Suppression	Supported				
Sampling Rate	8KHz				
Edge Storage	Micro SD, up to 128GB				
Network Storage	ANR, NAS, NFS				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL, SNMP				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+				
Network	10/100M Base-TX Ethernet				
Built-in Mic	Supported				
Certifications	CE: EN 60950-1				
	UL: UL60950-1				
	FCC: FCC Part 15				
Power	DC 12V±25%, PoE (IEEE 802.3af)				
	Power consumption: Max 8.5W				
Dimensions [L x W x H]	206 x 74 x 74mm (8.1" x 2.9" x 2.9")				
Net Weight	0.54kg (1.19lb)				
Material	metal				
Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)				
Storage Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)				
Surge Protection	6KV				
Ingress Protection	IP67				
Reset Button	Supported				

## Dimensions

