

IPC-P1F5W-I80S 4.0mm

5MP HD 80m IR Fixed Bullet Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- پشتیبانی از راهرو 9:16
- دارای 2 عدد میکروفون داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم
- IR هوشمند 80 تا 100 متر
- کاهنده نویز دیجیتال 3D
- Ultra265, H.265, H.264, MJPEG

Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	
Minimum Illumination	Colour: 0.003Lux (F1.6, A6C ON) 0Lux with IR on				Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser 2D/3D DNR	
Day/Night	IR-cut filter with auto switch (ICR)				Digital Noise Reduction	2D/3D DNR	
Shutter	Auto/Manual, 1 - 1/100000s				Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise	
Adjustment angle	Pan: 0° - 360°	Tilt: 0° - 90°	Rotate: 0° - 360°		Dewarping	N/A	
WDR	120dB				HLC	Supported	
S/N	>56dB				BLC	Supported	
Lens	4.0mm@F1.0				Defog	Digital Defog	
Angle of View (H)	91.2°				Audio Compression	G.711	
Angle of View (V)	47.9°				Audio Bitrate	64 Kbps	
Angle of View (O)	95.9°				Suppression	Supported	
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Sampling Rate	8KHZ
	4.0	90.0	36.0	18.0	9.0	Edge Storage	Micro SD, up to 256GB
IR Range	Up to 80-100m IR range				Network Storage	ANR, NAS(NFS)	
Wavelength	850nm				Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH	
IR On/Off Control	Auto/Manual				Compatible Integration	ONVIF (Profile S, Profile G, Profile TL API), SDK	
Video Compression	Ultra 265, H.265, H.264, MJPEG				User/Host	Up to 32 users, 2 user levels: administrator and common user	
H.264code profile	Baseline profile, Main profile, High profile				Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF	
Frame Rate	Main Stream: 5MP (2880*1620), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps;				Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below	
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;				Audio I/O	N/A	
Third Stream: D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; 128 Kbps-16 Mbps	Video Bit Rate				Alarm I/O	1/1	
	128 Kbps-16 Mbps				RS485	N/A	
ROI	Up to 8 areas				Built-in Mic	Support 2	
OSD	Up to 8 OSDs				Built-in Speaker	N/A	
Privacy Mask	Up to 4 areas				Network	1 RJ45 10M/100M Base-TX Ethernet	
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 8)				Video Output	N/A	

Dimensions

