

DE-P06-1U

High Definition Video Decoder



قابلیت های کلیدی

- قابلیت پخش کدک های H.265/H.264/MPEG4
- حالت های نمایش 1/2/3/4/6/7/9/16
- پشتیبانی از استاندارد ONVIF
- پشتیبانی از Multicast

- 6 خروجی 4K HDMI
- 2 ورودی 4K HDMI
- پشتیبانی از رزولوشن تا 8 مگاپیکسل
- قابلیت پخش 6 کانال 4K / 24 کانال 1080p / 54 کانال 720p / 96 کانال D1

Specifications

Output channel	6	Audio Output	1-ch
HDMI output	3840x2160 (4K) @30HZ, 1920X1200 (WUXGA) @60HZ, 1920X1080 (1080P) @60HZ, 1600X1200 (UXGA) @60HZ, 1440x900 (WXGA+) @60HZ, 1280x1024 (SXGA) @60HZ, 1280x720 (720P) @60HZ, 1024x768 (XGA) @60HZ	Alarm Input	6(Reservation)
Input channel	2*HDMI	Alarm Output	3 (Reservation)
HDMI input	3840x2160 (4K) @30HZ, 1920X1080 (1080P) @60HZ, 1920X1080 (1080P) @50HZ, 1600x1200 (UXGA) @60HZ, 1440x900 (WXGA) @60HZ, 1280x1024 (SXGA) @60HZ, 1280x720 (720P) @60HZ, 1280x720 (720P) @50HZ, 1024x768 (XGA) @60HZ	USB Interface	1*USB3.0
Video Stream Format	H.265, H.264, MPEG4	Serial Interface	1*RS-232, 1*RS485
Decoding Capability	6x8MP@30, 24x1080P@30, 54x720P@30, 96xD1	Network Interface	1*RJ-45, 10M/100M/1000M adaptive Ethernet Interfaces
Display split	1/2/3/4/6/7/8/9/16	Dimensions	440mm(W)×339mm(D)×44mm(H)
Audio Input	1-ch (Reservation)	Weight	3.30kg
		Working Temperature	-10~55°C
		Working Humidity	10% ~ 90%(No-condensing)
		Power Supply	100V ~ 240V AC
		Consumption	24W

Dimensions

