

# DE-P09-1U

High Definition Video Decoder



## قابلیت های کلیدی

- قابلیت پخش کدک های H.265/H.264/MPEG4
- حالت های نمایش 1/2/3/4/6/7/9/16
- پشتیبانی از استاندارد ONVIF
- پشتیبانی از Multicast

- 9 خروجی 4K HDMI
- 2 ورودی 4K HDMI
- پشتیبانی از رزولوشن تا 8 مگاپیکسل
- قابلیت پخش 9 کانال 4K / 36 کانال 1080p / 81 کانال 720p / 144 کانال D1

## Specifications

Output channel	9
HDMI output	3840x2160 (4K) @30HZ, 1920X1200 (WUXGA) @60HZ, 1920X1080 (1080P) @60HZ, 1600X1200 (UXGA) @60HZ, 1440x900 (WXGA+) @60HZ, 1280x1024 (SXGA) @60HZ, 1280x720 (720P) @60HZ, 1024x768 (XGA) @60HZ
Input channel	2*HDMI
HDMI input	3840x2160 (4K) @30HZ, 1920X1080 (1080P) @60HZ, 1920X1080 (1080P) @50HZ, 1600x1200 (UXGA) @60HZ, 1440x900 (WXGA) @60HZ, 1280x1024 (SXGA) @60HZ, 1280x720 (720P) @60HZ, 1280x720 (720P) @50HZ, 1024x768 (XGA) @60HZ
Video Stream Format	H.265, H.264, MPEG4
Decoding Capability	9x8MP@30, 36x1080P@30, 81x720P@30, 144xD1
Display split	1/2/3/4/6/7/8/9/16

Audio Input	1-ch (Reservation)
Audio Output	1-ch
Alarm Input	6(Reservation)
Alarm Output	3 (Reservation)
USB Interface	1*USB3.0
Serial Interface	1*RS-232, 1*RS485
Network Interface	1*RJ-45 , 10M/100M/1000M adaptive Ethernet Interfaces
Dimensions	440mm(W)×339mm(D)×44mm(H)
Weight	3.37kg
Working Temperature	-10-55°C
Working Humidity	10% - 90%(No-condensing)
Power Supply	100V - 240V AC
Consumption	31W

## Dimensions

