

HS-XVR16101-L5

Hybrid Video Recorder



Network
Cameras

NVRs

AHD
Series

Video
Decoders

Switches

Accessories

قابلیت های کلیدی

- یک عدد HDMI و یک عدد VGA
- پشتیبانی از 1 عدد هارد تا ظرفیت 8 ترابایت
- قابلیت بروزرسانی آنلاین

- پشتیبانی از سیگنال های تصویر TVI, AHD, CVI, CVBS, IP
- 16 کانال ورودی آنالوگ تا رزولوشن 5 مگاپیکسل
- 8 کانال IP تا رزولوشن 8 مگاپیکسل (تا 16 کانال فقط IP)
- پشتیبانی از دوربین های با پروتکل ONVIF

Specifications

Analog Video Input	16-ch, BNC
IP Video Input	8-ch(only IP up to 16ch), each channel up to 8MP
Supported Analog Camera Types	Support AHD input: 5MP@12fps 4MP@15fps 1080P@30fps 720P@30fps Support TVI input: 5MP@12fps 4MP@15fps 1080P@30fps 720P@30fps Support CVI input: 1080P@30fps 720P@30fps Support CVBS input
Audio Input	1-ch, RCA
Incoming Bandwidth	40Mbps (up to 56Mbps after all analog camera conversion)
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE
VGA Output	1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
HDMI Output	1920x1080/60Hz, 1920x1080/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz

Audio Output	1-ch, RCA	
Two-way Audio	1-ch, RCA	
Synchronous Playback	16-ch	
Recording Resolution	5MP Lite/4MP Lite /1080P/1080P Lite/720P/D1/CIF	
Recording Frame Rate	Main stream:	Sub stream:
	5MP Lite@6fps	D6@1fps
	4MP Lite@8fps	D8@1fps
	1080P Lite@15fps	D6@1fps
	720P@15fps	D10@1fps
SATA	1 SATA interface	
Capacity	Up to 8TB for each disk (The maximum HDD capacity varies with environment temperature)	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface	
USB Interface	Rear panel: 2 x USB2.0	
Serial Interface	1 x RS485	
Power Supply	12V DC Power Consumption: ≤ 10 W(without HDD)	
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)	
Dimensions (W×D×H)	260mm ×240mm× 46mm (10.2" × 9.4"×1.8")	
Weight (without HDD)	≤1.1 Kg (2.42lb)	

Rear Panel

Dimensions

