

IPC-A1A4WH-I100S

4MP LightHunter Intelligent Bullet Network Camera



قابلیت های کلیدی

- OSD قابل تنظیم
- قابلیت شب و روز
- IR هوشمند تا 100 متر
- کاهنده نویز دیجیتال 3D
- پایه قابل تنظیم 3 حالت
- Ultra H.265, H.264, MJPEG
- پشتیبانی از 5 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

Sensor	1/1.8", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8-12mm@F1.2				
Iris	Auto aperture				
DDRI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0(206.6ft)	25.2(82.6ft)	12.6(41.3ft)	6.3(20.7ft)
Angle of View (H)	42.6°-113.7°				
	24.1°-59°				
Angle of View (V)	48.9°-128.1°				
Angle of View (D)	Auto/Manual, 1 - 1/100000s				
Shutter	Colour:0.0005lux (F1.2, AGC ON) 0 lux with IR				
WDR	120dB				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>55dB				
IR Range	Up to 100m (328 ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
Video Compression	Ultra 265,H.265,H.264,MJPEG				
Frame Rate	Main Stream: 4MP(2688*1520),Max 60fps; 4MP(2560*1440),Max 60fps;				
	2MP(1920*1080),Max 60fps;				
	Sub Stream: 2MP (1920*1080), Max 60fps;				
	Third Stream: D1 (720*576), Max 60fps				
	Fourth Stream: D1 (720*576), Max 60fps Fifth Stream: D1 (720*576), Max 60fps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Supported				
Video stream	Five streams				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas (8 blacks / 8 mosaics)				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				
HLC	Support				
BLC	Support				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Smart Features	Tampering detection, Audio detection, Scene change detection, Object left, Object removed, Deep learning, Smart intrusion prevention, Face recognition (10000) faces, Video metadata, People counting (deep learning), Face capture (maximum 40)				
Audio Compression	G.711U, G.711A				
Two way audio	Supported				
Sampling Rate	8KHZ				
Edge Storage	Micro SD, up to 256 GB				
Network Storage	ANR,NAS(INFS)				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below				
Audio I/O	Audio cable				
	1 Input: impedance 35kΩ; amplitude 2V *p-p] 1 output: impedance 600Ω; amplitude 2V *p-p]				
Alarm I/O	2/1				
Network	1 x RJ45 10M/100M/1000M Base-TX Ethernet				
Serial Port	1 RS485				
Certifications	CE: EN 60950-1				
	UL: UL60950-1				
	FCC: FCC Part 15				
Power	AC24V±25%, DC12V(-10%~+25%), PoE(IEEE802.3at)				
	Power consumption: Max 13W Support overcurrent protection, Input short circuit protection				
Dimensions (Ø x H)	Ø306.4x104.1x98.1mm(Ø12.1"x4.1"x3.9")				
Net Weight	1.60kg(3.52lb)				
Material	Metal				
Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)				
Storage Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)				
Surge protection	6KV				
Vandal Resistant	IK10				
Ingress Protection	IP67				

Dimensions

