

IPC-A4A8W-SF

4K Ultra-HD LightHunter WDR Network Box Camera



قابلیت های کلیدی

- قابلیت روز و شب
- لوکس نوری پایین
- کاهنده نویز دیجیتال 3D
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- ورودی برق 24VAC/12VDC/POE
- دمای کارکرد -20 تا +60 درجه سانتیگراد
- حفاظت الکتریکی 6KV

Specifications

Sensor	1/1.8", 8.0 megapixel, progressive scan, CMOS	Audio Bitrate	64 Kbps
Minimum Illumination	Colour:0.002lux (F1.2, AGC ON) B/W: 0.0002Lux(F1.2, AGC ON)	Two-way Audio	Support
Day/Night	IR-cut filter with auto switch (ICR)	Suppression	Support
Shutter	Auto/Manual, 1 - 1/100000s	Sampling Rate	8KHz
WDR	120dB	Edge Storage	Micro SD, up to 256 GB
S/N	>56dB	Network Storage	ANR,NAS(NFS)
ABF	Support	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS
Lens Mount	C/CS	Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API,SDK
Iris	DC-Iris/P-Iris, DC 5V (4 Pins)	User/Host	Up to 32 users. 2 user levels: administrator and common user
Video Compression	Ultra 265, H.265, H.264, MJPEG	Security	Password protection, strong password, HTTPS encryption, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Frame Rate	Main Stream: 8MP (3840*2160), Max 30fps in Frame Rate Priority mode; Max 20fps in Smart Priority mode; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps	Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Video Bit Rate	128 Kbps-16 Mbps	Audio I/O	1/1
ROI	Up to 8 areas	Alarm I/O	2/1
OSD	Up to 8 OSDs	Zoom/focus	Support
Privacy Mask	Up to 4 areas per scene	Serial Port	1 RS485
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	Built-in Mic	N/A
Digital noise reduction	2D/3D DNR	Built-in Speaker	N/A
Flip	Normal/Flip Vertical/Flip Horizontal/180°	Network	1*100M/1000M SFP+ 1*RJ45 10M/100M/1000M Base-TX Ethernet
HLC	Support	Video Output	1 BNC
BLC	Support	Power	DC12V(±25%), AC24V(±25%), PoE(IEEE 802.3af) Power consumption: Max 8.0W
Defog	Optical Defog & Digital Defog	Power Interface	Two-core terminal block
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication	Dimensions (L x W x H)	152 x 71 x 65mm (6.0" x 2.8" x 2.6") (excluding the lens)
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40)	Weight	0.40kg (0.88lb)
Audio Compression	G.711U, G.711A	Working Environment	-20°C - 60°C (-4°F - 140°F), Humidity: ≤95% RH (non-condensing)
		Surge Protection	6KV
		Reset button	Support
		Protection	N/A

Dimensions

