

IPC-A7FCD-I10S

4K Ultra HD Vandal-resistant Fisheye Fixed Dome Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -35 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- رزولوشن 12 مگاپیکسل
- Ultra 256, H.265, H.264, MJPEG
- میکروفون و اسپیکر داخلی
- قابلیت صدای دو طرفه
- قابلیت جبران خمیدگی لبه های تصویر
- تصویر عریض 360 درجه
- IR هوشمند تا 10 متر با پوشش 360 درجه
- کاهنده نویز دیجیتال 3D

Specifications

sensor	1/1.7", 12.0 megapixel, progressive scan, CMOS					Audio Compression	G.711
Lens	1.8mm@F2.4					Two-way audio	Supported
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Suppression	Supported
	1.8	43.8	17.5	8.8	4.4	Sampling Rate	8KHZ
Angle of View	360°					Edge Storage	Micro SD, up to 256GB
Shutter	Auto/Manual, shutter time: 1 - 1/100000s					Network Storage	ANR
Minimum Illumination	Colour: 0.05Lux (F2.4, AGC ON)					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
	0Lux with IR						
Day / Night	IR-cut filter for day & night function					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Digital noise reduction	2D/3D DNR					Mount Type	Support table,
S/N Ratio	>52dB					Audio I/O	Audio interface
IR Range	Up to 10m (33ft)					Input: impedance 35kΩ; amplitude 2V [p-p]	
Defog	Digital Defog					Output: impedance 600Ω; amplitude 2V [p-p]	
WDR	100dB					Alarm I/O	2/1
Compression	Ultra265, H.265, H.264, MJPEG					Multiple Alarm linkage editable	
H.264 code profile	Baseline profile, Main Profile, High Profile					Built-in Mic	Supported
Fisheye Frame Rate	Main Stream: 15fps (4000*3000, 3000*3000); 25fps (2560*2560);					Built-in Speaker	Supported
	Sub Stream: 15fps (2000*1500, 2000*2000); 25fps (2000*2000);					Serial	1 channel RS485 interface
	Third Stream: 15fps (720*576, 320*288)					Network	1 RJ45 10M/100M Base-TX Auto-adaptive Ethernet
Panorama	25fps (3000*2000);					Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]
	15fps (4000*3000, 3000*2000, 3000*1500)					Power	DC 12V±25%, PoE (IEEE 802.3af)
Frame Rate PTZROI	15fps (1920*1080)					Power consumption: Max 9.6W	
ROI	Up to 8 areas					Dimensions (Ø x H)	Ø149 x 55mm (Ø5.87" x 2.17")
BLC	Supported					Weight	0.5kg (1.1lb)
OSD	Up to 8 OSDs					Working Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH
Privacy Mask	Up to 8 areas					Ingress Protection	IP66
Motion Detection	Up to 4 areas					Vandal Resistant	IK10
Smart Features	Audio detection, Cross line, intrusion, Heatmap					Reset Button	Supported

Dimensions

