

# IPC-E1F2D-I60 4.0mm/R

2MP Bullet Network Camera



## قابلیت های کلیدی

- دارای IR هوشمند 60 تا 80 متر
- کاهنده نویز دیجیتال 3D

- دارای میکروفون داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Network  
Cameras

NVRs

AHD  
Series

Video  
Decoders

Switches

Accessories

## Specifications

Sensor	1/3", progressive scan, CMOS				
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.02 (F2.1, AGC ON)				
	0Lux with IR on				
WDR	100dB				
Lens Type	4.0mm @F2.1				
Field of View (H)	80.2°				
Field of View (V)	42.9°				
Field of View (D)	86.0°				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0	66.7	26.7	13.3	6.7
IR Range	60-80m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video Compression	H.265, H.264				
Frame Rate	Main Stream: 2MP (1920*1080), Max 25fps; 720P (1280*720), Max 25fps;				
	Sub Stream: D1 (720*576), Max 25fps; 640*360, Max 25fps; 2CIF(704*288), Max 25fps; CIF(352*288), Max 25fps;				
Video Bit Rate	128 Kbps-6 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Supported				
Flip	Normal/Vertical/Horizontal/180°				

Dewarping	N/A
HLC	Supported
BLC	Supported
Defog	Digital Defog
Basic Detection	Tampering detection, audio detection
General Function	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication, HTTP authentication
Audio Compression	G.711A, G.711U
Audio Bitrate	64 Kbps
Two-way audio	N/A
Suppression	Support
Sampling Rate	8KHZ
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP, RTMP
Compatible Integration	ONVIF (Profile S, Profile T), API
User/Host	Up to 32 users. 2 user levels: administrator and common user
Web Browser	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+
Network	1 * RJ45 10M/100M Base-TX Ethernet
Built-in Mic	Supported
Protection	IP67 (IEC 60529:1989+AMD1:1999+AMD2:2013)
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 6.0W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (L x W x H)	246x 97 x 187mm (9.7" x 3.8" x 7.4")
Weight	0.65kg (1.43lb)
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	4KV
Reset Button	N/A

## Dimensions

