

IPC-E1F2W-I30

2MP Mini Fixed Bullet Network Camera



قابلیت های کلیدی

- قابلیت شب و روز
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

- Ultra H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -35 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F2.0				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	42	16.8	8.4	4.2
Angle of View (H)	112.7°				
Angle of View (V)	60.1°				
Angle of View (D)	121.2°				
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°	Rotate: 0° ~ 360°	
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.02Lux (F2.0, AGC ON)				
	0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	30-50m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	120db				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps				
	Sub Stream: 720P (1280*720), Max 30fps;				
Video Bit Rate	128 Kbps-16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
Smart Features	Tampering Detection, Human body detection				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Support				
Filp	Normal/Vertical/Horizontal/180°				
Dewarping	Support				
HLC	Supported				
BLC	Supported				
Behavior Detection	Human Body Detection, Motion Detection, Tampering Alarm				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Web Browser	Plug-in required (live view: IE9+, Chrome 41 and below, Firefox 52 and below) Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+				
Edge Storage	Micro SD, up to 128GB				
Network Storage	ANR				
Network	10/100M Base-TX Ethernet				
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4.5W				
Dimensions (L x W x H)	165 x 63.1 x 62.5mm (6.5" x 2.5" x 2.5")				
Net Weight	0.45kg (0.99lb)				
Material	Sun shield: plastic				
	Front cover: metal				
	Body: metal				
	Bracket: metal Bottom plate: metal				
Working Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)				
Storage Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)				
Surge Protection	2KV				
Ingress Protection	IP67				

Dimensions

