

# IPC-E1F4D-I30 4.0mm/R

4MP Mini Fixed Bullet Network Camera



## قابلیت های کلیدی

- پایه قابل تنظیم 3 حالت
- دارای میکروفون داخلی
- پشتیبانی از ROI
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- OSD قابل تنظیم
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

## Specifications

Sensor	1/3", progressive scan, CMOS				
Lens	4.0mm@F2.1				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0	90.0	36.0	18.0	9.0
Angle of View (H)	79.0°				
Angle of View (V)	42.3°				
Angle of View (D)	85.1°				
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 90°	Rotate: 0° - 360°	
Shutter	Auto/Manual, 1 - 1/100000s				
Minimum Illumination	Colour: 0.02Lux (F2.1, AGC ON)				
	0Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>52dB				
IR Range	30-50m IR range				
Defog	Digital Defog				
WDR	100dB				
Audio Compression	G.711				
Suppression	Supported				
Sampling Rate	8KHZ				
Video Compression	Ultra 265, H.265, H.264				
Frame Rate	Main Stream: 4MP (2560*1440), Max 20fps; 3MP (2304*1296), Max 20fps; 1080P (1920*1080), Max 30fps;				
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;				
HLC	Supported				
BLC	Supported				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
Basic Detection	Audio Detection				
Protocols	IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP, RTMP				
Compatible Integration	ONVIF (Profile S, Profile T), API				
Network	10/100M Base-TX Ethernet				
Built-in Mic	Supported				
Power	DC 12V±25%, PoE				
	Power consumption: Max 3.5W				
Dimensions (L x W x H)	144 x 60 x 65mm (5.6" x 2.4" x 2.6")				
Weight	0.17kg (0.37lb)				
Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)				
Surge Protection	4KV				
Ingress Protection	IP67				
Reset Button	N/A				

## Dimensions

