

IPC-E1F4W-150

4MP EasyStar Mini Fixed Bullet Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- قابلیت شب و روز
- IR هوشمند 50 تا 70 متر
- کاهنده نویز دیجیتال 3D
- شیشه ضد بازتاب نور مادون قرمز

Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS					Motion Detection	Up to 4 areas
Lens	2.8mm@F1.6					Smart Features	Human body detection
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)	White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
	2.8	63	25.2	12.6	6.3	Smart IR	Support
Angle of View (H)	105.3°					Flip	Normal/Vertical/Horizontal/180°
Angle of View (V)	57°					Dewarping	Support
Angle of View (D)	136.9°					HLC	Supported
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 90°		Rotate: 0° - 360°	BLC	Supported
Shutter	Auto/Manual, 1 - 1/100000s					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL
Minimum Illumination	Colour: 0.005Lux (F1.6, AGC ON) 0Lux with IR					Compatible Integration	ONVIF (Profile S, Profile T), API
Digital Noise Reduction	2D/3D DNR					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Day/Night	IR-cut filter with auto switch (ICR)					Network	10/100M Base-TX Ethernet
S/N	>52dB					Certifications	CE: EN 60950-1
IR Range	50-70m IR range						UL: UL60950-1
Wavelength	850nm					FCC: FCC Part 15	Power
IR On/Off Control	Auto/Manual					DC 12V±25%, PoE (IEEE 802.3af)	Power consumption: Max 6W
Defog	Digital Defog					Dimensions(L x W x H)	191.3×72.6×70.9mm (7.5"×2.9"×2.8")
WDR	120dB					Net Weight	0.5kg (1.1lb)
Video Compression	Ultra 265, H.265, H.264, MJPEG					Material	Metal
H.264 code profile	Baseline profile, Main Profile, High Profile					Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Frame Rate	Main Stream: 4MP (2688*1520), Max 25fps; Sub Stream: 720P (1280*720), Max 25fps					Storage Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Video Bit Rate	128 Kbps-16 Mbps					Surge Protection	2KV
OSD	Up to 4 OSDs					Ingress Protection	IP67
Privacy Mask	Up to 4 areas						
ROI	Up to 4 areas						

Dimensions

