

IPC-E1F8W-I30

4K mini fixed Bullet Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- قابلیت روز و شب
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/3", 8.0 megapixel, progressive scan, CMOS					ROI	Up to 2 areas
Lens	2.8mm@F2.0					Motion Detectio	Up to 4 areas
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)	Smr Features	intrusion, Human body detection
	2.8	84	33.6	16.8	8.4	White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Angle of View (H)	112.7°					Digital noise reduction	2D/3D DNR
Angle of View (V)	60.1°					Smart IR	Support
Angle of View (D)	146.5°					Flip	Normal/Vertical/Horizontal/180°
Adjustment angle	Pan: 0°-360°		Tilt: 0°-90°		Rotate: 0°-360°	Dewarping	NA
Shutter	Auto/Manual, 1-1/100000 s					HLC	Supported
Minimum Illumination	Colour: 0.05 Lux (F2.0, AGC ON)					BLC	Supported
	0 Lux with IR on					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Digital noise reduction	2D/3D DNR					Compatible Integration	ONVIF(Profile S, Profile T), AP
Day/Night	IR-cut filter with auto switch (ICR)					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
S/N	>56dB					Network	10/100M Base-TX Ethernet
IR Range	30-50m IR range					Certifications	CE: EN 60950-1
Wavelength	850nm						UL: UL60950-1
IR On/Off Control	Auto/Manual						FCC: FCC Part 15
Defog	Digital Defog					Power	12 V DC±25%, PoE (IEEE802.3 af) Power consumption: Max 5.5W
WDR	120dB					Dimensions (L x W x H)	167.3x62.9x62.7mm (6.6"x2.5"x2.5")
Video Compression	Ultra 265, H.265, H.264, MJPEG					Net Weight	0.45kg (0.99lb)
H.264 code profile	Baseline Profile, Main Profile					Material	Metal
Frame Rate	Main Stream:8MP (3840*2160): Max. 20 fps;5MP(2944*1656): Max. 30 fps;					Working Environment	-30°C ~ +60°C [-22°F ~ 140°F], Humidity: ≤95% RH(non-condensing)
	4MP(2560*1440): Max. 30 fps; 2MP(1920*1080): Max. 30 fps					Storage Environment	-30°C ~ +60°C [-22°F ~ 140°F], Humidity: ≤95% RH(non-condensing)
	Sub Stream:720P (1280*720): Max. 20 fps					Surge Protection	2KV
Third Stream:4CIF (704*576): Max. 20 fps						Ingress Protection	IP67
Video Bit Rate	128 Kbps-16 Mbps					Reset Button	Supported
OSD	Up to 4 OSDs						
Privacy Mask	Up to 4 areas						

Dimensions

