

IPC-E2A4D-I30

4MP VF Vandal-resistant IR Dome Network Camera



قابلیت های کلیدی

- IR هوشمند 30 تا 60 متر
- پاره شدن بازتاب نور مادون قرمز
- کاهنده نویز دیجیتال 3D
- پایه لنز قابل تنظیم 3 حالت
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- قابلیت روز و شب
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8 - 12mm, motorized zoom lens				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63	25.2	12.6	6.3
	12	270	108	54	27
Angle of View (H)	106.9° - 28.4°				
Angle of View (V)	55.3° - 16.4°				
Angle of View (D)	138.9° - 34.9°				
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 80°		Rotate: 0° - 360°
Shutter	Auto/Manual, 1 - 1/100000s				
Minimum Illumination	Colour: 0.01Lux (F1.6, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
IR Range	30-60m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog Digital	Defog				
WDR	100dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps;				
	Sub Stream: 720P (1280*720), Max 20fps;				
	Third Stream: D1 (704*576), Max 20fps				
Video Bit Rate	128 Kbps-16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 2 areas				
Motion Detection	Up to 4 areas				
Smart Features	intrusion, Human body detection				

White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Network	1 RJ45 10M/100M Base-TX Ethernet
Certifications	CE: EN 60950-1
	UL: UL60950-1
	FCC: FCC Part 15
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 7W
Dimensions (Ø x H)	Ø148 x 111.3mm (Ø5.8" x 4.4")
Net Weight	0.92kg (2.0lb)
Material	Metal + Plastic
Working Environment	-40°C - 60°C (-40°F - 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-40°C - 60°C (-40°F - 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67
Vandal Resistant	IK10
Reset Button	Supported

Dimensions

