

IPC-E2F4W-I30

4MP StarLight Vandal-resistant Network Fixed Dome Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت
- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- قابلیت روز و شب
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS					White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/ Auto2	
Lens	2.8mm@F1.6					Digital noise reduction	2D/3D DNR	
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)	Smart IR	Support	
	2.8	63	25.2	12.6	6.3	Flip	Normal/Vertical/Horizontal/180°	
Angle of View (H)	105.3°					Dewarping	Support	
Angle of View (V)	57°					HLC	Supported	
Angle of View (D)	136.9°					BLC	Supported	
Adjustment angle	Pan: 0°-360°		Tilt: 0°-68°		Rotate: 0°-360°	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL	
Shutter	Auto/Manual, 1 - 1/100000s					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API	
Minimum Illumination	Colour: 0.005Lux (F1.6, AGC ON) 0Lux with IR					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+	
Day/Night	IR-cut filter with auto switch (ICR)					Edge Storage	Micro SD, up to 256 GB	
Digital noise reduction	2D/3D DNR					Network Storage	ANR	
S/N	>52dB					Network	10/100M Base-TX Ethernet	
IR Range	30-50m IR range					Certifications	CE: EN 60950-1	
Wavelength	850nm						UL: UL60950-1	
IR On/Off Control	Auto/Manual						FCC: FCC Part 1	
Defog	Digital Defog					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 3.5W	
WDR	120dB					Dimensions (Ø x H)	Ø109 x 81mm (Ø4.3" x 3.2")	
Video Compression	Ultra 265, H.265, H.264, MJPEG					Net Weight	0.49kg (1.08lb)	
H.264 code profile	Baseline profile, Main Profile, High Profile120db					Material	Shield: PC	
Frame Rate	Main Stream: 4MP (2688*1520), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 2MP (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 25fps						Body: plastic	
Video Bit Rate	128 Kbps-16 Mbps					Bottom plate: metal	Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
OSD	Up to 4 OSDs					Storage Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)	
Privacy Mask	Up to 4 areas					Surge Protection	2KV	
ROI	Up to 4 areas					Ingress Protection	IP67	
Motion Detection	Up to 4 areas					Vandal Resistant	IK10	
Smart Features	Human body detection							

Dimensions

