

IPC-E3F2D-I30/D

2MP Fixed Dome Network Camera



قابلیت های کلیدی

- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

| | | | | | |
|-------------------------|---|------------|----------------|-------------------|--------------|
| Sensor | 1/2.8", 2.0 megapixel, progressive scan, CMOS | | | | |
| Lens | 2.8mm@F2.0 | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 2.8 | 43.4 | 17.4 | 8.7 | 4.3 |
| Angle of View (H) | 106.7° | | | | |
| Angle of View (V) | 57.1° | | | | |
| Angle of View (D) | 115.7° | | | | |
| Shutter | Auto/Manual, 1 - 1/100000s | | | | |
| Adjustment angle | Pan: 0° - 360° | | Tilt: 0° - 80° | Rotate: 0° - 360° | |
| Minimum Illumination | Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR on | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| Digital noise reduction | 2D/3D DNR | | | | |
| S/N | >52dB | | | | |
| IR Range | 30-50m IR range | | | | |
| Wavelength | 850nm | | | | |
| IR On/Off Control | Auto/Manual | | | | |
| Defog | Digital Defog | | | | |
| WDR | 100dB | | | | |
| Frame Rate | Main Stream: 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; 128 Kbps-16 Mbps | | | | |
| Video Bit Rate | 128 Kbps-16 Mbps | | | | |
| 9:16 Corridor Mode | Supported | | | | |
| OSD | Up to 4 OSDs | | | | |
| Privacy Mask | Up to 4 areas | | | | |
| ROI | Up to 8 areas | | | | |
| Motion Detection | Up to 4 areas | | | | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 | | | | |
| Smart Features | N/A | | | | |
| Digital Noise Reduction | 2D/3D DNR | | | | |
| Smart IR | Supported | | | | |
| Flip | Normal/Vertical/Horizontal/180° | | | | |
| Dewarping | N/A | | | | |
| HLC | Supported | | | | |
| BLC | Supported | | | | |
| Protocols | IPv4, IGMP, ICMP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, UPnP, HTTP | | | | |
| Compatible Integration | API | | | | |
| Web Browser | Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+ | | | | |
| Network | 10/100M Base-TX Ethernet | | | | |
| Power | DC 12V±25%, PoE (IEEE 802.3af) | | | | |
| | Power consumption: Max 5.0W | | | | |
| Dimensions (Ø x H) | Ø118 x 95mm (Ø4.6" x 3.8") | | | | |
| Net Weight | 0.29kg (0.64lb) | | | | |
| Material | Metal + Plastic | | | | |
| Working Environment | -30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing) | | | | |
| Storage Environment | -30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing) | | | | |
| Surge Protection | 4KV | | | | |
| Ingress Protection | IP67 | | | | |
| Reset Button | N/A | | | | |

Dimensions

