

IPC-E3F4D-I30/D

4MP Fixed Dome Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D

Specifications

| | | | | | |
|-------------------|--|------------|-------------|---------------|--------------|
| Sensor | 1/3", 4.0 megapixel, progressive scan, CMOS | | | | |
| Min Illumination | Color: 0.01 Lux (F2.0 AGC ON) 0Lux with IR | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| Shutter | Auto/Manual, 1 ~ 1/100000s | | | | |
| Adjustment angle | Pan: 0° ~ 360°, Tilt: 0° ~ 75°, Rotate: 0° ~ 360° | | | | |
| S/N | >56dB | | | | |
| WDR | 100dB | | | | |
| Lens Type | 2.8mm @2.0 | | | | |
| Lens Mount | M12 | | | | |
| Angle of View (H) | 97.0° | | | | |
| Angle of View (V) | 52.2° | | | | |
| Angle of View (D) | 107.5° | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 2.8 | 63.0 | 25.2 | 12.6 | 6.3 |
| IR Range | 30-50m IR range | | | | |
| Wavelength | 850nm | | | | |
| IR On/Off Control | Auto/Manual | | | | |
| Frame Rate | Main Stream: 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps; 720P (1280*720), Max 30fps Sub Stream: 4CIF (704*576), Max 30fps; 640*360, Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; | | | | |
| Video Bit Rate | 128 Kbps-6144 kbps | | | | |
| OSD | Up to 4 OSDs | | | | |
| Privacy Mask | Up to 4 areas | | | | |
| ROI | Up to 8 areas | | | | |
| Motion Detection | Up to 4 areas | | | | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 | | | | |
| Smart Features | Cross Line, Intrusion detection (based on human body detection) | | | | |
| Image Setting | Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser | | | | |

| | |
|-------------------------|--|
| Digital noise reduction | 2D/3D DNR |
| Smart IR | Supported |
| Flip | Normal/Vertical/Horizontal/180° |
| Dewarping | N/A |
| HLC | Supported |
| BLC | Supported |
| Defog | Digital Defog |
| Edge Storage | Micro SD, up to 128GB |
| Network Storage | ANR, NAS(NFS) |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL/TLS, SNMP |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API, SDK |
| Security | Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF ONVIF (Profile S, Profile G, Profile T), API |
| Web Browser | Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ |
| Network | 1 * RJ45 10M/100M Base-TX Ethernet |
| Power | DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4.0W |
| Dimensions (Ø x H) | Ø118 x 97mm (Ø4.6" x 3.8") |
| Weight | 0.30kg (0.66lb) |
| Material | Metal + Plastic |
| Working Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Storage Environment | -30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing) |
| Surge Protection | 4KV |
| Reset Button | N/A |
| Ingress Protection | Ingress protection: IP67 |

Dimensions

