

IPC-P1A4W-I50S

4MP LightHunter Intelligent Bullet Network Camera



قابلیت های کلیدی

- قابلیت روز و شب
- IR هوشمند 50 تا 80 متر
- کاهنده نویز دیجیتال 3D

- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- OSD قابل تنظیم

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

Sensor	1/2.7", 4.0 megapixel, progressive scan, CMOS					BLC	Support
Lens	2.7-13.5mm@F1.2, AF automatic focusing and motorized zoom lens					Smart Features	Cross line detection, intrusion detection, Enter area, Leave area, Face Capture (maximum 8), People counting(Deep Learning), People flow counting and Crowd density monitoring, object removed, object left behind
Iris	Auto aperture					General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Audio Compression	G.711U,G.711A
	2.7	70.9(232.5ft)	28.4(93.0ft)	14.2(46.5ft)	7.1(23.3ft)	Two way audio	Supported
	13.5	247.5(812.0ft)	99.0(324.8ft)	49.5(162.4ft)	24.8(81.2ft)	Sampling Rate	8KHZ
Angle of View (H)	26.0°-92.0°					Edge Storage	Micro SD, up to 256 GB
Angle of View (V)	15.0°-53.9°					Network Storage	ANR,NAS(NFS)
Angle of View (D)	30.7°-119.6°					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP
Shutter	Auto/Manual, 1 - 1/100000s					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Minimum Illumination	Colour:0.002lux (F1.2, A6C ON) 0 lux with IR					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
WDR	120dB					Audio I/O	Audio cable 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 output: impedance 600Ω; amplitude 2V [p-p]
Day/Night	IR-cut filter with auto switch (ICR)					Alarm I/O	1/1
S/N	>56dB					Network	1 x RJ45 10M/100M Base-TX Ethernet
IR Range	50-80m IR range					Power	DC12V(±25%), PoE(IEEE802.3af) Power consumption: Max 10W Support overcurrent protection and input short circuit protection
Wavelength	850nm					Dimensions (Ø x H)	Ø245.0x86.0x72.0mm(Ø9.6"x3.4"x2.8")
IR On/Off Control	Auto/Manual					Net Weight	0.98kg(2.16lb)
Defog	Digital Defog					Material	Metal
Frame Rate	Main Stream: 4MP(2688*1520),Max 30fps; 4MP(2560*1440),Max 30fps; 3MP(2304*1296),Max 30fps; 2MP(1920*1080),Max 30fps;					Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
	Sub Stream: 2MP (1920*1080), Max 30fps;					Storage Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
	Third Stream: D1 (720*576), Max 30fps					Surge protection	6KV
Video Bit Rate	128 Kbps-16 Mbps					Vandal Resistant	IK10
ROI	Supported					Ingress Protection	IP67
OSD	Up to 8 OSDs						
Privacy Mask	Up to 8 areas(8 blacks/8 mosaics)						
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2						
Digital noise reduction	2D/3D DNR						
Smart IR	Support						
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise						
HLC	Support						

Dimensions

