

IPC-P1A5W-I50S

5MP Network IR Bullet Camera



قابلیت های کلیدی

- قابلیت شب و روز
- IR هوشمند 50 تا 80 متر
- کاهنده نویز دیجیتال 3D
- Ultra H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

| | | | | | |
|-------------------------|--|------------|----------------|-------------------|--------------|
| Sensor | 1/2.7", 5.0 megapixel, progressive scan, CMOS | | | | |
| Lens | 2.8 - 12mm, AF automatic focusing and motorized zoom lens | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) |
| | 2.8 | 63 | 25.2 | 12.6 | 6.3 |
| Angle of View (H) | 96.23° - 31.69° | | | | |
| | 69.98° - 24.28° | | | | |
| Angle of View (V) | 125.10° - 37.39° | | | | |
| Angle of View (D) | 125.10° - 37.39° | | | | |
| Adjustment angle | Pan: 0° - 360° | | Tilt: 0° - 90° | Rotate: 0° - 360° | |
| Shutter | Auto/Manual, 1 - 1/100000s | | | | |
| Minimum Illumination | Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on | | | | |
| Day/Night | IR-cut filter with auto switch (ICR) | | | | |
| Digital noise reduction | 2D/3D DNR | | | | |
| S/N | >56 dB | | | | |
| IR Range | 50-80m IR range | | | | |
| Wavelength | 850nm | | | | |
| IR On/Off Control | Auto/Manual | | | | |
| Defog | Digital Defog | | | | |
| WDR | 120dB | | | | |
| Video Compression | Ultra 265, H.265, H.264, MJPEG | | | | |
| H.264 code profile | Baseline profile, Main Profile | | | | |
| Frame Rate | Main Stream: 5MP (2592*1944), Max 20fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps; Sub Stream: 4CIF (704*576), Max 30fps; Third Stream: CIF (352*288), Max 30fps | | | | |
| Video Bit Rate | 128 Kbps-16 Mbps | | | | |
| OSD | Up to 4 OSDs | | | | |
| Privacy Mask | Up to 4 areas | | | | |
| ROI | Up to 2 areas | | | | |
| Motion Detection | Up to 4 areas | | | | |
| Smart Features | Tampering detection, Audio detection, Intrusion detection, Human body detection | | | | |
| White Balance | Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2 | | | | |
| Digital noise reduction | 2D/3D DNR | | | | |
| Smart IR | Support | | | | |
| Flip | Normal/Vertical/Horizontal/180° | | | | |
| Dewarping | NA | | | | |
| HLC | Supported | | | | |
| BLC | Supported | | | | |
| Audio Compression | G.711 | | | | |
| Suppression | Supported | | | | |
| Sampling Rate | 8KHZ | | | | |
| Edge Storage | Micro SD, up to 256GB | | | | |
| Network Storage | ANR | | | | |
| Protocols | IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL | | | | |
| Compatible Integration | ONVIF (Profile S, Profile G, Profile T), API | | | | |
| Web Browser | Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+ | | | | |
| Audio I/O | Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p] | | | | |
| Alarm I/O | 1/1 | | | | |
| Network | 1 RJ45 10M/100M Base-TX Ethernet | | | | |
| Certifications | CE: EN 60950-1 | | | | |
| | UL: UL60950-1 | | | | |
| | FCC: FCC Part 15 | | | | |
| Power | DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 9.5W | | | | |
| Dimensions (L × W × H) | 240.3 × 86.4 × 75.6mm (9.5" × 3.4" × 3.0") | | | | |
| Net Weight | 1.0kg (2.2lb) | | | | |
| Material | Metal | | | | |
| Working Environment | -30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing) | | | | |
| Storage Environment | -30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing) | | | | |
| Surge Protection | 6KV | | | | |
| Ingress Protection | IP67 | | | | |

Dimensions

