

IPC-P1F4W-I30 4.0mm

4MP SD Card Mini Fixed Bullet Network Camera



Network Cameras
NVRs
AHD Series
Video Decoders
Switches
Accessories

قابلیت های کلیدی

- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- شیشه ضد بازتاب نور مادون قرمز
- پشتیبانی از کارت حافظه SD
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از حالت راهرو 9:16
- قابلیت روز و شب
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -35 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

sensor	1/3", 4.0 megapixel, progressive scan, CMOS					9:16 Corridor Mode	Supported
Lens	4.0mm@F2.0					HLC	Supported
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	BLC	Supported
	4.0	90	36	18	9	OSD	Up to 8 OSDs
Angle of View (H)	78.9°					Privacy Mask	Up to 8 areas
Angle of View (V)	39.6°					ROI	Up to 8 areas
Angle of View (D)	97.0°					Motion Detection	Up to 4 areas
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 90°		Rotate: 0° - 360°	Smart Features	Cross line, intrusion, object left, object removed, People Counting, Face capture
Shutter	Auto/Manual, 1 - 1/100000s					Edge Storage	Micro SD, Up to 128GB
Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on					Network Storage	ANR
Day/Night	IR-cut filter with auto switch (ICR)					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Digital noise reduction	2D/3D DNR					Compatible Integration Network	ONVIF (Profile S, Profile G, Profile T), API 1 RJ45 10M/100M Base-TX Ethernet
S/N	>52dB					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 6.5W
IR Range	30-50m IR range					Dimensions (L x W x H)	157.3 x 62.4 x 63mm (6.2" x 2.5" x 2.5")
Defog	Digital Defog					Weight	0.45kg (0.99lb)
WDR	120dB					Working Environment	-35°C ~ 60°C (-31°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Video Compression	Ultra 265, H.265, H.264, MJPEG					Ingress Protection	IP67
H.264 code profile	Baseline profile, Main Profile, High Profile					Reset Button	Supported
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; 4MP (2560*1440), Max 25fps; 3MP (2048*1520), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps						

Dimensions

