

## IPC-P1F5W-I30S

5MP SD Card Mini Fixed Bullet Network Camera



### قابلیت های کلیدی

- قابلیت شب و روز
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- Ultra H.265، H.264، MJPEG
- دارای میکروفن داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

### Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS					White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	
Lens	2.8mm@F2.0					Digital noise reduction	2D/3D DNR	
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Smart IR	Support	
	2.8	63.1	25.2	12.6	6.3	Flip	Normal/Vertical/Horizontal/180°	
Angle of View (H)	105.6°					Dewarping	NA	
Angle of View (V)	69.9°					HLC	Supported	
Angle of View (D)	137.3°					BLC	Supported	
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°		Rotate: 0° ~ 360°	Audio Compression	G.711	
Shutter	Auto/Manual, 1 ~ 1/100000s					Suppression	Supported	
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON)					Sampling Rate	8KHZ	
	0Lux with IR on					Edge Storage	Micro SD, up to 256GB	
Day/Night	2D/3D DNR					Network Storage	ANR	
Digital noise reduction	IR-cut filter with auto switch (ICR)					Protocols	IPV4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SSL	
S/N	>56dB					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API	
IR Range	30-50m IR range					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+	
Wavelength	850nm					Network	1 RJ45 10M/100M Base-TX Ethernet	
IR On/Off Control	Auto/Manual					Built-in Mic	Supported	
Defog	Digital Defog					Certifications	CE: EN 60950-1	
WDR	120dB						UL: UL60950-1	
Video Compression	Ultra 265, H.265, H.264, MJPEG					FCC: FCC Part 15		
H.264 code profile	Baseline profile, Main Profile					Power	DC 12V±25%, PoE (IEEE 802.3af)	
Frame Rate	Main Stream: 5MP (2592*1944), Max 20fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps;					Dimensions (L x W x H)	165 x 63.1 x 62.5mm (6.5" x 2.5" x 2.5")	
	Sub Stream: 4CIF (704*576), Max 30fps;						Net Weight	0.45kg (0.99lb)
	Third Stream: CIF (352*288), Max 30fps						Material	Metal
Video Bit Rate	128 Kbps-16 Mbps					Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)	
OSD	Up to 4 OSDs					Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)	
Privacy Mask	Up to 4 areas					Surge Protection	2KV	
ROI	Up to 2 areas					Ingress Protection	IP67	
Motion Detection	Up to 4 areas							
Smart Features	Tampering detection, Audio detection, Intrusion detection, Human body detection							

### Dimensions

