

IPC-P1F5W-I80S 4.0mm

5MP HD 80m IR Fixed Bullet Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- پشتیبانی از حالت راهرو 9:16
- IR هوشمند 80 تا 100 متر
- کاهنده نویز دیجیتال 3D
- Ultra265, H.265, H.264, MJPEG
- دارای 2 عدد میکروفون داخلی
- پشتیبانی از ROI
- OSD قابل تنظیم

Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Minimum Illumination	Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, 1 - 1/100000s				
Adjustment angle	Pan: 0° - 360°	Tilt: 0° - 90°	Rotate: 0° - 360°		
WDR	120dB				
S/N	>56dB				
Lens	4.0mm@F1.0				
Angle of View (H)	91.2°				
Angle of View (V)	47.9°				
Angle of View (D)	95.9°				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0	90.0	36.0	18.0	9.0
IR Range	80-100m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264code profile	Baseline profile, Main profile, High profile				
Frame Rate	Main Stream:5MP (2880*1620), Max 30fps; 4MP (2560*1440), Max 30fps; 3MP (2304*1296), Max 30fps; 1080P (1920*1080), Max 30fps;				
	Sub Stream: 720P (1280*720), Max 30fps; D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps; Third Stream: D1 (720*576), Max 30fps; 640*360,Max 30fps; 2CIF(704*288), Max 30fps; CIF(352*288), Max 30fps;128 Kbps-16 Mbps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Up to 8 areas				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 4 areas				
Smart Features	Audio detection, Deep Learning,Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 8)				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser				
Digital Noise Reduction	2D/3D DNR				
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise				
Dewarping	N/A				
HLC	Supported				
BLC	Supported				
Defog	Digital Defog				
Audio Compression	G.711				
Audio Bitrate	64 Kbps				
Suppression	Supported				
Sampling Rate	8KHZ				
Edge Storage	Micro SD, up to 256GB				
Network Storage	ANR, NAS(NFS)				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS, SSH				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API , SDK				
User/Host	Up to 32 users. 2 user levels: administrator and common user				
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+				
Audio I/O	N/A				
Alarm I/O	1/1				
RS485	N/A				
Built-in Mic	Support 2				
Built-in Speaker	N/A				
Network	1 RJ45 10M/100M Base-TX Ethernet				
Video Output	N/A				
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 7.0 W				
Dimensions (L x W x H)	206 x 74 x 74mm (8.1" x 2.9" x 2.9")				
Weight	0.51kg (1.12lb)				
Material	Metal				
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)				
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)				
Surge Protection	4KV				
Reset Button	Supported				
Protection	Ingression protection: IP67				

Dimensions

