

IPC-P2A2W-I30S

2MP WDR VF Vandal-resistant IR Dome Network Camera



قابلیت های کلیدی

- قابلیت روز و شب
- IR هوشمند 30 تا 60 متر
- کاهنده نویز دیجیتال 3D
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت

Specifications

Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS				
Lens	2.8 - 12mm, AF automatic focusing and motorized zoom lens				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	43.4	17.4	8.7	4.3
	12	186.2	74.5	37.2	18.6
Angle of View (H)	94.0° - 28°				
Angle of View (V)	56.7° - 14.4°				
Angle of View (D)	122.2° - 34.4°				
Adjustment angle	Pan: 0° - 360°		Tilt: 0° - 90°		Rotate: 0° - 360°
Shutter	Auto/Manual, 1 - 1/100000s				
Minimum Illumination	Colour: 0.002Lux (F1.6, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	30-60m IR range				
Defog	Digital Defog				
WDR	120dB				
Video Compression	Ultra 265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 2MP (1920*1080), Max 30fps;				
	Sub Stream: 2MP (1920*1080), Max 30fps;				
	Third Stream: D1 (720*576), Max 30fps				
HLC	Supported				
BLC	Supported				
9:16 Corridor Mode	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				
Smart Features	Audio detection, Cross line, intrusion, object left, object removed, People counting, Face capture				
Audio Compression	G.711				
Two-way audio	Supported				
Suppression	Supported				
Sampling Rate	8KHZ				
Edge Storage	Micro SD, up to 256GB				
Network Storage	ANR				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Audio I/O	Audio cable				
	Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]				
Alarm I/O	1/1				
Network	1 RJ45 10M/100M Base-TX Ethernet				
Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]				
Power	DC 12V±25%, PoE (IEEE 802.3af)				
	Power consumption: Max 7.2W				
Dimensions (Ø x H)	Ø148 x 111.3mm (Ø5.8" x 4.4")				
Weight	0.92kg (2.0lb)				
Working Environment	-40°C - 60°C (-40°F - 140°F), Humidity: ≤95% RH (non-condensing)				
Ingress Protection	IP67				
Vandal Resistant	IK10				
Reset Button	Supported				

Dimensions

