

IPC-P2A4WH-I40S

4MP LightHunter Intelligent Vandal-resistant Dome Network Camera



قابلیت های کلیدی

- پشتیبانی از 5 استریم تصویر
- IR هوشمند 40 تا 70 متر
- کاهنده نویز دیجیتال 3D

- پایه لنز قابل تنظیم 3 حالت
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

Sensor	1/1.8", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8-12mm@F1.2, AF automatic focusing and motorized zoom lens				
Iris	Auto aperture				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	42(137.8ft)	16.8(55.1ft)	8.4(27.6ft)	4.2(13.8ft)
DORI Distance	12	180(590.4ft)	72(236.2ft)	36(118.1ft)	18(59.0ft)
Angle of View (H)	35.6°-107.9°				
Angle of View (V)	20.4°-75.4°				
Angle of View (D)	43.8°-140.3°				
Shutter	Auto/Manual, 1 - 1/100000s				
Adjustment angle	Pan: 0°-355°		Tilt: 0°-68°		Rotate: 0°-355
Min. Illumination	Colour:0.0005lux (F1.2, AGC ON) 0 lux with IR				
WDR	120dB				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>55dB				
IR Range	40-70m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
Video Compression	Ultra 265,H.265,H.264,MJPEG				
Frame Rate	Main Stream: 4MP(2688*1520),Max 30fps; 4MP(2560*1440),Max 30fps; 2MP(1920*1080), Max 60fps				
	Sub Stream: 2MP (1920*1080), Max 60fps;				
	Third Stream: D1 (720*576), Max 60fps				
	Fourth Stream: D1 (720*576), Max 60fps				
	Fifth Stream: D1 (720*576), Max 60fps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas (8 blacks/8 mosaics)				
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture, (Maximum 40)				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				
HLC	Support				
BLC	Support				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Audio Compression	G.711U,G.711A				
Two way audio	Supported				
Sampling Rate	8KHZ				
Edge Storage	Micro SD, up to 256 GB				
Network Storage	ANR,NAS(NFS)				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP				
Compatible Integration	ONVIF, API				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below				
Audio I/O	Audio cable				
	1 Input: impedance 35kΩ; amplitude 2V *p-p] 1 output: impedance 600Ω; amplitude 2V *p-p]				
Alarm I/O	1/1				
Network	1 x RJ45 10M/100M Base-TX Ethernet				
Power	AC24V±25%, DC12V(±25%), PoE(IEEE 802.3af)				
	Power consumption: Max 10W Support overcurrent protection , Input short circuit protection				
Dimensions (Ø x H)	Ø148 x 111.3mm(Ø5.8" x 4.4")				
Net Weight	0.96kg(2.12lb)				
Material	Metal				
Working Environment	-30°C-60°C(-22°F - 140°F), Humidity: ≤95% RH (non-condensing)				
Surge Protection	6KV				
Vandal Resistant	IK10				
Ingress Protection	IP67				
Reset Button	Supported				

Dimensions

