

# IPC-P2F4W-I50S

4MP LightHunter Deep Learning Vandal-resistant Dome Network Camera



## قابلیت های کلیدی

- قابلیت شب و روز
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه لنز قابل تنظیم 3 حالت

## Specifications

Sensor	1/2.7", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8-4.0mm@F1.6				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0(206.7ft)	25.2(82.7ft)	12.6(41.7ft)	6.3(20.7ft)
Angle of View (H)	4.0	90.0(295.3ft)	36.0(118.1ft)	18.0(59.1ft)	9.0(29.5ft)
	95.8°-78.9°				
Angle of View (V)	51.5°-40.8°				
Angle of View (D)	124.5°-97.0°				
Adjustment angle	Pan: 0°-355°		Tilt: 0°-80°	Rotate: 0°-355°	
Shutter	Auto/Manual, 1 - 1/100000s				
Minimum Illumination	Colour: 0.003lux (F1.6, AGC ON) 0 lux with IR				
WDR	120dB				
Day/Night	IR-cut filter with auto switch (ICR)				
IR Range	Up to 50m (164 ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
Frame Rate	Main Stream: 4MP(2688*1520), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Supported				
Privacy Mask	Up to 8 areas(8 blacks/8 mosaics)				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				
HLC/BLC	Support				
Smart intrusion prevention	Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection				
Recognition	Face capture Support face detection masked area				
Statistical Analysis	People counting, support people flow counting and crowd density monitoring				
Basic Detection	Motion detection, Audio detection, Tampering alarm				
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Audio Compression	G.711U,G.711A				
Two-way Audio	Supported				
Suppression	Supported				
Sampling Rate	8KHZ				
Edge Storage	Micro SD, up to 256 GB				
Network Storage	ANR,NAS(NFS)				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Client	EZStation EZLive Ezview				
Audio I/O	Audio cable 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 output: impedance 600Ω; amplitude 2V [p-p]				
Network	1 * RJ45 10M/100M Base-TX Ethernet				
Certifications	CE: EN 60950-1 UL: UL 60950-1 FCC: FCC Part 15				
Power	DC12V(±25%), PoE(IEEE 802.3af) Power consumption: Max 5W				
Dimensions (Ø x H)	Ø109 x 81mm(Ø4.3" x 3.2")				
Weight	0.43kg(0.95lb)				
Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)				
Storage Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)				
Surge protection	2KV				
Vandal Resistant	IK10				
Ingress Protection	IP67				

## Dimensions

