

## IPC-P2F8W-I50S

8MP LightHunter Dome Network Camera



### قابلیت های کلیدی

- پشتیبانی از 3 استریم تصویر
- IR هوشمند 50 تا 70 متر
- کاهنده نویز دیجیتال 3D

- پایه لنز قابل تنظیم 3 حالت
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از ROI
- OSD قابل تنظیم

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

### Specifications

Sensor	1/2.8", 8.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F1.6				
Iris	Fixed				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	86.9(285.1ft)	34.8(114.0ft)	17.4(57.0ft)	8.7(28.5ft)
Angle of View (H)	96.6°				
Angle of View (V)	50.8°				
Angle of View (D)	125.6°				
Shutter	Auto/Manual, 1 - 1/100000s				
Adjustment angle	Pan: 0°-355°	Tilt: 0°-80°	Rotate: 0°-355°		
	Colour: 0.003lux (F1.6, AGC ON)				
Min. Illumination	0Lux with IR				
WDR	120dB				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>56dB				
IR Range	50-70m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
Frame Rate	Main Stream: 8MP(3840*2160), Max 20fps;				
	Sub Stream: 2MP (1920*1080), Max 30fps;				
	Third Stream: D1 (720*576), Max 30fps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 8 areas(8 blacks/8 mosaics)				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				

HLC	Supported
BLC	Supported
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Smart Features	Audio detection, Scene Change Detection, Object Left, Object removed, Deep Learning, Smart Intrusion Prevention, (Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 10)
Audio Compression	G.711U, G.711A
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR, NAS(NFS)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Audio I/O	Audio cable 1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	1/1
Network	1 * RJ45 10M/100M Base-TX Ethernet
Power	DC12V(±25%), PoE(IEEE 802.3af) Power consumption: Max 5W
Dimensions (Ø x H)	Ø109 x 81mm(Ø4.3" x 3.2")
Weight	0.43kg(0.95lb)
Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
surge protection	2KV
Vandal Resistant	IK10
Ingress Protection	IP67

### Dimensions

