

IPC-P7F5W-I10

5MP Fisheye Fixed Dome Network Camera



قابلیت های کلیدی

- رزولوشن 5 مگاپیکسل
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +60 درجه سانتیگراد
- قابلیت جبران خمیدگی لبه های تصویر
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- تصویر عریض 360 درجه
- IR هوشمند تا 10 متر با پوشش 360 درجه
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/2.8", progressive scan, 5.0 megapixel, CMOS				
Lens	1.4mm@F2.0				
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	1.4 mm	31.5	12.6	6.3	3.2
Angle of View	360°				
Shutter	Auto/Manual, shutter time: 1-1/100000 s				
Minimum Illumination	Colour: 0.01 Lux (F2.0, AGC ON)				
	0 Lux with IR				
Day/Night	IR-cut filter for day & night function				
S/N	>55dB				
IR Range	UP to 10m (33ft)				
wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	120dB				
Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: (2592×1944): Max.30fps;				
	Sub Stream: (1920×1080): Max.30fps;				
	Third Stream: D1(720 x 576): Max.30 fps				
Video Bit Rate	128 Kbps-16 Mbps				
OSD	Up to 8 OSDs				
ROI	Up to 8 areas				
Privacy Mask	Up to 8 areas				
Motion Detection	Up to 4 areas				
Smart Features	heat map				
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output,				
	Access Policy, ARP Protection, RTSP Authentication, User Authentication				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Flip Vertical/ Flip Horizontal/180°				
Dewarping	N/A				
HLC	N/A				
BLC	Support				
Audio Compression	N/A				
Two-way audio	N/A				
Suppression	N/A				
Sampling Rate	N/A				
Edge Storage	Micro SD, up to 256GB				
Network Storage	ANR, NAS(NFS)				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below				
	Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+				
Mount Type	Support table, wall, and ceiling				
Audio I/O	N/A				
Alarm I/O	N/A				
Built-in Mic	N/A				
Video Output	N/A				
Network	1 RJ45 10M/100M Base-TX Auto-adaptive Ethernet				
Certifications	CE: EN 60950-1				
	UL: UL60950-1				
	FCC: FCC Part 15				
Power	DC12V±25%,PoE (IEEE 802.3af)				
	Power consumption: Max. 8.9 W				
Dimensions (Φ × H)	Φ125 × 43.7 mm (Φ4.9" × 1.7")				
Net Weight	0.39kg (0.86lb)				
Material	Metal + Plastic				
Working Environment	-40°C-60°C (-40°F-140°F), Humidity: ≤95% RH				
Storage Environment	-40°C-60°C (-40°F-140°F), Humidity: ≤95% RH				
surge protection	6KV				
Ingress Protection	IP66				
Vandal Resistant	IK10				
Reset Button	Supported				

Dimensions

