

IPX-A1A4W-I100S

4MP 33X IR Explosion-Proof Bullet Network Camera



قابلیت های کلیدی

- زوم اپتیکال تا 33 برابر بزرگ نمایی
- OSD قابل تنظیم
- IR هوشمند 100 تا 120 متر
- کاهنده نویز دیجیتال 3D
- بدنه استیل ضد زنگ 304
- Exd IIC T6 Gb/ Ex tD A21 IP68 T80°C Standard
- پشتیبانی از ROI
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -35 تا +70 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP68

Specifications

Sensor	1/1.8", 4.0 megapixel, progressive scan, CMOS			
Lens	6.5 - 214.5 mm, AF automatic focusing and motorized zoom lens			
Optical Zoom	33			
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)
	6.5mm	98.7(323.8ft)	39.5(129.5ft)	19.7(64.8ft)
Angle of View (H)	214.5mm	3256.8(10684.9ft)	1302.7(4274.0ft)	651.4(2137.0ft)
	60.0°		2.7°	
Angle of View (V)	36.0°		1.5°	
Angle of View (D)	73.8°		3.2°	
Shutter	Auto/Manual, 1-1/100000 s			
Minimum Illumination	Colour: 0.001 Lux (F1.5, AGC ON) 0 lux with IR			
Iris	Auto/Manual, F1.5-F3.4			
Digital noise reduction	2D/3D DNR			
Day/Night	IR-cut filter with auto switch (ICR)			
S/N	>56dB			
WDR	120dB			
IR Range	100-120m IR range			
Wavelength	850nm			
IR On/Off Control	Auto/Manual			
Video Compression	H.265, H.264, MJPEG			
Frame Rate	Main Stream: 4MP (2688*1520): Max. 30 fps;			
	Sub Stream: 2MP (1920*1080): Max. 30 fps;			
	Third Stream: D1 (720*576): Max. 30 fps;			
Video Bit Rate	128 Kbps-16 Mbps			
OSD	Time, Custom, Zoom, Serial port, Network port, Picture overlay, People counting			
Privacy Mask	Up to 4 areas per scene			
ROI	Up to 8 areas			
Smart intrusion prevention	Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection			
Face capture	Support, Face attributes: Gender, Age range, Glasses, Mask			
People counting	Support people flow counting and crowd density monitoring			
Basic Detection	Motion detection, Audio detection, Tampering alarm			
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication			
Audio Compression	G.711U, G.711A			
Audio Bitrate	64 Kbps			
Two-way Audio	Support			
Suppression	Support			
Sampling Rate	8kHz			
Edge Storage	Micro SD, up to 256 GB (Built-in SD card is available for customization)			
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS			
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK			
Audio I/O	1/1			
Alarm I/O	2/1			
Serial Port	Support			
Built-in Heater	N/A			
Network	10/100M Base-TX Ethernet			
Power	AC220V(100-240V) Power consumption: Max 18W			
Dimensions (L x W x H)	377mmx145mmx247mm (14.8" x 5.7" x 9.7")			
Weight	7.95kg (17.5lb)			
Working Environment	-35°C ~ +70°C (-31°F ~ 158°F), Humidity: ≤95% RH(non-condensing)			
Ingress Protection	IP68			

Dimensions

