

# IPX-A1F5W-I30

5MP IR Fixed Explosion-Proof Bullet Network Camera



## قابلیت های کلیدی

- OSD قابل تنظیم
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- بدنه استیل ضد زنگ 304
- Exd IIC T6 Gb/ Ex tD A21 IP68 T80°C
- پشتیبانی از ROI
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP68

## Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS					OSD	Up to 8 OSDs
Lens	4mm					Privacy Mask	24 areas, up to 4 areas per scene
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	ROI	Up to 8 areas
	4.0mm	90.0	36.0	18.0	9.0	Behavior Detection	Motion detection, Tampering Detection
Angle of View (H)	91.8°					Smart intrusion	Support false alarm filtering: Line crossing detection, Intrusion detection, Region entrance detection, Region exit detection
Angle of View (V)	46.4°					Prevention	
Angle of View (D)	119.3°					Recognition	Face capture
Shutter	Auto/Manual, 1-1/100000 s					Protocols	L2TP, IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, DNS, DDNS, NTP, FTP, UPnP, HTTP, SNMP, HTTPS, SIP, RTMP
Minimum Illumination	Colour: 0.003 Lux (F1.6, AGC ON)					Compatible Integration	ONVIF, GB/T28181, IMOS, API
	BW: 0.002 Lux (F1.6, AGC ON)					Network	10/100M Base-TX Ethernet
WDR	120dB					Power	DC12V(±25%), PoE(IEEE802.3af)
Iris	Auto/Manual, F1.6						Power consumption: 4.3W
Day/Night	IR-cut filter with auto switch (ICR)					Dimensions (L x W x H)	134 x 114 x 115 mm (5.3" x 4.5" x 4.5")
IR Range	30-50m IR Range					Weight	2.07kg (4.56lb)
S/N	>56dB					Working Environment	-30°C ~ +60°C (-22°F ~ 140°F), Humidity :5%-95% RH(non-condensing)
Video Compression	H.265, H.264, MJPEG					Ingress Protection	IP68
Frame Rate	Main Stream:5MP (2880*1620): Max 30 fps;						

## Dimensions

