

IPZ-A8245WH-I250S

2MP 45X Lighthunter IR Network PTZ Dome Camera



Network
Cameras

NVRs

AHD
Series

Video
Decoders

Switches

Accessories

قابلیت های کلیدی

- رزولوشن 2 مگاپیکسل
- پشتیبانی از پروتکل ONVIF
- فوکوس دقیق و سریع
- طراحی مؤثر دفع گرما
- IR هوشمند تا 250 برابر
- پشتیبانی از 3 استریم تصویر
- تکنولوژی کنترل دمای هوشمند
- OSD قابل تنظیم
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- زوم اپتیکال تا 45 برابر بزرگ نمایی
- PoE++(IEEE 802.3bt)

Specifications

Sensor	1/1.8", 2.0 megapixel, progressive scan, CMOS				
Minimum Illumination	Colour: 0.0005Lux (F1.3, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, 1 - 1/100000s				
WDR	120dB				
S/N	>52dB				
Lens type	5.7 - 256.5mm, AF automatic focusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	45				
Iris	Auto; F1.3 - F4.6				
Angle of View (H)	59.5° - 2.2°				
Angle of View (V)	35.6° - 1.2°				
Angle of View (D)	73.2° - 2.6°				
DDRI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	5.7	107.2(351.8ft)	42.9(140.7ft)	21.4(70.4ft)	10.7(35.2ft)
IR Range	256.5	3330.6(10927.2ft)	1332.2(4370.9ft)	666.1(2185.4ft)	333.1(1092.7ft)
	Up to 250m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Frame Rate	Main Stream: 2MP (1920*1080), Max 60fps;				
	Sub Stream: 2MP (1920*1080), Max 60fps;				
	Third Stream: D1 (720*576), Max 60fps				
Video Bit Rate	128 Kbps-16 Mbps				
ROI	Up to 8 areas				
OSD	Up to 8 OSDs				
Privacy Mask	24 areas, up to 4 areas per scene				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise				
EIC	Support				
HLC	Support				
BLC	Support				
Defog	Optical Defog & Digital Defog				
Smart Features	Deep learning, Smart intrusion Prevention Line Crossing, intrusion detection, Region entrance detection, Region exit detection, People flow counting and Crowd density monitoring, Face Capture (Maximum 40), Auto tracking (Deep learning), Audio Detection				
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication				
Audio Compression	G.711U, G.711A				
Audio Bitrate	64 Kbps				
Two-way audio	Support				
Suppression	Support				
Sampling Rate	8 kHz				
Edge Storage	Micro SD, up to 256GB				
Network Storage	ANR, NAS(NFS)				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS				
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK				
User/Host	Up to 32 users, 2 user levels: administrator and common user				
Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+				
Pan Range	360° (endless)				
Pan Speed	0.1°/s - 180°/s Preset speed: 300°/s				
Tilt Range	-15° - 90° (auto reverse)				
Tilt Speed	0.1°/s - 180°/s Preset speed: 240°/s				
Number of Presets	1024				
Preset Patrol	16 patrols, up to 64 presets for each patrol				
Route Patrol	16 patrols, up to 32 actions for each patrol				
Recorded Patrol	16 patrols, up to 128 actions for each patrol				
Patrol Stay Time	15s-1800s				
Preset Image Freeze	Support				
Home Position	Support				
Audio I/O	1/1				
Alarm I/O	7/2				
Serial Port	1 RS485				
Network	1 RJ45 10M/100M Base-TX Ethernet				
Video output	N/A				
Power	AC 24V ±25%, DC 24V±25%, PoE++ (IEEE 802.3bt) Power consumption: Max 61W				
Dimensions (Ø x H)	Ø270 x 497mm (Ø10.6" x 19.6")				
Weight	10.3kg(22.66lb)				
Working Environment	-40°C - 70°C (-40°F - 158°F), Humidity: ≤95% RH (non-condensing)				
Surge Protection	6KV				
Reset Button	Support				
Protection	Ingress Protection: IP66 Vandal Resistant: N/A				

Dimensions

