

IPZ-P4425W-I100S

4MP 25x Lighthunter Network PTZ Dome Camera



Network
Cameras

NVRs

AHD
Series

Video
Decoders

Switches

Accessories

قابلیت های کلیدی

- رزولوشن 4 مگاپیکسل
- زوم اپتیکال تا 25 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق تر و سریع
- IR هوشمند تا 100 متر
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +70 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- بدنه ضد ضربه با استاندارد IK10
- رزولوشن 4 مگاپیکسل
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم

Specifications

Sensor	1/2.8", 4.0 megapixel, progressive scan, CMOS					Audio Compression	6.711U,6.711A
Minimum Illumination	Colour: 0.003 Lux (F1.5, AGC ON) 0 Lux with IR					Two-way Audio	Support
Day/Night	IR-cut filter with auto switch (ICR)					Suppression	Support
Shutter	Auto/Manual, 1 - 1/100000s					Sampling Rate	8 kHz
WDR	120dB					Edge Storage	Micro SD, up to 256 GB
S/N	>56dB					Network Storage	ANR,NAS(NFS)
Lens type	4.8 - 120mm, AF automatic focusing and motorized zoom lens					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP,SSL/TLS
Digital Zoom	16					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API,SDK
Optical Zoom	25					User/Host	Up to 32 users. 2 user levels: administrator and common user
Iris	Auto; F1.5 - F3.8					Security	Password protection, strong password, HTTPS encryption, Export operation logs, basic and digest authentication for RTSP, digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Angle of View (H)	52.20°-2.74°					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Angle of View (V)	30.81°-1.54°					Pan Range	360° (endless)
Angle of View (D)	64.20°-3.23°					Pan Speed	0.1°/s - 200°/s Preset speed: 240°/s
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Tilt Range	-15° - 90° (auto reverse)
	4.8	119.3(391.2ft)	47.7(156.5ft)	23.9(78.2ft)	11.9(39.1ft)	Tilt Speed	0.1°/s - 200°/s Preset speed: 200°/s
IR Range	Up to 100m IR range					Number of Presets	1024
Wavelength	850nm					Preset Patrol	16 patrols, up to 64 presets for each patrol
IR On/Off Control	Auto/Manual					Patrol Stay Time	15s-1800s
Video Compression	Ultra 265, H.265, H.264, MJPEG					Home Position	Support
Frame Rate	Main Stream: 4MP(2688*1520),Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps;					Audio I/O	1/1
Video Bit Rate	128 Kbps-16 Mbps					Alarm I/O	2/1
ROI	Support					Serial Port	1 RS485
OSD	Up to 8 OSDs					Network	1 * RJ45 10M/100M Base-TX Ethernet
Privacy Mask	24 areas, up to 4 areas per scene					Video Output	1 BNC
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2					Power	DC12V(±25%,3A), PoE+(IEEE 802.3at) Power consumption: MAX 21W
Digital noise reduction	2D/3D DNR					Weight	3.05kg(6.72lb)
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise					Working Environment	-40°C~70°C(-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
HLC	Support					Surge Protection	6KV
BLC	Support					Reset Button	Support
Defog	Digital Defog					Protection	Ingression protection: IP67 Vandal resistant: IK10
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication						
Smart Features	Audio detection, Deep Learning, Cross Line, Enter Area, Leave Area, Intrusion, People counting, People Flow counting, Crowd Density Monitoring, Face Capture (Maximum 40), Auto Tracking						

Dimensions

