

IPZ-P6233W-I150S

2MP 33X Starlight IR Network PTZ Dome Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -40 تا +65 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP66
- پایه قابل تنظیم 3 حالت
- رزولوشن 2 مگاپیکسل
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- زوم اپتیکال تا 33 برابر بزرگ نمایی
- لوکس نوری پایین
- IR هوشمند تا 150 متر
- طلق ضد بازتاب نور مادون قرمز
- تثبیت کننده الکترونیکی لرزش تصویر

Specifications

sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS					Smart Features	Audio detection, Cross line, intrusion, object left, object removed, people counting, face detection, Auto tracking
Lens	4.5 - 148.5mm, AF automatic focusing and motorized zoom lens					General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Digital Zoom	16					Audio Compression	G.711
Optical Zoom	33					Two-way Audio	Supported
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Suppression	Supported
	4.5	69.8	27.9	14.0	7.0	Sampling Rate	8KHZ
Angle of View (H)	148.5	2304.3	921.7	460.9	230.4	Edge Storage	Micro SD, up to 256GB
	76.8° - 2.1°					Network Storage	ANR
Angle of View (V)	38.4° - 1.2°					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL, QoS
Angle of View (D)	94.46° - 2.48°					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Shutter	Auto/Manual, shutter time: 1 - 1/100000s					Pan Range	360°
Minimum Illumination	Colour: 0.001Lux (F1.5, AGC ON)					Pan Speed	0.1°/s - 300°/s Preset speed: 200°/s
	0Lux with IR					Tilt Range	-15° - 90° (auto reverse)
Iris	F1.5 - F4.0					Tilt Speed	0.1° - 80°/s Preset speed: 80°/s
Day/Night	IR-cut filter with auto switch (ICR)					Number of Presets	1024
Digital noise reduction	2D/3D DNR					Patrol	Preset patrol, route patrol, recorded patrol
S/N	>55 dB					Home Position	Supported
IR Range	UP to 150m (492ft)					Audio I/O	1 Input: impedance 1kΩ±10%; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]
Defog	Digital Defog					Alarm I/O	2/1
WDR	120dB					Power	DC 12V±25%, PoE (PSE Required) Power consumption: 16 - 30W
Video Compression	Ultra 265, H.265, H.264, MJPEG					Dimensions (D x H)	Ø220 x 369mm (Ø8.7" x 14.5")
H.264 code profile	Baseline profile, Main Profile, High Profile					Weight	3.0kg (6.6lb)
Frame Rate	Main Stream: 2MP (1920*1080), Max 30fps;					Working Environment	-40°C - 65°C (-40°F - 149°F), Humidity: ≤95% RH (non-condensing)
	Sub Stream: 2MP (1920*1080), Max 30fps;					Ingress Protection	IP66
	Third Stream: D1 (720*576), Max 30fps					Reset Button	Supported
HLC	Supported						
BLC	Supported						
EIS	Supported						
OSD	Up to 8 OSDs						
Privacy Mask	Up to 24 areas						
ROI	Up to 8 areas						
Motion Detection	Up to 4 areas						

Dimensions

