

IPZ-P6433W-S

4MP 33X Lighthunter Network PTZ Dome Camera



Network Cameras
NVRs
AHD Series
Video Decoders
Switches
Accessories

قابلیت های کلیدی

- زوم اپتیکال تا 33 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق و سریع
- رزولوشن 4 مگاپیکسل
- Ultra265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- تکنولوژی کنترل دمای هوشمند
- بدنه ضد ضربه با استاندارد IK10
- مقاومت در برابر نفوذ آب و گرد و غبار IP67

Specifications

Sensor	1/2.8", 4.0 megapixel, progressive scan, CMOS					Edge Storage	Micro SD, up to 256GB
Minimum Illumination	Colour: 0.003Lux (F1.5, AGC ON) BW: 0.001Lux (F1.5, AGC ON)					Network Storage	ANR,NAS(NFS)
Day/Night	IR-cut filter with auto switch (ICR)					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Shutter	Auto/Manual, 1 - 1/100000s					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
WDR	120dB					User/Host	Up to 32 users. 2 user levels: administrator and common user
S/N	>56dB					Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Lens type	4.5 - 148.5mm, AF automatic focusing and motorized zoom lens					Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
Digital Zoom	16					Pan Range	360° (endless)
Optical Zoom	33					Pan Speed	2°/s - 200°/s Preset speed: 400°/s
Iris	Auto; F1.5 - F4.0					Tilt Range	1° - 90°
Angle of View (H)	53.0° - 2.3°					Tilt Speed	2°/s - 200°/s Preset speed: 240°/s
Angle of View (V)	40.5° - 1.7°					Number of Presets	1024
Angle of View (D)	65.2° - 2.7°					Preset Patrol	16 patrols, up to 64 presets for each patrol
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Route Patrol	16 patrols, up to 32 actions for each patrol
	4.5	105.8(346.9ft)	42.3(138.8ft)	21.2(69.4ft)	10.6(34.7ft)	Recorded Patrol	16 patrols, up to 128 actions for each patrol
Frame Rate	148.5	3172.5(10408.5ft)	1269.0(4163.4ft)	634.5(2081.7ft)	317.3(1040.8ft)	Patrol Stay Time	15s-1800s
	Main Stream: 4MP (2688*1520), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps					Preset Image Freeze	Support
Video Bit Rate	128 Kbps-16 Mbps					Home Position	Support
ROI	Up to 8 areas					Audio I/O	1/1
OSD	Up to 8 OSDs					Alarm I/O	7/2
Privacy Mask	24 areas, up to 4 areas per scene					Serial Port	1 RS485
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2					Network	1*10M/100M Base-TX Ethernet
Digital noise reduction	2D/3D DNR					Video output	1 BNC
Flip	Normal/Flip Vertical/Flip Horizontal/180°/90°Clockwise/90°Anti-clockwise					Safety	IEC 62368-1 EN 62368-1 UL 60950-1
EIC	N/A					Power	AC 24V ±25%, DC 24V±25%,PoE+(IEEE802.3 at) Power consumption: Max 16W
HLC	Support					Dimensions (Ø x H)	Ø218 x 297mm (Ø8.6" x 11.7")
BLC	Support					Weight	4.07kg(8.97lb)
Defog	Digital Defog					Working Environment	-40°C - 70°C (-40°F - 158°F), Humidity: ≤95% RH (non-condensing)
Smart Features	Deep learning, Smart intrusion Prevention Line Crossing, intrusion detection, Region entrance detection, Region exit detection, People flow counting and Crowd density monitoring, Face Capture (Maximum), Auto tracking (Deep learning), Audio Detection					Storage Environment	-40°C - 70°C (-40°F - 158°F), Humidity: ≤95% RH (non-condensing)
	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication					Surge Protection	6KV
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication					Reset Button	Support
Audio Compression	G.711U,G.711A					Protection	Ingress Protection: IP67 Vandal Resistant: IK10
Audio Bitrate	64 Kbps						
Two-way audio	Support						
Suppression	Support						
Sampling Rate	8 kHz						

Dimensions

