

IPZX-A6533W-S

5MP 33X Starlight Explosion-proof PTZ Dome Camera



قابلیت های کلیدی

- رزولوشن 5 مگاپیکسل
- پشتیبانی از پروتکل ONVIF
- Ultra 256, H.265, H.264, MJPEG
- دمای کارکرد -30 تا +70 درجه سانتیگراد
- بدنه استیل ضد زنگ 304
- مقاومت در برابر نفوذ آب و گرد و غبار IP68
- Exd IIC T6 Gb/ Ex tD A21 IP68 T80°C Standard
- زوم اپتیکال تا 33 برابر بزرگ نمایی
- OSD قابل تنظیم
- لوکس نوری پایین
- کاهنده نویز دیجیتال 3D

Specifications

Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	4.5 - 148.5 mm, AF automatic focusing and motorized zoom lens				
Optical Zoom	33				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.5mm	105.8(346.9ft)	42.3(138.8ft)	21.2(69.4ft)	10.6(34.7ft)
Angle of View (H)	148.5mm	3172.5(10408.5ft)	1269.0(4163.4ft)	634.5(2081.7ft)	317.3(1040.8ft)
	56.8°		2.8°		
Angle of View (V)					1.6°
Angle of View (D)					3.3°
Shutter	Auto/Manual, 1-1/100000 s				
Minimum Illumination	Colour: 0.003 Lux (F1.5, AGC ON) B/W: 0.002 Lux (F1.5, AGC ON)				
Iris	Auto/Manual, F1.5-F4.0				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>56dB				
WDR	120dB				
Video Compression	Ultra 256, H.265, H.264, MJPEG				
Frame Rate	Main Stream: 5MP (2880*1620): Max. 30 fps; Sub Stream: 2MP (1920*1080): Max. 30 fps; Third Stream: D1 (720*576): Max. 30 fps;				
Video Bit Rate	128 Kbps-16 Mbps				
OSD	Time, Custom, Preset, PTZ coordinates, Zoom, Serial port, Direction, Network port, Picture overlay, People counting				
Privacy Mask	24 areas, up to 4 areas per scene				
ROI	Up to 8 areas				
Smart intrusion prevention	Support false alarm filtering: Cross Line detection, Intrusion detection, Enter Area detection, Leave Area detection				
Intelligent auto tracking	Support intelligent tracking and target tracking, focus on motor vehicles, non-motor vehicles and people				
Face capture	Support, Face attributes: Gender, Age range, Glasses, Mask				
People counting	Support people flow counting and crowd density monitoring				
Basic Detection	Motion detection, Audio detection, Tampering alarm				

General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	G.711U, G.711A
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8kHz
Edge Storage	Micro SD, up to 256 GB (Built-in SD card is available for customization)
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
Pan Range	360°
Pan Speed	0.1°/s-400°/s Preset speed: 540°/s
Tilt Range	-17°-+90°
Tilt Speed	0.1° - 80°/s Preset speed: 80°/s
Number of Preset	1024
Patrol	Preset patrol, Route patrol, Record patrol
Home Position	Supported
Audio I/O	1/1
Alarm I/O	2/1
Serial Port	Support
Built-in Heater	Support
Network	10/100M Base-TX Ethernet
Power	AC220V(100-240V), PoE (PSE required)
Dimensions (L x W x H)	Power consumption: Max 29W
Weight	Ø230mm×347mm (9.1" × 13.7")
Working Environment	11kg (24.3lb)
Ingress Protection	-30°C ~ +70°C (-22°F ~ 158°F), Humidity: ≤95% RH(non-condensing)

Dimensions

