

NVR-E20-2/16A

Network Video Recorder



قابلیت های کلیدی

- یک عدد 4K HDMI و یک عدد VGA
- پشتیبانی از 2 عدد هارد تا ظرفیت 10 ترابایت برای هر کدام
- قابلیت برگرداندن تصاویر ضبط شده بعد از قطع شبکه
- قابلیت بروز رسانی آنلاین

- پشتیبانی از فرمت های تصویر Ultra265/H.265/H.264
- 20 کانال تصویر ورودی تا رزولوشن 8 مگاپیکسل
- دارای 16 پورت PoE با توان کلی 240 وات
- پشتیبانی از دوربین های با پروتکل ONVIF

Specifications

IP Video Input	20-ch	Capacity	Up to 10TB for each disk
Two-way Audio Input	1-ch, RCA	VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object Left Behind, Object Removed Human Body detection
Incoming Bandwidth	160Mbps	VCA Search	Face search, Behavior search
Outgoing Bandwidth	64Mbps	Statistical Analysis	People counting
Remote Users	128	Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
Protocols	P2P, UPnP, NTP, DHCP, PPPoE	USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0
HDMI/VGA Output	HDMI: 4K (3840x2160@30), 1920X1080@60, 1920X1080@50, 1600X1200@60, 1280X1024@60, 1280X720@60, 1024X768@60 VGA: 1920X1080@60, 1920X1080@50, 1280X1024@60, 1280X720@60, 1024X768@60	Alarm In	4-ch
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Alarm Out	1-ch
Audio Output	1-ch, RCA	Interface	16 independent 100Mbps PoE network interfaces
Synchronous Playback	16-ch	Max Power	Max 30W for single port Max 240W in total
Corridor Mode Screen	3/4/5/7/9/10/12/16	Supported Standard	IEEE 802.3af/at
Decoding format	Ultra265/H.265/H.264	Power Supply	100 ~ 240 V AC Power Consumption: ≤10W(without HDD)
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Capabilit	2 x 4K@30, 4x 4MP@30, 5 x 3MP@30, 8 x 1080P@30, 16 x 720P@30	Dimensions (W×D×H)	380mm × 315mm × 53mm (14.9" × 12.4" × 2.1")
SATA	2 SATA interfaces	Weight (without HDD)	≤2.6kg (5.29lb)

Dimensions

