

# NVR-E20-2A

Network Video Recorder



## قابلیت های کلیدی

- یک عدد 4K HDMI و یک عدد VGA
- پشتیبانی از 2 عدد هارد تا ظرفیت 6 ترابایت برای هر کدام
- قابلیت برگرداندن تصاویر ضبط شده بعد از قطع شبکه
- قابلیت بروز رسانی آنلاین
- پشتیبانی از فرمت های تصویر Ultra265/H.265/H.264
- 20 کانال تصویر ورودی تا رزولوشن 8 مگاپیکسل
- پشتیبانی از دوربین های با پروتکل ONVIF

## Specifications

IP Video Input	20-ch	Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Two-way Audio Input	1-ch, RCA	Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30
Incoming bandwidth	160Mbps	SATA	2 SATA interfaces
Outgoing bandwidth	64Mbps	Capacity	up to 6TB for each disk
Remote Users	128	VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object Left Behind, Object Removed, Human Body detection
Protocols	P2P, UPnP, NTP, DHCP, PPPoE	VCA Search	Face search, Behavior search
HDMI/VGA Output	HDMI: 4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60	Statistical Analysis	People counting
Audio Output	1-ch, RCA	Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0
Synchronous Playback	16-ch	Power Supply	12V DC Power Consumption: ≤ 15 W (without HDD)
Corridor Mode Screen	3/4/5/7/9/10/12/16	Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Decoding format	Ultra265/H.265/H.264	Dimensions (W×D×H)	380mm × 315mm ×53mm (15.0" × 12.4" ×2.1")
		Weight (without HDD)	≤ 0.98Kg (2.16lb)

## Dimensions

