

NVR-E32-2D

Network Video Recorder



Network
Cameras

NVRs

AHD
Series

Video
Decoders

Switches

Accessories

قابلیت های کلیدی

- یک عدد 4K HDMI و یک عدد VGA
- پشتیبانی از 2 عدد هارد تا ظرفیت 8 ترابایت برای هر کدام
- قابلیت برگرداندن تصاویر بعد از قطع شبکه
- قابلیت بروزرسانی آنلاین

- پشتیبانی از فرمت های تصویر Ultra265, H.265, H.264
- 32 کانال تصویر ورودی تا رزولوشن 12 مگاپیکسل
- پشتیبانی از دوربین های با پروتکل ONVIF

Specifications

IP Video Input	32-ch	SATA	2 SATA interfaces
Two-way Audio Input	1-ch, RCA	Capacity	Up to 8TB for each disk (The maximum HDD capacity varies with environment temperature)
Incoming Bandwidth	320Mbps	eSATA	NA
Outgoing Bandwidth	320Mbps	VCA Detection	Face detection, Intrusion detection, Cross Line detection, Audio detection, Human Body detection, People Counting, People flow Counting, Crowd density monitoring, Scene Change detection, Defocus detection, Auto Tracking, Face and Vehicle Recognition by IPC, Heat map, Object Left Behind, Object Removed, SIP by IPC
Remote Users	128	VCA Search	Face Search, Behavior Search
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS	Disk Group	Support
Browser	IE(IE10/11) for Windows Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows Edge(version 79 and above) for Windows	Smart Intrusion Prevention (SIP), Vehicle Detection by Camera	Total -8ch
HDMI/VGA Output	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI: 4K [3840x2160]/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	Alert Alarm	IP Conflict, Network Disconnected, Disk Offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet Interfaces
Audio Output	1-ch, RCA	USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB1.2.0 x USB3.0
Audio Compression	G.711A, G.711U	RS232	NA
Synchronous Playback	16-ch	RS485	1
Live View Display	1/4/6/8/9/16/25/36	Alarm In	8-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32	Alarm Out	2-ch
FTP/Schedule/Event Snapshot	16-ch snapshot, up to 1080P resolution	Power Supply	12VDC/3.3A Power Consumption: ≤ 12 W (without HDD)
Decoding Format	Ultra 265, H.265, H.264	Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Live View/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Dimensions (W×D×H)	380mm × 315mm × 53mm (15.0" × 12.4" × 2.1")
Capability	1 x 12MP@30, 2 x 4K@30, 5 x 4MP@30, 10 x 1080P@30, 22 x 720P@30, 32 x D1	Weight (without HDD)	≤1.8Kg (3.97lb)

Rear Panel

Dimensions

