

SW-SL2-24P-2G2F

24-Port PoE Switch



قابلیت های کلیدی

- حالت های کاری نرمال، ایمن، نظارت تصویری
- کنترل ترافیک پورت ها
- انتقال دیتا و برق تا 250 متر در حالت نظارت تصویری

Specifications

Ports	24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports	Operating humidity	10%~90% (noncondensing)	
Standards	IEEE802.3,IEEE802.3u,IEEE802.3z,IEEE802.3ab,IEEE802.3x,IEEE802.3af,IEEE802.3at,IEEE802.3az	Storage humidity	5%~90% (noncondensing)	
Switching capacity	8.8Gbps	Indicator	PWR: Steady on: AC input is normal Off: No AC input	
Forwarding performance	6.55Mpps		PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal	
Packet Buffer	4Mbit		LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data	
MAC	16K		Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps Default(Normal mode) : All ports can communicate with each other.	
Dimensions (W×D×H)	440mm x 207mm x 45mm(17.3"×8.1"×1.8")		Working Mode	VLAN(Secure mode): Downlink ports can communicate only with uplink ports. EXTEND(Surveillance mode): Transmission distance up to 250 meters ,also downlink ports can communicate only with uplink ports.
Weight	<4.2kg			
Power supply	AC: 100-240V, 50/60Hz			
PoE	802.3at/af			
Max. PoE Power	Max capacity: 370W Max capacity for single port: 30W			
Switch Power	390W			
Surge Protection	Common mode ±6KV Differential mode ±4KV			
Electrostatic standard	Common mode ±6KV Differential mode ±8KV			
Cooling Fans	2			
Mean Time Between Failure(MTBF)	>50000 hours			
Operating humidity	0°C-45°C (32°F-113°F)			

Dimensions

