

# NVR-E20-2A

Network Video Recorder



## قابلیت های کلیدی

- یک عدد HDMI 4K و یک عدد VGA
- پشتیبانی از 2 عدد هارد تا ظرفیت 6 ترابایت برای هر کدام
- قابلیت برگرداندن تصاویر ضبط شده بعد از قطع شبکه
- قابلیت بروز رسانی آنلاین
- پشتیبانی از فرمت های تصویر Ultra265/H.265/H.264
- 20 کانال تصویر ورودی تا رزولوشن 8 مگاپیکسل
- پشتیبانی از دوربین های با قابلیت ONVIF

## Specifications

IP Video Input	20-ch	Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Two-way Audio Input	1-ch, RCA	Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30
Incoming bandwidth	160Mbps	SATA	2 SATA interfaces
Outgoing bandwidth	64Mbps	Capacity	up to 6TB for each disk
Remote Users	128	VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
Protocols	P2P, UPnP, NTP, DHCP, PPPoE	VCA Search	Face search, Behavior search
HDMI/VGA Output	HDMI:	Statistical Analysis	People counting
	4K (3840x2160)@30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60	Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
Audio Output	VGA:	USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0
	1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60	Power Supply	12V DC Power Consumption: ≤ 15 W (without HDD)
Recording Resolution	1-ch, RCA	Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Synchronous Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Dimensions (W×D×H)	380mm × 315mm × 53mm (15.0" × 12.4" × 2.1")
Corridor Mode Screen	16-ch	Weight (without HDD)	≤ 0.98Kg (2.16lb)
Decoding format	3/4/5/7/9/10/12/16		
	Ultra265/H.265/H.264		

## Dimensions

