


## DS-AJ6816S Enterprise-Class SAS Enclosure



### Key Features


- Mini SAS with Transmittability 4 Times Faster than 6G
- Support for Cascading Expansion
- Support for 4 types of HDD interfaces, including SATA I, SATA II, SATA III, and SAS
- Up to 4 TB Capacity for each HDD

Available model: DS-AJ6816S

### Specifications

DS-AJ6816S	
Controller Parameters	
Controller	1 controller
SAS Interface (Upper-level)	1 (6 Gbps)
SAS Interface (Lower-level)	1 (6 Gbps)
HDD Interfaces	16
HDD Interface Type	SATA, SAS
Hot Swap HDD	Supported
Power	Redundant (1 + 1)
General	
Chassis	3U chassis
Dimension (W x D x H)	17.3" x 5.2" x 18.9" (440 x 132 x 480 mm)
Weight (Without Hard Disk)	33.08 lbs (15 kg)
Consumption (with Maximum Hard Disks)	≤ 550 W
Working Temperature	41° F to 104° F (5° C to 40° C)
Storage Temperature	-4° F to 158° F (-20° C to 70° C)
Working Humidity	20% to 80% (with no icing and condensation)
Storage Humidity	5% to 90% RH (with no icing and condensation)

### Dimensions



- |                                |                                |
|--------------------------------|--------------------------------|
| 1: Power Supply                | 4: NIC                         |
| 2: SAS Interface (Upper-level) | 5: SAS Interface (Lower-level) |
| 3: Serial Port Interface       | 6: Fan                         |