

NVR-E20-2/16A

Network Video Recorder



قابلیت های کلیدی

- یک عدد HDMI 4K و یک عدد VGA
- پشتیبانی از 2 عدد هارد تا ظرفیت 10 ترابایت برای هر کدام
- قابلیت برگرداندن تصاویر ضبط شده بعد از قطع شبکه
- قابلیت بروز رسانی آنلاین

- پشتیبانی از فرمت های تصویر Ultra265/H.265/H.264
- 20 کانال تصویر ورودی تا رزولوشن 8 مگاپیکسل
- دارای 16 پورت PoE با توان کلی 240 وات
- پشتیبانی از دوربین های با قابلیت ONVIF

Specifications

IP Video Input	20-ch	SATA	2 SATA interfaces
Two-way Audio Input	1-ch, RCA	Capacity	Up to 10TB for each disk
Incoming Bandwidth	160Mbps	VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking, Object Left Behind, Object Removed
Outgoing Bandwidth	64Mbps	VCA Search	Face search, Behavior search
Remote Users	128	Statistical Analysis	People counting
Protocols	P2P, UPnP, NTP, DHCP, PPPoE	Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
HDMI/VGA Output	HDMI:	USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB3.0
	4K [3840x2160@30], 1920X1080@60, 1920X1080@50, 1600X1200@60, 1280X1024@60, 1280X720@60, 1024X768@60	Alarm In	4-ch
Recording Resolution	VGA:	Alarm Out	1-ch
	1920X1080@60, 1920X1080@50, 1280X1024@60, 1280X720@60, 1024X768@60	Interface	16 independent 100Mbps PoE network interfaces
Audio Output	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Max Power	Max 30W for single port Max 240W in total
Synchronous Playback	1-ch, RCA	Supported Standard	IEEE 802.3af/at
Corridor Mode Screen	3/4/5/7/9/10/12/16	Power Supply	100 ~ 240 V AC
Decoding format	Ultra265/H.265/H.264	Working Environment	Power Consumption: ≤10W(without HDD)
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Dimensions (W×D×H)	-10°C~+55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Capability	2 x 4K@30, 4x 4MP@30, 5 x 3MP@30, 8 x 1080P@30, 16 x 720P@30	Weight (without HDD)	380mm × 315mm × 53mm [14.9" × 12.4" × 2.1"]
			≤2.6kg [5.29lb]

Dimensions

