

NVR-A130RH-16A

Network Video Recorder



قابلیت های کلیدی


- پشتیبانی از 16 عدد هارد تا ظرفیت 10 ترابایت برای هر کدام
- دو عدد درگاه mini SAS
- خروجی 12 ولت
- قابلیت برگرداندن تصاویر ضبط شده بعد از قطع شبکه
- قابلیت بروز رسانی آنلاین

- پشتیبانی از فرمت های تصویر Ultra265/H.265/H.264
- 130 کانال تصویر ورودی تا رزولوشن 12 مگاپیکسل
- پشتیبانی از دوربین های با قابلیت ONVIF
- دو عدد 4K HDMI و یک عدد VGA مستقل از هم

Specifications

IP Video Input	130-ch	eSATA	1 eSATA interface
Two-way Audio Input	1-ch, BN	miniSAS	2 miniSAS ports
Incoming Bandwidth	512Mbps	VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection, Defocus detection, Scene change detection, Auto tracking
Outgoing Bandwidth	384Mbps	VCA Search	Face search, Behavior search
Remote Users	128	Statistical Analysis	People counting
Protocols	P2P, UPnP, NTP, DHCP, PPPoE	Array Type	RAID 0/1/5/6/10/50/60
HDMI/VGA Output	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI1: 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI2: 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	Network Interface	4 RJ-45 10M/100M/1000M adaptive Ethernet Interface 2 1000M SFP Ethernet Interface
Recording Resolution	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Serial Interface	1 x RS232, 1 x RS485
Audio Output	1-ch, BNC	USB Interface	Rear panel: 4 x USB3.0
Synchronous Playback	16-ch	Alarm In	24-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32	Alarm Out	8-ch
Decoding format	Ultra 265, H.265, H.264	Decoding Card (optional)	2 slots (4-ch HDMI or 6-ch HDMI outputs per card)
Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Power Output	12V
Capability	4 x 12MP@20, 4 x 4K@30, 16 x 1080p@30, 36 x 720p@30, 64 x D1	Power Supply	100 - 240V AC Power Consumption: ≤ 50 W (without HDD)
SATA	16 SATA interfaces	Working Environment	-10°C - + 55°C (+14°F - +131°F), Humidity ≤ 90% RH (non-condensing)
Capacity	up to 10TB for each HDD	Chassis	19-inch rack-mounted 3U chassis
		Dimensions	482mm × 477mm × 131mm (18.8" × 19.0" × 5.1")
		Weight (without HDD)	≤ 10 Kg (22.05 lb)

Dimensions



۶۰