

# IPZ-P6233W-I150S

## 33X Starlight IR Network PTZ Dome Camera



Accessories

Control

NVR

Network Camera

Video Decoder

- زوم اپتیکال تا 33 برابر بزرگ نمایی
- لوکس نوری پایین
- IR هوشمند تا 150 متر
- طلق ضد بازتاب نور مادون قرمز
- تثبیت کننده الکترونیکی لرزش تصویر

- رزولوشن 2 مگاپیکسل
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم


- ### قابلیت های کلیدی
- پشتیبانی از پروتکل ONVIF
  - دمای کارکرد 40- تا +65 درجه سانتیگراد
  - مقاومت در برابر نفوذ آب و گرد و غبار IP66
  - پایه قابل تنظیم 3 حالت

## Specifications

sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS				
Lens	4.5 - 148.5mm, AF automatic focusing and motorized zoom lens				
Digital Zoom	16				
Optical Zoom	33				
Angle of View (H)	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
Angle of View (V)	4.5	69.8	27.9	14.0	7.0
Angle of View (O)	148.5	2304.3	921.7	460.9	230.4
Angle of View (H)	76.8° - 2.1°				
Angle of View (V)	38.4° - 1.2°				
Angle of View (O)	94.46° - 2.48°				
Shutter	Auto/Manual, shutter time: 1 - 1/100000s				
Minimum Illumination	Colour: 0.001Lux (F1.5, AGC ON) 0Lux with IR				
Iris	F1.5 - F4.0				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>55 dB				
IR Range	UP to 150m (492ft)				
Defog	Digital Defog				
WDR	120dB				
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile, High Profile				
Frame Rate	Main Stream: 2MP (1920*1080), Max 30fps; Sub Stream: 2MP (1920*1080), Max 30fps; Third Stream: D1 (720*576), Max 30fps				
HLC	Supported				
BLC	Supported				
EIS	Supported				
OSD	Up to 8 OSDs				
Privacy Mask	Up to 24 areas				
ROI	Up to 8 areas				
Motion Detection	Up to 4 areas				

Smart Features	Audio detection, Cross line, intrusion, object left, object removed, people counting, face detection, Auto tracking
General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	G.711
Two-way Audio	Supported
Suppression	Supported
Sampling Rate	8KHZ
Edge Storage	Micro SD, up to 256GB
Network Storage	ANR
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Pan Range	360°
Pan Speed	0.1°/s - 300°/s Preset speed: 200°/s
Tilt Range	-15° - 90° (auto reverse)
Tilt Speed	0.1° - 80°/s Preset speed: 80°/s
Number of Presets	1024
Patrol	Preset patrol, route patrol, recorded patrol
Home Position	Supported
Audio I/O	1 Input: impedance 1kΩ±10%; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]
Alarm I/O	2/1
Power	DC 12V±25%, PoE (PSE Required) Power consumption: 16 - 30W
Dimensions (Ø x H)	Ø220 × 369mm (Ø8.7" x 14.5")
Weight	3.0kg (6.6lb)
Working Environment	-40°C - 65°C (-40°F - 149°F), Humidity: ≤95% RH (non-condensing)
Ingress Protection	IP66
Reset Button	Supported

## Dimensions



۴۰