

IPZ-P6222W-I150S

22X Lighthunter IR Network PTZ Dome Camera



قابلیت های کلیدی

- زوم اپتیکال تا 22 برابر بزرگ نمایی
- لوکس نوری پایین
- فوکوس دقیق و سریع
- IR هوشمند تا 150 متر
- رزولوشن 2 مگاپیکسل
- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- OSD قابل تنظیم
- پشتیبانی از پروتکل ONVIF
- تکنولوژی کنترل دمای هوشمند
- طراحی موثر دفع گرما
- حفاظت الکتریکی 6KV
- مقاومت در برابر نفوذ آب و گرد و غبار IP66

Specifications

sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS					Smart Features	Audio detection, Cross line, intrusion, object left, object removed, people counting, face detection, Auto tracking
Lens	5.2 - 114.4mm, AF automatic focusing and motorized zoom lens					General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Digital Zoom	16					Audio Compression	6.711
Optical Zoom	22					Two-way Audio	Supported
Angle of View (H)	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	Suppression	Supported
Angle of View (V)	5.2	80.7(264.7ft)	32.3(105.9ft)	16.1(52.9ft)	8.1(26.5ft)	Sampling Rate	8KHZ
Angle of View (O)	114.4	1775.2(5824.1ft)	710.1(2329.6ft)	355.0(1164.8ft)	177.5(582.4ft)	Edge Storage	Micro SD, up to 256GB
Angle of View (H)	53.4° - 2.7°					Network Storage	ANR
Angle of View (V)	32.3° - 1.5°					Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Angle of View (O)	60.3° - 3.1°					Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API
Shutter	Auto/Manual, shutter time: 1 - 1/100000s					Pan Range	360° (endless)
Minimum Illumination	Colour: 0.003Lux (F1.5, AGC ON) 0Lux with IR					Pan Speed	0.1°/s - 240°/s Preset speed: 300°/s
Iris	Auto/Manual; F1.5 - F3.8					Tilt Range	-15° - 90° (auto reverse)
Day/Night	IR-cut filter with auto switch (ICR)					Tilt Speed	0.1° - 80°/s Preset speed: 80°/s
Digital noise reduction	2D/3D DNR					Number of Presets	1024
S/N	>52 dB					Patrol	Preset patrol, route patrol, recorded patrol
IR Range	UP to 150m (492ft)					Home Position	Supported
Defog	Digital Defog					Audio I/O	1 Input: impedance 35kΩ; amplitude 2V [p-p] 1 Output: impedance 600Ω; amplitude 2V [p-p]
WDR	120dB					Alarm I/O	1/1
Video Compression	Ultra 265, H.265, H.264, MJPEG					Power	DC 12V±10%, PoE (PSE Required) Power consumption: 4 - 27.6W
H.264 code profile	Baseline profile, Main Profile, High Profile					Dimensions (W x H)	Φ220 x 369mm (Φ8.7" x 14.5")
Frame Rate	Main Stream: 2MP (1920*1080), Max 60fps; Sub Stream: 2MP (1920*1080), Max 60fps; Third Stream: D1 (720*576), Max 60fps					Weight	3.4kg (7.5lb)
HLC	Supported					Working Environment	-40°C - 65°C (-40°F - 149°F), Humidity: ≤95% RH (non-condensing)
BLC	Supported					Ingress Protection	IP66
EIS	Supported					Reset Button	Supported
OSD	Up to 8 OSDs						
Privacy Mask	Up to 24 areas						
ROI	Up to 8 areas						
Motion Detection	Up to 4 areas						

Dimensions

