

IPC-A4A2WH-SF

2MP WDR Starlight Network Box Camera



قابلیت های کلیدی

- قابلیت روز و شب
- لوکس نوری پایین
- کاهنده نویز دیجیتال 3D


- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از حالت راهرو 9:16

- پشتیبانی از پروتکل ONVIF
- پورت شبکه و فیبر نوری
- ورودی برق 24VAC/12VDC/POE
- دمای کارکرد -20 تا +60 درجه سانتیگراد
- حفاظت الکتریکی 6KV

Specifications

Sensor	1/1.8", 2.0 megapixel, progressive scan, CMOS	General Function	Watermark, IP Address Filtering, Tampering Alarm, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Lens Mount	CS	Audio Compression	6.711
Shutter	Auto/Manual, 1 - 1/100000s	Two-way Talking	Supported
Minimum Illumination	Colour: 0.0005Lux (F1.2, AGC ON) B/W: 0.0001Lux (F1.2, AGC ON)	Suppression	Supported
Day & Night	Automatically removable IR-cut filter(ICR)	Sampling Rate	8KHZ
Digital noise reduction	2D/3D DNR	Edge Storage	Micro SD, up to 256GB
S/N	>52dB	Network Storage	ANR
Defog	Optical Defog & Digital Defog	Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
WDR	120dB	Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API 3.5mm audio interface
Video Compression	Ultra 265, H.265, H.264, MJPEG	Audio I/O	Input: impedance 35kΩ; amplitude 2V [p-p] Output: impedance 600Ω; amplitude 2V [p-p]
H.264 code profile	Baseline profile, Main Profile, High Profile	Alarm I/O	2/1
Frame Rate	Main Stream: 2MP (1920*1080), Max 60fps; Sub Stream: 2MP (1920*1080), Max 60fps; Third Stream: D1 (720*576), Max 60fps	Zoom/focus	N/A
9:16 Corridor Mode	Supported	Iris	P-Iris/DC- Iris
HLC	Supported	Serial Port	1 RS485 (support Pelco-D/P)
BLC	Supported	Network	1 RJ45 100M/1000M Base-FX SFP+100M/1000M Base-TX Ethernet
ABF	Supported	Video Output	1 BNC, impedance 75Ω; amplitude 1V [p-p]
OSD	Up to 8 OSDs	Power	AC 24V±25%, DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 6.8W
ROI	Up to 8 areas	Dimensions (L x W x H)	151.5 x 71 x 65mm (6.0" x 2.8" x 2.6") (excluding the lens)
Privacy Mask	Up to 8 areas	Weight	0.48kg (1.1lb)
Motion Detection	Up to 4 areas	Working Environment	-20°C - 60°C (-4°F - 140°F), Humidity: ≤95% RH (non-condensing)
Smart Features	Audio detection, cross line, intrusion, object left, object removed, People counting, Face capture	Reset Button	Supported

Dimensions



9