



# SXT 2

SXT is a low cost, high speed 2GHz outdoor wireless device, now also available as a high power Gigabit, or as a low cost Lite version. SXT can be used for point to point links, as a CPE for point to multipoint installations or even as an AP/Sector (G model) because of it's wide beamwidth antenna.

Complete with a ready to mount enclosure and built-in 10dBi antenna, the package contains everything you need to set it up in a matter of minutes.



Approximately 60° beamwidth in all polarizations

| Model                | SXT 2   | SXT Lite2                          |
|----------------------|---|------------------------------------|
| Product code         | RBSXTG2HnD  | RBSXT2nDr2                         |
| CPU                  | AR9344 600MHz   |                                    |
| Memory               | 64MB RAM  |                                    |
| Ethernet             | 10/100/1000 (Gigabit) Ethernet port<br>L2MTU frame size up to 4076  | 10/100 Ethernet port               |
| Wireless             | Onboard dual chain 2GHz 802.11b/g/n. 10kV ESD protection on each RF port  |                                    |
| Wireless regulations | Specific frequency range may be limited by country regulations  |                                    |
| Extras               | Reset switch, beeper, voltage and temperature monitors  | Reset switch, beeper               |
| LEDs                 | Power LED, Ethernet LED, 5 wireless signal LED  |                                    |
| Power input          | PoE in: 8-30V DC. Packaged with 24V PSU and passive PoE injector  |                                    |
| Dimensions           | 140x140x56mm  |                                    |
| Power consumption    | Up to 7W  | Up to 8W                           |
| Operating temp.      | -40°C .. +70°C tested   |                                    |
| License              | Level 4 license (CPE, PtP or AP as sector)  | Level 3 license (CPE or PtP modes) |
| Package contains     | SXT wireless device with integrated antenna, pole mounting bracket, mounting ring, PoE injector, 24V 0.8A power adapter (SXT 2), 24V 0.38A power adapter (SXT Lite2), quick setup guide |                                    |
| Certifications       | FCC, CE, ROHS   |                                    |

|                 | SXT 2   | SXT Lite2      |
|-----------------|---|----------------|
| TX/RX at MCS0   | 32dBm / -95dBm  | 27dBm / -95dBm |
| TX/RX at MCS7   | 25dBm / -74dBm  | 22dBm / -77dBm |
| TX/RX at 6Mbit  | 32dBm / -96dBm  | 27dBm / -95dBm |
| TX/RX at 54Mbit | 29dBm / -80dBm  | 23dBm / -80dBm |
| Antenna         | Dual polarization 2GHz antenna, 10dBi, -18 dB port to port isolation, Beam-Width: H-Plane, E-Plane typ. 60° |                |



24V 0.38A Adapter

Mounting ring

Pole mounting bracket

PoE injector