

NVR-E04-1B

Network video Recorder



قابلیت های کلیدی

- خروجی همزمان HDMI و VGA
- پشتیبانی از 1 عدد هارد تا ظرفیت 6 ترابایت
- قابلیت بروز رسانی آنلاین

- پشتیبانی از فرمت های تصویر Ultra265/H.265/H.264
- 4 کانال تصویر ورودی تا رزولوشن 6 مگاپیکسل
- پشتیبانی از دوربین های با پروتکل ONVIF

Specifications

IP Video Input	4-ch	Decoding format	Ultra 265/H.265/H.264
Incoming Bandwidth	40Mbps	Liveview/Playback	6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Outgoing Bandwidth	40Mbps	Capability	1 x 6MP@20, 1 x 5MP@30, 2 x 4MP@25, 2 x 3MP@30, 4 x 1080p@25, 8 x 960p@25, 8 x 720p@30
Remote Users	128	SATA	1 SATA interface
Protocols	P2P, UPnP, NTP, DHCP, PPPoE	Capacity	up to 6TB for each disk
HDMI/VGA Output	HDMI: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection
	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
Audio Output	1-ch, RCA	USB Interface	Rear panel: 2 x USB2.0
Recording Resolution	6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF	Supported Standard	IEEE 802.3at, IEEE 802.3af
Synchronous Playback	4-ch	Power Supply	12V DC Power Consumption: ≤9 W (without HDD)
Corridor Mode Screen	3/4	Working Environment	-10°C ~ +55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
		Dimensions (W×D×H)	260mm × 240mm × 46mm (10.2"×9.4"×1.8")
		Weight (without HDD)	1kg (2.20 lb)

Dimensions

