

IPC-E1F4D-I30

4MP Mini Fixed Bullet Network Camera



قابلیت های کلیدی

- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- شیشه ضد بازتاب نور مادون قرمز
- Ultra 265, H.265, H.264, MJPEG
- پشتیبانی از 3 استریم تصویر
- پشتیبانی از ROI
- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت

Specifications

Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F2.0				
DORI Distance	Lens(mm)	Detect(m)	Observe(m)	Recognize(m)	Identify(m)
	2.8	63	25.2	12.6	6.3
Angle of View (H)	104.4				
Angle of View (V)	54.4				
Angle of View (D)	135.7				
Adjustment angle	Pan: 0° - 360°		Tilt: 0°-90°	Rotate: 0°- 360°	
Shutter	Auto/Manual 1 - 1/100000s				
Minimum Illumination	Colour: 0.03 Lux (F2.0, A6C ON) 0 Lux with IR on				
Digital Noise Reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>52dB				
IR Range	30-50m IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	100dB				
Video Compression	Ultra 265,H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				
Frame Rate	Main Stream:4MP (2592*1520): Max. 20 fps;				
	Sub Stream:720P (1280*720): Max. 20 fps;				
	Third Stream:01 (720*576): Max. 20 fps				
Video Bit Rate	128 Kbps-16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 2 areas				
Motion Detection	Up to 4 areas				
Smart Features	Intrusion, Human body detection				
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital noise reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Vertical/Horizontal/180°				
Dewarping	NA				
HLC	Supported				
BLC	Supported				
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS				
Compatible Integration	ONVIF (Profile S, Profile T), API				
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+				
Network	10/100M Base-TX Ethernet				
Certifications	CE: EN 60950-1				
	UL: UL60950-1				
	FCC: FCC Part 15				
Power	12 V DC±25%, PoE (IEEE802.3 af) Power consumption: Max 5W				
Dimensions(L x W x H)	165 x 63.1 x 62.5mm (6.5" x 2.5" x 2.5")				
Net Weight	0.45kg (0.99lb)				
Material	Metal				
Working Environment	-30°C - +60°C (-22°F - 140°F), Humidity :≤95% RH(non-condensing)				
Storage Environment	-30°C - +60°C (-22°F - 140°F), Humidity :≤95% RH(non-condensing)				
Surge Protection	2KV				
Ingress Protection	IP67				
Reset Button	Supported				

Dimensions

