



HIKVISION®
First Choice for Security Professionals

کاتالوگ جامع محصولات هایک ویژن
با گارانتی پارس ارتباط افزار
۱۳۹۶ دوم نیمسال



First Choice for Security Professionals



هایکویژن تولیدکننده برتر دوربین‌های مداربسته و سیستم‌های نظارت تصویری در جهان است و طبق گزارش موسسه تحقیقاتی IHS آوردن ۲۱/۶ درصد سهم بازار، برای ششمین سال پیاپی موفق به کسب رتبه اول جهان در صنعت سیستم‌های حفاظتی و امنیتی شده است. شرکت پارس ارتباط افزار، بیش از چهارده سال در حوزه ارائه تجهیزات و راهکارهای حوزه فناوری اطلاعات فعالیت داشته و از سال ۲۰۱۵ بعنوان تنها نماینده رسمی و ارائه‌دهنده خدمات پس از فروش سیستم‌های حفاظتی و نظارت تصویری شرکت هایکویژن در ایران مشغول به فعالیت است.

مرکز خدمات پس از فروش شرکت پارس ارتباط، با تعهد کامل به شرایط گارانتی محصول، با کادری مجرب و متخصص آماده رفع کامل مشکلات فنی کاربران و مشتریان و ارائه خدمات پس از فروش می‌باشد. در حال حاضر، پارس ارتباط مفتخر است با تکیه بر سیاست‌های مشتری مداری، به یک گارانتی معتبر، قابل اتکا و شناخته شده در حوزه IT کشور تبدیل شده است.

موقعیت جهانی هایکویژن

- ارائه کننده سیستم‌ها و راهکارهای جامع نظارتی و امنیتی برای تمامی سناریوهای ممکن
- کسب جایگاه نخست جهان در صنعت سیستم‌های نظارتی برای ششمین سال متوالی
- کسب جایگاه نخست در رتبه‌بندی ۵۰ شرکت برتر سیستم‌های نظارتی و امنیتی توسط رسانه A&S
- کسب جایگاه نخست در بازار خاورمیانه و شمال آفریقا
- کسب جایگاه نخست گردش مالی در صنعت سیستم‌های نظارتی (۴/۶۷ میلیارد دلار در سال ۲۰۱۶)
- دارای بیش از ۲۰۰۰ پرسنل متخصص
- دارای ۹۰۰۰ مهندس تحقیق و توسعه شامل ۲۰۰۰ مهندس نرم‌افزار
- بیش از ۱۱۰۰ مهندس برای تست سلامت محصولات
- دارای بزرگترین امکانات تولید در جهان (۲ کارخانه فعال و ۱ کارخانه جدید در حال توسعه)
- ثبت بیش از ۶۰۰ کپیرایت و ۱۳۰۰ اختراع



H2

PRODUCT SERIES

Easy IP 3.0 Series

**Easy & Powerful Security
for the Small-Medium Business**

- Up to 4K ultra-HD, advanced H.265+ encoding
- DarkFighter ultra-low illumination technology
- Efficient VCA functions
- Easy to install, setup, and manage
- Budget-friendly and powerful



1

Turbo HD 4.0 Series

**Supercharging Analog Systems
to Hi-Def**

- 8 MP Cameras & up to 4K output over coax
- Advanced H.265+ encoding
- Built In POC
- Ultra Lowlight

TURBO HD 4.0



2



3

Thermal Cameras Series

Bringing the Invisible to Light

- Advanced thermal sensors
- Unaffected by changes in weather, light conditions
- Single- & dual-lens and handheld cameras
- Wide range of Smart features



4

Access Control + Intrusion Series

A Steady Guard at the Gate

- Video intercom system
- Fully integrated security solution
- Alarm triggering and remote access
- Wide range of options for any application

STAR PRODUCTS

VMS (Blazer) Series

Powerful One-Piece Server & VMS Station

- A server, date storage, VMS station, and NVR in one device
- Advanced hardware and software design for high availability
- Budget-friendly and powerful
- Manages multiple sites and NVRs from one location



5



6

Network Video Recorder Series

Stable Video Data Storage & Management Station

- Super PoE up to 300 meters
- Patent industry designs to build a stable station
- Powerful decoding and storage capacity
- Low power consumption and light noise

PanoVu Cameras

Huge Panoramas. Incredible Zoom

- 8 & 16 MP Multi-Sensors with DarkFighter technology
- 180° & 360° Panoramas, with in-camera image stitching
- 23x Optical zoom; 16x digital zoom
- Smart tracking, Smart detection, & more

PanoVu



DarkFighter Cameras

Stunning Color Video in Near Darkness

- 1/1.8" Prog. scan CMOS sensor
- Color imaging at 0.002 Lux; B/W: 0.0002 Lux
- Full HD 1080p; 120 dB WDR; with up to 128 GB on-board storage
- Full smart feature-set
- IP67; EXIR; Motorized lens with smart focus

DARKFIGHTER



Super series NVR

Easily build a stable local surveillance center

- Up to 768Mbps bit rate input Max [Up to 128/256 camera input]
- Up to 192T storage capacity[8Tx24HDD],support hot swapping
- Redundant power supply
- Support RAID 0/1/5/6/10
- 20-ch 1080p decoding capacity
- Output resolution at up to 4K



PTZ CAMERA



SMART NETWORK PTZ

DS-2DF8436IX-AEL(W)

4MP 36X IR PTZ network camera



- H.265+/H.265/H.264+/H.264
- Ultra-low illumination technology
- 4MP HD resolution, 36X Optical Zoom
- DarkFighter ultra-low light technology
- Smart features (smart tracking, etc)
- 200m IR distance
- Wiper for self-cleaning
- Vandal-proof (IK10)

DS-2DF8236IX-AEL(W)

DarkFighter series 2MP 36X IR PTZ network camera



- H.265+/H.265/H.264+/H.264
- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 36X Optical Zoom
- Smart features (smart tracking, etc), optical defog
- 120dB WDR
- 200m IR distance
- Wiper for self-cleaning(-W)
- Vandal-proof (IK10)

DS-2DF8836IX-AELW

8MP 36X IR PTZ Network Camera



- H.265+/H.265/H.264+/H.264
- Ultra-low illumination technology
- 8MP ultra-HD resolution, 36X Optical Zoom
- Smart features (smart tracking, etc)
- 200m IR distance
- Wiper for self-cleaning
- Vandal-proof (IK10)

DS-2DT6223-AELY

DarkFighter Series 2MP 23X Anti-corrosion PTZ Network Camera



- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X Optical Zoom
- Smart features (smart tracking, etc)
- 316L stainless steel housing
- 120dB WDR
- Vandal-proof (IK10)
- ISO C5-M, NEMA 4X certification

NETWORK PTZ

DS-2DE4A320/4A220IW-DE

3MP/2MP 20X Mini PTZ Dome Network Camera



- 3MP/2MP real-time, 20X Optical Zoom
- Pan 0° to 360°; Tilt -5° to 90°
- Up to 50m IR range, prevent IR reflection
- New-generation bubble, prevent blurs at any angle
- IP66; MIC: Customizable

DS-2DE4A204IW-DE

2MP 4X/20X Mini PTZ Dome Network Camera



- 2MP real-time, Pan 0° to 360°; Tilt -5° to 90°
- Up to 50m IR range, prevent IR reflection
- New-generation bubble, prevent blurs at any angle
- 4X (2.8 to 12mm) Optical Zoom
- DarkFighter
- IP66; MIC: Customizable

DS-2DY3320/3220-DE(4)

3MP/2MP 20X IR PTZ Bullet Network Camera



- 3MP/2MP real-time, 20X Optical Zoom
- -40°~30° tilt range, 360° endless pan range
- 3D intelligent positioning
- Up to 100m IR range
- Wall-mount/Stand-Mount

DS-2DE2204IW-DE3

2MP 4X mini PTZ network camera



- 2MP real-time
- 4X Optical Zoom
- 3D intelligent positioning
- Privacy mask
- PoE / 12VDC

DS-2DE3304W/3204-DE

3MP/2MP 4X Mini PTZ Network Camera



- 3MP/2MP real-time
- 4X Optical Zoom
- 3D intelligent positioning
- Privacy mask
- PoE/12VDC
- IP66 protection

DS-2DE7230/7220IW-AE

2MP 30X/20X IR PTZ network camera



- 1920*1080P Full HD, 30X/20x Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- Up to 150m IR distance
- 24VAC / High-PoE

DS-2DE7430/7530IW-AE

1.3MP 30X/20X IR PTZ network camera



- 4/5MP HD, 30X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- Up to 150m IR distance
- 24VAC / High-PoE

DS-2DE5230/5220W-AE(3)

2MP 30X/20X PTZ Dome Network Camera



- 1920*1080P Full HD, 30X/20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- 24VAC / High-PoE

DS-2DE5130/5120W-AE(3)

1.3MP 30X/20X PTZ network camera



- 1280*960P HD, 30X/20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- 24VAC / High-PoE

DS-2DE5220IW-AE

2MP 20X IR PTZ Network Camera



- 5-inch sized IR PTZ
- 2MP real-time, 20X Optical Zoom
- 3D DNR, DWDR, ICR
- Alarm input/output, privacy mask
- Up to 150m IR
- 24VAC/PoE+

DS-2DE5120I-AE

1.3MP 20X IR PTZ Network Camera



- 5-inch sized IR PTZ
- 1.3MP real-time, 20X Optical Zoom
- 3D DNR, DWDR, ICR
- Alarm input/output, privacy mask
- Up to 150m IR
- 24VAC/PoE+

DS-2DE4220IW-D

2MP 20X IR PTZ network camera



- 4-inch sized IR PTZ
- 2MP real-time, 20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output, privacy mask
- Up to 100m IR
- 12VDC power

PTZ CAMERA

DS-2DE4120I-D

1.3MP 20X IR PTZ network camera



- 4-inch sized IR PTZ
- 1.3MP real-time, 20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output, privacy mask
- Up to 100m IR
- 12VDC power

DS-2DE4220W/4120-AE(3)

2MP/1.3MP 20X PTZ Network Camera



- 4-inch bubble
- 2MP/ 1.3MP real-time, 20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output, privacy mask
- 24VAC/PoE+

TURBO HD PTZ

DS-2AE5223TI/5123TI-A

1080P/720P 23X IR PTZ Analog Camera



- 1080P/720P video output
- 23X optical zoom
- Up the coaxial function
- Privacy masking
- Up to 150m IR distance

DS-2AE4223TI/4123TI-D

1080P/720P 23X PTZ IR Analog Camera



- 1080P/720P video output
- 23X optical zoom
- Up the coaxial function
- Privacy masking
- Up to 100m IR distance
- 12VDC

DS-2AE7230TI-A

1080P 30X PTZ IR Analog Camera



- 1080P video output
- 30X optical zoom
- Up the coaxial function
- Privacy masking
- Up to 150m IR distance

DS-2AE7123TI-A

720P 23X PTZ IR Analog Camera



- 720P video output
- 23X optical zoom
- Up the coaxial function
- Privacy masking
- Up to 150m IR distance

DS-2AE5230T-A(3)

1080P 30X PTZ Dome Analog Camera



- 1080P video output
- 30X optical zoom
- Up the coaxial function
- Privacy masking

DS-2AE5123T-A(3)

720P 23X PTZ Dome Analog Camera



- 720P video output
- 23X optical zoom
- Up the coaxial function
- Privacy masking

PanoVu NETWORK CAMERA

DS-2DP1636Z-D

16MP 360° panoramic + 2MP 23x PTZ network camera



Panoramic features

- 8 x 1/1.9" CMOS sensor, 2-ch 4096×1800 realtime videop output
- Horizontal angle of view: 360°, Vertical angle of view: 78°
- DarkFighter ultra-low light technology
- PTZ features**
- 1/1.9"CMOS sensor, 1920×1080 resolution@30fps
- 23X optical zoom, 16X digital zoom
- smart tracking, smart detection
- DarkFighter ultra-low light technology

DS-2DP0818Z-D

8MP 180° panoramic + 2MP 23x PTZ network camera



Panoramic features

- 8 x 1/1.9" CMOS sensor, 1-ch 4096×1800 realtime videop output
- Horizontal angle of view: 180°, Vertical angle of view: 78°
- DarkFighter ultra-low light technology
- PTZ features**
- 1/1.9"CMOS sensor, 1920×1080 resolution@30fps
- 23X optical zoom, 16X digital zoom
- smart tracking, smart detection
- DarkFighter ultra-low light technology

DS-2DP1636-D

16MP 360° panoramic network camera



- 8 x 1/1.9" CMOS sensor, 2-ch 4096×1800 realtime videop output
- Horizontal angle of view: 360°, Vertical angle of view: 78°
- DarkFighter ultra-low light technology

DS-2CD6986F-H

8MP 180° panoramic network camera



- 4 x 1/1.9" CMOS sensors, 1-ch 4096×1800 realtime video output
- 180° horizontal panoramic view
- DarkFighter ultra-low light technology

PTZ POSITIONING SYSTEM

DS-2DY5223IW-AE

DarkFighter 2MP 23X Pan-Tilt Positioning Network Camera



- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X optical Zoom
- -90°~90° tilt range, 360° endless pan range
- 3D intelligent positioning
- 120dB WDR
- Up to 150m IR distance
- Vandal-proof (IK10)

DS-2DY9185-A(I2)

DarkFighter 2MP 23X Pan-Tilt Positioning Network Camera



- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X optical Zoom
- -90°~40° tilt range, 360° endless pan range
- 120dB WDR
- Up to 200m IR distance(optional)

DS-2DY9188-A(I2)(I8)

DarkFighter 2MP 36X Pan-Tilt Positioning Network Camera



- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 36X optical Zoom
- -90°~40° tilt range, 360° endless pan range
- 120dB WDR
- Up to 200m IR distance(optional)
- Up 800m laser IR distance(optional)

DS-2DY9187-AI8

2MP 32X Pan-Tilt Positioning Network Camera



- 1920*1080P Full HD, 32X optical Zoom
- -90°~40° tilt range, 360° endless pan range
- 120dB WDR
- Up 800m laser IR distance

NETWORK CAMERA



EasyIP 3.0 NETWORK CAMERA

DS-2CD2085FWD-I

8MP EXIR Mini Bullet network camera



H.265+

- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67;
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2185FWD-I(S)

8MP EXIR Dome network camera



H.265+

- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2385FWD-I

8MP EXIR Turret network camera



H.265+

- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67;
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T85FWD-I(5/8)

8MP EXIR Bullet network camera



H.265+

- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67;
- 3 streams;
- I5: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2055FWD-I

5MP EXIR Mini Bullet network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2155FWD-I(S)

5MP EXIR Dome network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2355FWD-I

5MP EXIR Turret network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T55FWD-I(5/8)

5MP EXIR Bullet network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- I5: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2035FWD-I

3MP EXIR Mini Bullet network camera



H.265+

- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2135FWD-I(S)

3MP EXIR Dome network camera



H.265+

- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2335FWD-I

3MP EXIR Turret network camera



H.265+

- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T35FWD-I(5/8)

3MP EXIR Bullet network camera



H.265+

- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- I5: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2025FWD-I

2MP EXIR Mini Bullet network camera



H.265+

- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2125FWD-I(S)

2MP EXIR Dome network camera



H.265+

- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2325FWD-I

2MP EXIR Turret network camera



H.265+

- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T25FWD-I(5/8)

2MP EXIR Bullet network camera



H.265+

- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- I5: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

NETWORK CAMERA

DS-2CD2685FWD-Izs

8MP Vari-focal EXIR Bullet network camera



H.265+

- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2655FWD-Izs

5MP Vari-focal EXIR Bullet network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2635FWD-Izs

3MP Vari-focal EXIR Bullet network camera



H.265+

- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2625FWD-Izs

2MP Vari-focal EXIR Bullet network camera



H.265+

- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2785FWD-Izs

8MP Vari-focal EXIR Dome network camera



H.265+

- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2755FWD-Izs

5MP Vari-focal EXIR Dome network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2735FWD-Izs

3MP Vari-focal EXIR Dome network camera



H.265+

- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2725FWD-Izs

2MP Vari-focal EXIR Dome network camera



H.265+

- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H85FWD-Izs

8MP Vari-focal EXIR Turret network camera



H.265+

- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H55FWD-Izs

5MP Vari-focal EXIR Turret network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H35FWD-Izs

3MP Vari-focal EXIR Turret network camera



H.265+

- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H25FWD-Izs

2MP Vari-focal EXIR Turret network camera



H.265+

- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2955FWD-I(S)

5MP EXIR Fisheye network camera



H.265+

- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 1.05 mm @ F2.2, horizontal field of view: 180°, vertical field of view: 180°
- 120dB WDR
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2935FWD-I(S)

3MP EXIR Fisheye network camera



H.265+

- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 1.16 mm @ F2.2, horizontal field of view: 180°, vertical field of view: 180°
- 120dB WDR
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

NETWORK CAMERA



EasyIP 2.0 WDR NETWORK CAMERA

DS-2CD2022/42WD-I(W)(S)
2MP/4MP WDR IR Mini Bullet Network Camera



- 2MP/4MP real-time resolution
- Intrusion & line crossing detection
- 120dB WDR
- On-board storage(optional)
- Up to 30m IR range
- DC12V & PoE
- Metallic housing, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2122/42WD-I(W)(S)

2MP/4MP WDR IR Fixed Dome Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- 3-axis adjustment
- On-board storage(optional)
- Up to 30m IR range
- DC12V & PoE
- Vandal-proof metallic housing, IP67
- Cloud P2P mobile surveillance

DS-2CD2T22/42WD-I(S)(I8)

2MP/4MP WDR EXIR Bullet Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- Up to 50m/80m IR range
- DC12V & PoE
- IP67
- Hik-connect cloud mobile surveillance

DS-2CD2322/42WD-I

2MP/4MP WDR EXIR Turret Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- Up to 30m IR range
- DC12V & PoE
- Plastic housing, Vandal-proof, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2422/42FWD-IW

2MP/4MP WDR IR Cube Network Camera



- 2MP/4MP real-time resolution
- On-board storage(optional)
- PIR detection
- Up to 10m IR range
- 120dB WDR
- DC12V & PoE
- Built-in Speaker, Mic, WiFi
- Hik-connect cloud mobile surveillance

DS-2CD2522/42FWD-I(W)(S)

2MP/4MP WDR Mini Dome Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- 3-axis adjustment
- On-board storage
- Up to 10m IR range
- DC12V & PoE
- IK8 protection, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2F22/42FWD-I(W)(S)

4MP WDR IR Mini PT Network Camera



- 2MP/4MP real-time resolution
- Intrusion & line crossing detection
- 120dB WDR
- Pan & tilt rotation, easy-to-adjust
- On-board storage
- Up to 10m IR range
- Built-in Wi-Fi (optional)
- Hik-connect cloud mobile surveillance

DS-2CD2942F-I(W)(S)

4MP 180° Panoramic Network Camera



- 4MP high resolution
- 180° horizontal panoramic view
- ePTZ control
- Compact design
- IR, WiFi, Audio & alarm optional

DS-2CD2622/42FWD-I(Z)(S)

2MP/4MP WDR Vari-focal IR Bullet Network Camera



- 2MP/4MP real-time resolution
- 2.8-12mm motorized(-Z) VF lens
- 120dB WDR
- On-board storage
- Up to 30m IR range
- DC12V & PoE
- Metallic housing, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2722/42FWD-I(Z)(S)

2MP/4MP WDR Vari-focal IR Dome Network Camera



- 2MP/4MP real-time resolution
- 2.8-12mm motorized(-Z) VF lens
- 120dB WDR
- On-board storage
- Up to 30m IR range
- Metallic housing, IP67
- Hik-connect cloud mobile surveillance

DS-2CD4B26FWD-I(Z)(S)

DarkFighter Lite Series 2MP Bullet Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Color:0.002Lux/F1.2, B/W:0.0002Lux/F1.2
- Full HD1080P
- 120dB WDR
- Up to 128GB on-board storage
- Up to 120m IR range
- IP67

DS-2CD4B36FWD-I(Z)(S)

DarkFighter Lite Series 1.3MP Bullet Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/2.8" progressive scan CMOS sensor
- Color:0.005Lux/F1.2, B/W:0.0005Lux/F1.2
- 3MP high resolution
- 120dB WDR
- Up to 128GB on-board storage
- Up to 120m IR range
- IP67

DS-2CD4C36FWD-(AP)

DarkFighter series 3MP Box network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- DarkFighter ultra-low light technology
- 1/2.8" progressive scan CMOS sensor
- 3MP high resolution
- 120dB WDR
- Intrusion & line crossing & object removal & unattended baggage & face detection&Region Entrance/Left&Scene Change
- Up to 128GB on-board storage

DS-2CD4C26FWD-(AP)

DarkFighter series 2MP Box network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080P
- 120dB WDR
- Intrusion & line crossing & object removal & unattended baggage & face detection&Region Entrance/Left&Scene Change
- Up to 128GB on-board storage

DS-2CD4D26FWD-I(Z)(S)

DarkFighter Lite Series 2MP Dome Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Color:0.002Lux/F1.2, B/W:0.0002Lux/F1.2
- Full HD1080P
- 120dB WDR
- Up to 128GB on-board storage
- EXIR, prevent IR reflection
- IP66

DS-2CD4D16FWD-I(Z)(S)

DarkFighter Lite Series 1.3MP Dome Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/3" progressive scan CMOS sensor
- Color:0.005Lux/F1.2, B/W:0.0005Lux/F1.2
- 3MP high resolution
- 120dB WDR
- Up to 128GB on-board storage
- EXIR, prevent IR reflection
- IP66

NETWORK CAMERA

4-LINE SMART NETWORK CAMERA

DS-2CD4A24FWD-I(H)(S)
2MP 20X Zoom Bullet Network Camera



- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 4.7-94mm 20X optical zoom Smart Focus
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 120m IR range
- IP67

DS-2CD4026FWD(-AP)

DarkFighter Series 2MP Box Network Camera



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Auto back focus
- P-Iris optional

DS-2CD4126FWD-IZ

DarkFighter Series 2MP Indoor Dome Network Camera



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A26FWD-I(H)(S)

DarkFighter Series 2MP Bullet Network Camera



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4526FWD-I(H)(M)

DarkFighter Series 2MP Dome Network Camera



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66
- HDMI interface optional

DS-2CD4626FWD-I(H)(S)

DarkFighter Series 2MP Bullet Network Camera



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

DS-2CD4025FWD(-AP)

LightFighter Series 2MP Indoor Box Network Camera



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Auto back focus
- P-Iris optional

DS-2CD4125FWD-IZ

LightFighter Series 2MP Indoor Dome Network Camera



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A25FWD-I(H)(S)

LightFighter Series 2MP Bullet Network Camera



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4526FWD-I(H)(M)

LightFighter Series 2MP Dome Network Camera



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

DS-2CD4626FWD-I(H)(S)

Lightfighter Series 2MP Bullet Network Camera



- Lightfighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

DS-2CD4035FWD(-AP)

3MP Indoor Box Network Camera



- 1/2.8" progressive scan CMOS sensor
- 3MP@45fps resolution
- 120dB WDR
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD4135FWD-IZ

3MP Indoor IR Dome Network Camera



- 1/2.8" progressive scan CMOS sensor
- 3MP@45fps resolution
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A35FWD-I(H)(S)

3MP IR Bullet Network Camera



- 1/2.8" progressive scan CMOS sensor
- 3MP@45fps resolution
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4565F-I(H)

6MP IR Dome Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

DS-2CD4665F-I(H)(S)

6MP IR Bullet Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

NETWORK CAMERA



DS-2CD4065F-(AP)

6MP Indoor Box Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD4165FWD-IZ

6MP Indoor IR Dome Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A65F-I(H)(S)

6MP IR Bullet Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4085F-(AP)

8MP Indoor Box Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD4185FWD-IZ

6MP Indoor IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A85F-I(H)(S)

8MP IR Bullet Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4585F-I(H)

8MP IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

DS-2CD4685F-I(H)(S)

8MP IR Bullet Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

DS-2CD40C5F-(AP)

12MP Indoor Box Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD41C5F-IZ

12MP Indoor IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4AC5F-I(H)(S)

12MP IR Bullet Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD45C5F-I(H)

12MP IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

6-LINE NETWORK CAMERA

DS-2CD63C2F-II(V)(S)

12MP Panoramic IR Network Camera



- 360° panoramic view
- Up to 4000x3072@20fps resolution
- Up to 1600x1200 ePTZ control
- Heat mapping analytic
- Support on-board hardware de-warping
- Support software de-warping
- IP66 & Vandal-proof (-V)
- Up to 15m IR

DS-2CD6362F-II(V)(S)

6MP Panoramic IR Network Camera



- 360° panoramic view
- Up to 3072x2048 resolution
- ePTZ control
- 120dB WDR
- Support on-board hardware de-warping
- Support software de-warping
- IP66 & Vandal-proof (-V)
- Up to 15m IR

DS-2CD6332F-II(V)(S)

3MP Panoramic IR Network Camera



- 360° panoramic view
- Up to 2048x1536 resolution
- ePTZ control
- 120dB WDR
- Support on-board hardware de-warping
- Support software de-warping
- IP66 & Vandal-proof (-V)
- Up to 15m IR

DS-2CD6426FWD-50

DarkFighter Series 2MP Mini Bullet Covert Network Camera



- Ultra-low illumination technology
- 1/1.8" progressive CMOS sensor
- 2MP real-time resolution
- 120dB WDR
- Full Smart Feature-set
- Up to 128GB on-board storage
- Mini bullet part support IP66

NETWORK CAMERA

DS-2CD6424FWD-10/20/30
2MP Covert Network Camera



- 2MP real-time resolution
- 120dB WDR
- Up to 128GB on-board storage
- Pinhole lens (-10/20)
- Fixed tube lens (-30)

DS-2CD6424FWD-40/E1(E2)
2MP Covert Network Camera



- 2MP real-time resolution
- 120dB WDR
- Up to 128GB on-board storage
- Mini ball lens (-40/E1)
- Embedded lens (-40/E2)

MOBILE NETWORK CAMERA

DS-2XM6122FWD-I(M)
2MP Vehicle Mini Dome network camera



- Special design for vehicle-mounted
- 2MP realtime resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- 120dB WDR
- IP66, IK8
- EN50155, EN50121 certification
- Build-in microphone
- Multiple smart events supported

DS-2CD6520ET-I(O)
2MP Outer-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 2MP real time resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- Up to 30m IR range
- IP68, IK10
- EN50155, EN50121 certification

DS-2CD6510-I(O)
1.3MP Outer-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 1.3MP real time resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- Up to 30m IR range
- IP68, IK10
- EN50155, EN50121 certification

DS-2CD6520DT-I(O)
2MP Inner-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 2MP realtime resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- IP54, IK8
- EN50155, EN50121 certification

DS-2CD6510DT-I(O)
1.3MP Inner-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 1.3MP real time resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- IP54, IK8
- EN50155, EN50121 certification

**DS-2XM6612FWD-I (1.3MP)
DS-2XM6622FWD-I (2.0MP)**
Mobile Network Camera



- HD720p or Full HD1080p video
- 120dB WDR
- Smart IR, up to 3m IR range
- Up to 128GB on-board storage
- Built-in Microphone

EXPLOSION-PROOF & ANTI-CORROSION NETWORK CAMERA

DS-2XE6222F-IS
2MP Explosion-Proof Dome network camera



- H.265+/H.264+/H.265/H.264
- 2MP realtime resolution
- 120dB WDR
- ATEX, IECEx, IP68
- 316L Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- Support on-board storage, up to 128GB
- AC 100V to 240V/PoE

DS-2XE6242F-IS
4MP Explosion-Proof Bullet network camera



- H.265+/H.264+/H.265/H.264
- 4MP high resolution
- 120dB WDR
- 316L Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- Support on-board storage, up to 128GB
- AC 100V to 240V/PoE

DS-2DF6223-CX(W)
DarkFighter series 2MP Anti-corrosion PTZ network camera



- 2MP 1/1.8" progressive scan CMOS
- 23x optical zoom
- 120dB WDR
- Explosion-Proof: II 2 G Ex d IIC T6 Gb, Ta -40°
- C to +60°C; II 2 D Ex tb IIIC T80° C Db
- IP68 standard

DS-2CD6626DS-IZ(H)S
DarkFighter Series 2MP Anti-corrosion Dome Network Camera



- Ultra-low illumination technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 2.8-12mm motorized VF lens
- 120dB WDR
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

DS-2CD6626BS-R
DarkFighter Series 2MP Anti-corrosion Bullet Network Camera



- Ultra-low illumination technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 120dB WDR
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

DS-2CD6626B/E-HIR5/IRA
DarkFighter Series 2MP Anti-corrosion IR Bullet Network Camera



- Ultra-low illumination technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 120dB WDR
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification
- IR5: 3.8-16mm VF lens, up to 50m IR range
- IRA: 11-40mm VF lens, up to 100 IR range

DS-2CD6626B-IZHS
DarkFighter series 2MP Anti-corrosion IR Bullet network camera



- DarkFighter ultra-low light technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 120dB WDR
- Motorized lens with Smart Focus
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

DS-2CD6652B-IZHS
DarkFighter series 2MP Anti-corrosion IR Bullet network camera



- 5MP 2592 × 1944@60 fps
- 316L stainless steel housing
- 120dB WDR
- Motorized lens with Smart Focus
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

NETWORK CAMERA



DS-2XC6122FWD-IS

DarkFighter series 2MP Anti-corrosion
Dome network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- 2MP realtime resolution
- 120dB WDR
- Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- IP67
- Support on-board storage, up to 128GB

DS-2XC6142FWD-IS

DarkFighter series 2MP Anti-corrosion
Dome network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- 4MP realtime resolution
- 120dB WDR
- Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- IP67
- Support on-board storage, up to 128GB

ANPR NETWORK CAMERA

**DS-2CD4026FWD/P-IR5
(3.8-16mm) /IRA(11-40mm)**

2MP Low Light Smart Box LPR Camera with
housing



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 50m/100m IR range

**DS-2CD4026FWD/P-(H)(N)RA
(11-40mm)**

2MP Low Light Smart Box LPR Camera with
housing



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 30m light range

**DS-2CD4026FWD/P-L
(3.8-16mm)(11-40mm)(7-33mm)**

2MP Low Light Smart Box LPR Camera
with housing



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 30m light range

**DS-2CD4A26FWD-IZ(S)(H)/P
(2.8-12mm)/(8-32mm)(-WG)**

2MP Low Light Smart Bullet LPR Camera



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

**DS-2CD4A26FWD-LZS/P
(2.8-12mm)**

2MP Low Light Smart Bullet LPR Camera



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range

**DS-2CD4626FWD-IZ(HS)/P
(2.8-12mm)**

2MP Low Light Smart Bullet LPR Camera



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- IP67; IK10

THERMAL CAMERA

DS-2TD2136-7/10/15/25/35

DS-2TD2136T-10/15/25

Thermal Network Single-lens



- Thermal: 384×288
- 7mm(60°)/10mm(36°)/15mm (24°)/ 25mm(15°)/ 35mm (11°) thermal lens optional
- Main/Sub/Third stream in max resolution at 50fps
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- -T: -20°C ~ 550°C (-4°F to 1,022°F) temperature Range, Max(±2°C ,±2%) temperature accuracy (only DS-2TD2136T support)
- IP66

DS-2TD2166-7/15/25/35

DS-2TD2166T-15/25

Thermal Network single-lens Bullet Camera



- Thermal: 640×512
- 7mm (88°)/ 15mm (39°)/ 25mm (24°)/35mm (17°) thermal lens optional
- Main/Sub/Third stream in max resolution at 50fps
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- -T: -20°C ~ 550°C (-4°F to 1,022°F) temperature Range, Max(±2°C ,±2%) temperature accuracy (only DS-2TD2136T support)
- IP66

DS-2TD2336-50/75/100

Thermal Network Single-lens

Bullet Camera(Long focal lens)



- Thermal: 384×288
- 50mm (7.47°)/ 75mm (4.98°)/100mm (3.74°) thermal lens optional
- Support auto-focus
- Main/Sub/Third stream in max resolution at 50fps
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- IP66

DS-2TD2366-50/75/100

Thermal Network Single-lens
Bullet Camera(Long focal lens)



- Thermal: 640×512
- 50mm (12.42°)/ 75mm (8.30°)/100mm (6.23°) thermal lens optional
- Support auto-focus
- Main/Sub/Third stream in max resolution at 50fps
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- IP66

DS-2TD2466-25/50

Thermal Network Single-lens
Bullet Camera(Anti-corrosion)



- Thermal: 640×512
- 25mm (24°)/ 50mm (12.42°) thermal lens optional
- Support auto-focus
- Main/Sub/Third stream in max resolution at 50fps
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- 316L stainless steel housing
- IP66

DS-2TD2235D-25/50

Thermal + Visible Bi-spectrum
Network Bullet Camera



- Thermal: 384×288, Visible: 1920×1080
- Thermal: 25mm (21.7°)/ 50mm (11°) thermal lens optional
- Darkfighter Ultra low light, Min. Illumination 0.002lux(color)
- Support line crossing and intrusion
- Support temperature exception alarm
- Support fire detection
- up to 120m IR
- IP66

NETWORK CAMERA

DS-2TD4035D-25/50

Thermal + Visible Bi-spectrum
Network Speed Dome



- Thermal: 384×288, Visible: 1920×1080
- Thermal: 25mm (21.7°) / 50mm (11°) thermal lens optional
- Visible: 4.3-129mm vari-focal lens, 30x optical zoom
- 360°endless pan range, -15°~ 90° tilt range
- Support line crossing and intrusion, which can be linked to auto tracking
- Support temperature exception alarm
- Support fire detection
- up to 150m IR
- IP66

DS-2TD4166-25/50

Thermal + Visible Bi-spectrum
Network Speed Dome



- Thermal: 640×512, Visible: 1920×1080
- Thermal: 25mm (24°) / 50mm (12.42°) thermal lens optional
- Visible: 5.7-205.2 mm vari-focal lens, 36x optical zoom
- Darkfighter Ultra low light, Min. Illumination 0.002lux(color)
- 360°endless pan range, -15°~ 90° tilt range
- Support line crossing and intrusion, which can be linked to auto tracking
- Support temperature exception alarm
- Support fire detection
- up to 150m IR
- IP66

DS-2TD4136-25/50

Thermal + Visible Bi-spectrum
Network Speed Dome



- Thermal: 384×288, Visible: 1920×1080
- Thermal: 25mm (15°) / 50mm (7.47°) thermal lens optional
- Visible: 5.7-205.2 mm vari-focal lens, 36x optical zoom
- Darkfighter Ultra low light, Min. Illumination 0.002lux(color)
- 360°endless pan range, -15°~ 90° tilt range
- Support line crossing and intrusion, which can be linked to auto tracking
- Support temperature exception alarm
- Support fire detection
- up to 150m IR
- IP66

DS-2TD6135-50/75B2L DS-2TD6166-50/75B2L

Thermal + Visible Bi-spectrum Network PTZ Camera



- Thermal: 384×288/640×512, Visible: 1920×1080
- Visible: 8-250mm vari-focal lens, 32x optical zoom
- Thermal: 50mm [6135: 11°, 6166: 12.4°] / 75mm [6135: 7.3°, 6166: 8.3°] thermal lens optional
- 360°endless pan range, +40°~-90° tilt range
- Support line crossing and intrusion detection with smart tracking linkage
- Support temperature exception alarm
- Support fire detection
- up to 500m IR
- IP66

DS-2TD6135T-25/50A2L

Thermometric Thermal + Optical Bi-spectrum Network PTZ Camera



- Thermal: 384×288, Visible: 1920×1080
- Visible: 4.3-129mm vari-focal lens, 30x optical zoom
- Thermal: 25mm [21.74°] / 50mm [10.97°] thermal lens optional
- 360°endless pan range, +40°~-90° tilt range
- -20°C ~ 550°C (-4°F to 1,022°F) temperature Range, Max(±2°C ,±2%) temperature accuracy
- Support line crossing and intrusion detection with smart tracking linkage
- Support fire detection
- up to 150m IR
- IP66

DS-2TD6236-50H2L/75C2L

Thermal + Visible Bi-spectrum Network PTZ Camera



- Thermal: 384×288, Visible: 1920×1080
- Thermal: 50mm (7.47°) / 75mm (4.98°) thermal lens optional
- Visible: 5.7-205.2mm / 6.7-330 mm vari-focal lens, 36x / 49x optical zoom optional
- 360°endless pan range, +40°~-90° tilt range
- Support line crossing and intrusion detection with smart tracking linkage
- Support temperature exception alarm
- Support fire detection
- up to 500m Laser
- IP66

DS-2TD6266-50H2L/75C2L/100C2L

Thermal + Visible Bi-spectrum Network PTZ Camera



- Thermal: 640×512, Visible: 1920×1080
- Thermal: 50mm (12.42°) / 75mm (8.30°) / 100mm (6.23°) thermal lens optional
- Visible: 5.7-205.2mm / 6.7-330 mm vari-focal lens, 36x / 49x optical zoom optional
- 360°endless pan range, +40°~-90° tilt range
- Support line crossing and intrusion detection with smart tracking linkage
- Support temperature exception alarm
- Support fire detection
- up to 500m Laser
- IP66

DS-2TD8166-75/100C2F DS-2TD8166-150/180ZE2F

Thermal + Visible Bi-spectrum Network Positioning System



- Thermal: 640×512, Visible: 1920×1080
- Thermal: 75mm / 100mm fixed thermal lens 30-150mm/45-180mm vari-focal thermal lens optional
- Visible lens: 6.7-330 mm, 12.5-750mm vari-focal lens optional
- 360°endless pan range, +45°~-45° tilt range
- 0.01°/s to 40°/s pan speed, 0.01°/s to 20°/s tilt speed
- Support line crossing and intrusion detection with smart tracking linkage
- Support temperature exception alarm
- Support fire detection
- Laser module optional, up to 3km
- IP66

DS-2TP03-15VM/W

Handheld Thermometric Thermal Camera



- Thermal: 384×288 17μm, Visible: 8MP
- 15mm (25°) thermal lens
- 3.6-inch LCD Capacitive Touch Panel 320×240
- -20°C ~ 550°C (-4°F to 1,022°F) temperature Range
- Max(±2°C ,±2%) temperature accuracy
- 64GB SD card
- >4 hours operating time
- IP66

DS-2TS03-025UM/W

Handheld Observational Thermal Camera



- Thermal: 384×288
- 25mm (15°) thermal lens
- 0.39" OLED, 1024×768
- Built-in memory module (16GB)
- Hot spot tracking
- Support Wi-Fi
- Support Hik-Connect
- >5 hours operating time
- IP67
- 2m fall resistant level

TURBO HD ANALOG CAMERA



TURBO HD 5MP EXIR CAMERA

DS-2CE16H1T-IT
Outdoor EXIR Bullet



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56H1T-ITM
Outdoor EXIR Eyeball



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16H1T-IT1/3/5
Outdoor EXIR Bullet



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56H1T-IT1/3
Outdoor EXIR Eyeball



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20/40m IR distance
- IP66 weatherproof

DS-2CE16H1T-(A)IT3Z

Outdoor EXIR Motorized Vari-focal Bullet



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56H1T-IT3Z

Outdoor EXIR Motorized Vari-focal Eyeball



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof

DS-2CE56H1T-(A)ITZ

Indoor EXIR Motorized Vari-focal Dome



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56H1T-(A)VPT3Z

Outdoor EXIR Motorized Vari-focal Dome



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

TURBO HD 3MP WDR EXIR CAMERA

DS-2CE16F7T-IT
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56F7T-ITM
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56F7T-VPIT

Outdoor Vandalproof EXIR Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16F7T-IT1/3/5

Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56F7T-IT1/3
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66 weatherproof

DS-2CE16F7T-IT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66 weatherproof

DS-2CE16F7T-AIT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE56F7T-IT3Z
Outdoor EXIR Motorized Vari-focal Eyeball



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof

TURBO HD ANALOG CAMERA

DS-2CE56F7T-ITZ

Indoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance

DS-2CE56F7T-AITZ

Indoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE56F7T-VPIT3Z

Outdoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof

DS-2CE56F7T-AVPI3Z

Outdoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC

TURBO HD 3MP EXIR CAMERA

DS-2CE16F1T-IT

Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56F1T-ITM

Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16F1T-IT1/3/5

Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56F1T-IT1/3

Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66 weatherproof

TURBO HD 1080P Starlight+PoC CAMERA

DS-2CC12D9T-IT3

HD1080P Starlight+ POC Bullet



- Built-in PoC(Power over Coax)
- True Day/Night,
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 40m IR distance
- IP66 weatherproof

DS-2CC52D9T-IT3

HD1080P Starlight+ POC Eyeball



- Built-in PoC(Power over Coax)
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 40m IR distance
- IP66 weatherproof

DS-2CC12D9T-AIT3ZE

HD1080P Starlight+ POC Vari-focal Bullet



- Built-in PoC(Power over Coax)
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

DS-2CC52D9T-AVPI3ZE

HD1080P Starlight+ POC Vari-focal Dome



- Built-in PoC(Power over Coax)
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC

Turbo HD HD1080P EXIR PoC Cameras

DS-2CC52D9T-AITZE

HD1080P Starlight+ POC Vari-focal Dome



- Built-in PoC(Power over Coax)
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE56D8T-(A)VPIT3Z

Outdoor EXIR Motorized VF Auto Focus Dome



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 2.8-12mm motorized auto focus Lens
- 40m IR distance
- Vandalproof & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE16D8T-ITE

Outdoor EXIR Bullet



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- Up to 20m IR distance
- Built-in PoC & IP66 weatherproof

DS-2CE56D8T-ITME

Outdoor EXIR Eyeball



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- Up to 20m IR distance
- Built-in PoC & IP66 weatherproof

TURBO HD ANALOG CAMERA



DS-2CE56D8T-VPITE
Outdoor Vandalproof EXIR Dome



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- Up to 20m IR distance
- Built-in PoC & IP66 weatherproof

DS-2CE16D8T-IT1/3/5E
Outdoor EXIR Bullet



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 20/40/80m IR distance
- Built-in PoC & IP66 weatherproof

DS-2CE56D8T-IT1/3E
Outdoor EXIR Eyeball



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 20/40m IR distance
- Built-in PoC & IP66 weatherproof

DS-2CE16D8T-(A)IT3ZE
Outdoor EXIR Motorized VF Auto Focus Bullet



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- 2.8-12mm motorized auto focus Lens
- Ultra low illumination 0.005 lux/F1.2
- 40m IR distance
- IP66 weatherproof
- Built-in PoC, 12 VDC/ 24 VAC (-A model only)

DS-2CE56D8T-IT3ZE
Outdoor EXIR Motorized VF Auto Focus Eyeball



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 2.8-12mm motorized auto focus Lens
- 40m IR distance
- Built-in PoC & IP66 weatherproof

DS-2CE56D8T-(A)ITZE
Indoor EXIR Motorized VF Auto Focus Dome



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Built-in PoC, 12 VDC/ 24 VAC (-A model only)

DS-2CE56D8T-(A)VPIT3ZE
Outdoor EXIR Motorized VF Auto Focus Dome



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 2.8-12mm motorized auto focus Lens
- 40m IR distance
- Vandalproof & IP66 weatherproof
- Built-in PoC, 12 VDC/ 24 VAC (-A model only)

Turbo HD HD1080P Ultra Lowlight EXIR Cameras

DS-2CE16D8T-IT(P)
Outdoor EXIR Bullet



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- Up to 20m IR distance

DS-2CE56D8T-ITM
Outdoor EXIR Eyeball



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- Up to 20m IR distance

DS-2CE56D8T-VPIT
Outdoor Vandalproof/EXIR Dome



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56D8T-(A)ITZ
Indoor EXIR Motorized VF Auto Focus Dome



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE16D8T-IT1/3/5
Outdoor EXIR Bullet



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56D8T-IT1/3
Outdoor EXIR Eyeball



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 20/40m IR distance
- IP66 weatherproof

DS-2CE16D8T-(A)IT3Z
Outdoor EXIR Motorized VF Auto Focus Bullet



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- 2.8-12mm motorized auto focus Lens
- Ultra low illumination 0.005 lux/F1.2
- 40m IR distance
- IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D8T-IT3Z
Outdoor EXIR Motorized VF Auto Focus Eyeball



- Turbo HD output, up to HD1080p resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- Ultra low illumination 0.005 lux/F1.2
- 2.8-12mm motorized auto focus Lens
- 40m IR distance
- IP66 weatherproof

TURBO HD ANALOG CAMERA

DS-2CE16D7T-IT
Outdoor EXIR Bullet



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56D7T-ITM
Outdoor EXIR Eyeball



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56D7T-VPIT
Outdoor Vandalproof EXIR Dome



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16D7T-IT1/3/5
Outdoor EXIR Bullet



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56D7T-IT1/3
Outdoor EXIR Eyeball



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66 weatherproof

DS-2CE16D7T-(A)IT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D7T-IT3Z
Outdoor EXIR Motorized Vari-focal Eyeball



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof

DS-2CE56D7T-(A)ITZ
Indoor EXIR Motorized Vari-focal Dome



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D7T-(A)VPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof

TURBO HD1080P CAMERA

DS-2CE56DOT-IRMM
Indoor IR Dome



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56DOT-IRP
Indoor IR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE16DOT-IR(P)
Outdoor IR Bullet



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56DOT-IR
Outdoor IR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56DOT-IRM
Outdoor IR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE16DOT-IT1/3/5
Outdoor EXIR Bullet



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20/40/80m IR distance with EXIR
- IP66 weatherproof

DS-2CE56DOT-IT1/3
Outdoor EXIR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20/40m IR distance with EXIR
- IP66 weatherproof

TURBO HD ANALOG CAMERA



TURBO HD HD1080P WDR EXIR CAMERA

DS-2CC12D9T(-A)
HD1080P Box Camera



- True day/night
- 3D DNR, smart IR
- True WDR, up to 120dB
- OSD menu controlled via UTC
- Alarm input & output (DS-2CC12D9T-A)
- Dual voltage: 12 VDC / 24 VAC

DS-2CE16D9T-AIRAZH
HD1080P Outdoor Vari-focal Bullet Camera



- Turbo HD output, up to 1080P resolution
- 5 – 50mm motorized vari-focal lens
- True Day/Night
- Auto Focus, EXIR Technology
- OSD menu, 3D DNR, Smart IR
- True WDR, up to 120dB

DS-2CE56COT-IRMM
Indoor IR Dome



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56COT-IT1/3
Outdoor EXIR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20/40m IR distance with EXIR
- IP66 weatherproof

DS-2CE56COT-IRP
Indoor IR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE16COT-IR(P)
Outdoor IR Bullet



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56COT-IR(M)
Outdoor IR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16COT-IT1/3/5
Outdoor EXIR Bullet



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20/40/80m IR distance with EXIR
- IP66 weatherproof

NVR

DS-96128/256NI-I16/H

DS-96128/256NI-/24/H

Embedded H.265+ S 4K Super NVR



- 768Mbps Bit Rate input Max(up to 128/256 IP cameras input)
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264 video formats
- 68-ch 1080P decoding capability
- HDMI output at up to 4K resolution, 8 HDMI output
- Up to 16/24 SATA interfaces , up to 8 TB for each HDD, 4 Gigabit optical interfaces
- Redundant power supply to ensure system stability
- HDD hot swapping with RAID 0/1/5/6/10
- One LCD screen optional , mini SAS optional

DS-9664NI-I8

DS-9632NI-I8

DS-9616NI-I8

Embedded H.265+ 4K 2U NVR



- 320 Mbps Bit Rate Input Max(up to 16/32/64-ch IP cameras input)
- Third-party network cameras supported
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264/MPEG4 video formats
- 2-ch HDMI and 2-ch VGA outputs interfaces provided, HDMI1 output at up to 4K resolution
- 8 SATA,HDD hot swapping, 1 eSATA, 2 USB2.0, 1 USB3.0
- Support RAID0,1,5,6,10
- *Hot spare working mode

DS-7700NI-H4/8P

DS-7700NI-H4/16P

X86 open platform for software developers and integrators, PoE port



- Intel Celeron Processor(2M Cache, 2.00GHz)
- 300 Mbps Bit Rate input Max
- HDMI output resolution at up to 4MP, VGA output resolution at up to 2MP
- 4 hot-swappable SATA
- 4GB memory
- 2 USB 2.0 & 1 USB 3.0
- Alarm in/out : 16/4
- 1 RJ-45 10/100/1000 Mbps self-adaptive interface
- 8P/16P models support 8/16 independent 100M PoE network interfaces

DS-7732NI-E4(16P)

DS-7716NI-E4(16P)

Embedded 1.5U PoE NVR



- 160 Mbps Bit Rate input Max(up to 16/32-ch IP cameras input)
- Third-party network cameras supported
- Up to 6MP resolution recording
- Support H.264+/H.264/MPEG4 video formats
- HDMI and VGA output at up to 2M Resolution
- 4 SATA, 2 USB 2.0, 1 USB 3.0
- /16P series support 16 independent PoE network interfaces

DS-96128/256NI-I16

DS-96128/256NI-/24

Embedded H.265+ 4K Super NVR



- 576/768Mbps Bit Rate input Max(up to 128/256 IP cameras input)
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264 video formats
- 20-ch 1080P decoding capability
- HDMI output at up to 4K resolution
- Up to 16/24 SATA interfaces, up to 8 TB for each HDD,4 Gigabit optical interfaces
- Redundant power supply to ensure system stability
- HDD hot swapping with RAID 0/1/5/6/10
- One LCD screen optional , mini SAS optional

iDS-9632NXI-I8/16S

DeepInmind Series NVR



- False alarm filtering for up to 16 behavior detection channels
- 320/256 Mbps bitrate input/output (up to 32-ch. of IP camera input)
- Up to 12 MP resolution recording / live view
- H.265+/H.265/H.264+/H.264 video formats, self-adapting
- 1080p decoding capability on 8 channels
- HDMI output at up to 4K resolution
- Up to 8 SATA interfaces; up to 8 TB for each HDD
- HDD hot swapping with RAID 0, 1, 5, 6, 10

DS-9664NI-I16

DS-9632NI-I16

DS-9616NI-I16

Embedded H.265+ 4K 3U NVR



- 256/320 Mbps Bit Rate Input Max(up to 16/32/64-ch IP cameras input)
- Third-party network cameras supported
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- 2-ch HDMI and 2-ch VGA outputs interfaces provided, HDMI1 output at up to 4K resolution
- 16 SATA, HDD hot swapping , 1 eSATA,2 USB2.0, 1 USB3.0
- Support RAID0,1,5,6,10
- *Hot spare working mode

DS-9000AI-S16-D

NVR+X86 , compatible with third-party VMS and worked as a workstation, Redundant power supply



- 576Mbps Bit Rate input Max(up to 128-ch IP cameras input)

- Up to 20-ch decoding capacity at 1080p resolution
- Redundant power supply
- Support RAID 0/1/5/6/10
- Server board: Intel Processor ;Ubuntu Linux installed by default , Microsoft windows is optional; up to 64GB DDR memory, 128 GB system disk; 4 x RJ45, 2 x USB2.0, 2 x USB3.0
- Storage board : Up to 16 SATA ,hot swapping,1 x eSATA , 4 x RJ45, 2 x USB 3.0, 2 x USB2.0

DS-7732NI-K4(16P)

DS-7716NI-K4(16P)

Embedded entry level H265+ 4K NVR, 1.5U PoE



- 160/256Mbps Bit Rate input Max(up to 32/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 8MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 4 SATA,1 eSATA, 2 x USB 2.0, 1 x USB 3.0
- /16P series support 16 independent PoE network interfaces, up to 300m
- *4-ch 4K decoding or 16-ch 1080P decoding

DS-7608NI-I2(8P)

DS-7616NI-I2(16P)

Embedded H.265+ 4K 1U PoE NVR



- 160/256 Mbps Bit Rate Input Max(up to 8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 2 SATA, 1 x USB 2.0, 1 x USB 3.0
- /8P/16P series support 8/16 independent PoE network interfaces, up to 300m
- 4-ch 4K decoding or 16-ch 1080P decoding

NVR



DS-7604/08NI-K1/W

Wi-Fi NVR with Dual External Antennas



- 50/40 Mbps bitrate input/output (up to 4/8-ch. for Wi-Fi IP camera input)
- Transmission distance at up to 150 m in open areas
- Wi-Fi frequency at 2.4 GHz
- Up to 5 MP resolution recording / live view
- H.265+/H.265/H.264+/H.264 video formats, self-adapting
- 4-ch 1080P decoding capability
- HDMI/VGA output at up to 1080P resolution
- 1 SATA interface; up to 6 TB for HDD

DS-7608NI-E2(8P)

DS-7616NI-E2(16P)

Embedded 1U PoE NVR



- 80/160Mbps bit rate input max(up to 8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 6MP resolution recording
- Support H.264+/H.264/MPEG4 video formats
- HDMI and VGA output resolution at up to 2M
- 2 SATA, 1 x USB 2.0, 1 x USB 3.0
- 8P/16P series support 8/16 independent PoE network interfaces

DS-7608NI-K2(8P)

DS-7616NI-K2(16P)

Embedded entry level H265+ 4K NVR, 1U PoE



- 160/256Mbps Bit Rate input Max(up to 8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 8MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 2 SATA, 1 x USB 2.0, 1 x USB 3.0
- 8P/16P series support 8/16 independent PoE network interfaces, up to 300m

DS-7604NI-K1(4P)

Embedded entry level H265+ 4K NVR, 1U PoE



- 40Mbps Bit Rate input Max(up to 4-ch IP cameras input)
- Third-party network cameras supported
- Up to 8MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 1 SATA, 2 USB 2.0
- 4P series support 4 independent PoE network interfaces, up to 300m

DS-7104NI-SN(P)

DS-7108NI-SN(P)

DS-7116NI-SN(P)

Embedded Mini 1U NVR



- 25/50/100Mbps bit rate input max(up to 4/8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 6MP resolution recording
- Support H.264+/H.264/MPEG4 video formats
- HDMI and VGA output at up to 2M resolution
- 1 SATA, 1 USB 2.0, 1 USB 3.0
- 4P series support 4 independent PoE network interfaces

DS-7600NI-E1/A

DS-7600NI-E1/A/500G

DS-7600NI-E1/A/1T

Embedded All-in-One NVR



- 80Mbps bit rate input max(up to 8-ch IP cameras input)
- Third-party network cameras supported
- 22" LCD monitor up to 1080P resolution & NVR all in one
- Optional display of HDMI/VGA/internal NVR video sources
- Up to 6MP resolution recording
- 1 SATA, 2 USB2.0
- Up to 1920×1080P display resolution
- Support advertising files import from USB port and preview

TURBO HD DVR

Output 4K Resolution

DS-7104/08/16HQHI-K1

HD1080P Mini 1U Turbo
HD DVR



H265+

DS-7204/08/16HQHI-K1

HD1080P 1U Turbo HD DVR



H265+

DS-7208/16HQHI-K2

HD1080P 1U Turbo HD
DVR



H265+

- 4 / 8 / 16-ch video input, 1-ch audio input
- HD-TVI / CVI / AHD / CVBS / IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- Ch 1 / Ch 1-2 / Ch 1-4 supports up to 3 MP resolution,
- HDMI output at 4K resolution (DS-7116HQHI-K1)
- Extended transmission distance over coax cable
- 1 SATA, 2 USB 2.0

- 4 / 8 / 16-ch video input, 1-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- Ch 1 / Ch 1-2 / Ch 1-4 supports up to 3 MP resolution,
- HDMI output at 4K resolution (DS-7216HQHI-K1)
- Extended transmission distance over coax cable
- 1 SATA, 1 USB2.0 & 1 USB3.0(DS-7216HQHI-K1)

- 8 / 16-ch video input, 1-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- Ch 1-2 / Ch 1-4 supports up to 3 MP resolution,
- HDMI output at 4K resolution (DS-7216HQHI-K2)
- Extended transmission distance over coax cable
- 2 SATA, 1 USB2.0 & 1 USB3.0(DS-7216HQHI-K2)

DS-7204/08HUHI-K1

5 MP 1U Turbo HD DVR



H265+

DS-7204/08/16HUHI-K2

5 MP 1U Turbo HD DVR



H265+

DS-7204HQHI-K1/P

HD1080P 1U Turbo HD PoC
DVR



H265+

- 4 / 8-ch video input, 4-ch audio input
- HD-TVI / CVI / AHD / CVBS / IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- 12 fps recording at 5 MP resolution, 15 fps recording at 4 MP resolution
- HDMI output at 4K resolution (DS-7208HUHI-K1)
- Extended transmission distance over coax cable
- 1 SATA, 1 USB2.0 & 1 USB3.0(DS-7208HUHI-K1)

- 4 / 8 / 16-ch video input, 4-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- 12 fps recording at 5 MP resolution, 15 fps recording at 4 MP resolution
- HDMI output at 4K resolution (DS-7208/16HUHI-K2)
- Extended transmission distance over coax cable
- 2 SATA, 1 USB2.0 & 1 USB3.0
(DS-7208HUHI-K2,DS-7216HUHI-K2)

- 4-ch video input, 1-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- Ch 1 supports up to 3 MP resolution
- HDMI and VGA output at up to 1920 x 1080P resolution
- Extended transmission distance over coax cable
- Built-in PoC(only support hikvision PoC camera)
- 1 SATA, 2 USB 2.0

DS-7208/16HQHI-K2/P

HD1080P 1U Turbo HD
PoC DVR



H265+

DS-7204HUHI-K1/P

5 MP 1U Turbo HD PoC DVR



H265+

DS-7208HUHI-K2/P

5 MP 1U Turbo HD PoC DVR



H265+

- 8 / 16-ch video input, 1-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.265+ / H.265+ video compression
- Ch 1-2 / Ch 1-4 supports up to 3 MP resolution,
- HDMI output at 4K resolution (DS-7216HQHI-K2/P)
- Extended transmission distance over coax cable
- Built-in PoC(only support hikvision PoC camera)
- 2 SATA, 1 USB2.0 & 1 USB3.0(DS-7216HQHI-K2/P)

- 4-ch video input, 4-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- 12 fps recording at 5 MP resolution, 15 fps recording at 4 MP resolution
- HDMI and VGA output at up to 1920 x 1080P resolution
- Extended transmission distance over coax cable
- Built-in PoC(only support hikvision PoC camera)
- 1 SATA, 2 USB 2.0

- 8-Ch video input, 4-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- 12 fps recording at 5 MP resolution, 15 fps recording at 4 MP resolution
- HDMI output at 4K resolution
- Extended transmission distance over coax cable
- Built-in PoC(only support hikvision PoC camera)
- 2 SATA, 1 USB2.0 & 1 USB3.0(DS-7208HUHI-K2/P)

DS-7304/08/16HUHI-K4

5 MP 1.5U Turbo HD DVR



H265+

DS-7304/08/16HQHI-K4

3 MP 1.5U Turbo HD DVR



H265+

SMP/3MP/1080P Series

DS-7204/08HUHI-F1/S

5MP 1U Turbo HD DVR



- 4 / 8 / 16-ch video input, 4-ch audio input
- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- 12 fps recording at 5 MP resolution, 15 fps recording at 4 MP resolution
- Dual HDMI Output, HDMI output at 4K resolution
- Extended transmission distance over coax cable
- 4 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

- HD-TVI / CVI / AHD / CVBS/IP video signal supported
- H.264/H.264+/H.265+/H.265 video compression
- Ch 1-2 / Ch 1-4 supports up to 3 MP resolution,
- HDMI output at 4K resolution
- Extended transmission distance over coax cable
- 4 SATA, 2 USB2.0 & 1 USB3.0

- 4/8-ch video & 4-ch audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- 12fps recording at 5MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F1/S), support CVBS output
- 4K UHD output (DS-7208HUHI-F1/S)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F1/S)

TURBO HD DVR

DS-7204/08/16HUHI-F2/S
5MP 1U Turbo HD DVR



- 4/8/16-ch video & 4-ch audio input
- HDTV/Aalog/AHD/IP camera quadruple hybrid
- 12fps recording at 5MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F2/S), support CVBS output
- 4K UHD output (DS-7208/16HUHI-F2/S)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208/16HUHI-F2/S)

DS-7104/08/16HGHI-F1
720P Mini 1U Turbo HD DVR



- 4/8/16-ch HD TVI/AHD/analog cameras video&audio input
- HD-TVI/Aalog/AHD/IP camera hybrid
- HD-TVI and analog cameras self-adaptive access
- Up to full channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- 1SATA, 2 USB2.0

DS-7104/08/16HQHI-F1/N
1080P Mini 1U Turbo HD DVR



- 4/8/16-ch HD TVI/Aalog/AHD cameras video&audio input
- HD-TVI/Aalog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- 1 SATA, 2 USB 2.0

DS-7204/08/16HGHI-F1
DS-7208/16HGHI-F2
720P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/AHD/analog cameras video&audio input
- HD-TVI/Aalog/AHD/IP camera quadruple hybrid
- HD-TVI and analog cameras self-adaptive access
- Up to full channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1SATA(DS-7204/08/16HGHI-E1)/2 SATA(DS-7208/16HGHI-E2), 2 USB2.0

DS-7204/08/16HQHI-F1/N
1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/AHD/analog/AHD cameras video&audio input
- HD-TVI/Aalog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 2 USB 2.0

DS-7208/16HQHI-F2/N
1080P 1U Turbo HD DVR



- 8/16-ch HD TVI/Aalog/AHD cameras video&audio input
- HD-TVI/Aalog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 2 USB 2.0

DS-7204/08HUHI-F1/N
3MP 1U Turbo HD DVR



- 4/8-ch video & 1-ch audio input
- HDTV/Aalog/AHD/IP camera quadruple hybrid
- 15fps recording at 3MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F1/N), support CVBS output
- 4K UHD output (DS-7208/HUHI-F1/N)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F1/N)

DS-7204/08HUHI-F2/N
3MP 1U Turbo HD DVR



- 4/8/16-ch video & 1-ch audio input
- HDTV/Aalog/AHD/IP camera quadruple hybrid
- 15fps recording at 3MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F2/N), support CVBS output
- 4K UHD output (DS-7208/HUHI-F2/N)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F2/N)

DS-7204/08/16HGHI-SH
1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/Aalog cameras video&audio input
- HD-TVI/Aalog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA(DS-7216HGHI-SH)/1 SATA(DS-7204/08HGHI-SH), 2 USB2.0

DS-7204/08/16HQHI-SH
Full 1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/Aalog cameras video&audio input
- HD-TVI/Aalog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@1080P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA(DS-7208/16HQHI-SH)/1 SATA(DS-7204/08HQHI-SH), 2 USB2.0

DS-7304/08/16HQHI-F4/N
1080P 1.5U Turbo HD DVR



- 4/8/16-ch video & 4-ch audio input
- HDTV/Aalog/AHD/IP camera quadruple hybrid
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7304/08HQHI-F4/N), support CVBS output
- 4K UHD output (DS-7316HQHI-F4/N)
- Long transmission distance over coax cable
- 4 SATA, 1 eSATA, 3 USB2.0, gigabit NIC

DS-7304/08/16/24/32HGHI-SH
1080P 1.5U Turbo HD DVR



- 4/8/16/24/32-ch HD TVI/Aalog cameras video&audio input
- HD-TVI/Aalog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Gigabit network interfaces
- 4 SATA, 1 eSATA, 3 USB2.0

TURBO HD DVR

DS-7304/08/16HUHI-F4/N
3MP 1.5U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 6/10/18-ch 8MP ONVIF conformant IP cameras input
- 4K (3840 × 2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 4 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-8104/08/16HUHI-F8/N
3MP 2U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 6/10/18-ch 8MP ONVIF conformant IP cameras input
- 4K (3840 × 2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-7604HUHI-F1/N & DS-7608/16HUHI-F2/N
3MP 1U Turbo HD DVR



- Up to 8/16/32-ch (Analog video + IP video) input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 8MP resolution IP video recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 2 USB 2.0(DS-7604HUHI-F1/N)
- 2 SATA, 1 USB 2.0 & 1 USB 3.0(DS-7608/16HUHI-F2/N)

DS-7304/08/16HFHI-ST(-SL)
Full 1080P/720P 1.5U HD-SDI DVR



- 4/8/16-ch HD-SDI video&audio input
- H.264 & dual-stream video compression
- Full channel(@1920×1080P resolution real-time recording)(-ST series)
- Full channel(@1280×720P resolution real-time recording)(-SL series)
- HDMI and VGA output at up to 1920×1080P resolution
- Gigabit network interfaces
- HDD quota and group management
- 4 SATA, 1 eSATA, 3 USB2.0

DS-8104/08/16HQHI-F8/N
1080P 2U Turbo HD DVR



- 4/8/16-ch video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-8104/08HQHI-F8/N), support CVBS output
- 4K UHD output (DS-8116HQHI-F8/N)
- Long transmission distance over coax cable
- 8 SATA, 1 eSATA, 3 USB2.0, gigabit NIC

HYBRID DVR

DS-9004/08/16HUHI-F8/N
3MP 2U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 10/18/32-ch 8MP ONVIF conformant IP cameras input
- 4K (3840 × 2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-7604/08/16HI-ST
Full 4CIF 1U Hybrid DVR



- Up to 8/16/32-ch (Analog video + IP video) input
- H.264 & dual-stream video compression
- Full channel(@4CIF real-time analog video recording
- Up to 5MP resolution IP video recording
- Third-party network cameras supported
- HDMI output at up to 1920×1080P resolution
- 1 SATA(DS-7604HI-ST)/2 SATA(DS-7608/16HI-ST), 2 USB2.0

DS-8104/08/16/24/32HGHI-SH
1080P 2U Turbo HD DVR



- 4/8/16/24/32-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 3 USB2.0

DS-9004/08/16HFHI-ST(-RT)
Full 4CIF 2U Hybrid DVR



- Up to 8/16/32-ch (Analog video + IP video) input
- H.264 & dual-stream video compression
- Full channel(@4CIF real-time analog video recording
- Up to 5MP resolution IP video recording
- Third-party network cameras supported
- HDMI and VGA output at up to 1920×1080P resolution
- 8 SATA, 1 eSATA, 3 USB2.0
- *-RT series support RAID0, 1, 5, 10

DS-8104/08/16HFHI-ST(-SL)
Full 1080P/720P 2U HD-SDI DVR



- 4/8/16-ch HD-SDI video&audio input
- H.264 & dual-stream video compression
- Full channel(@1920×1080P resolution real-time recording)(-ST series)
- Full channel(@1280×720P resolution real-time recording)(-SL series)
- HDMI and VGA output at up to 1920×1080P resolution
- Dual Gigabit network interfaces
- HDD quota and group management
- 8 SATA, 1 eSATA, 3 USB2.0

KEYBOARD

DS-1600KI

Network Keyboard



- 10.1" capacitive touchscreen with 1024×600 resolution
- Touchscreen and joystick detachable
- Live view
- Wifi connection
- PoE power supply
- External video play via USB interface
- HDMI, DVI output
- Emergency event recording and picture capturing
- Video wall control: window division, screen splicing, cross-window video roaming

DS-1100KI

Network Keyboard



- 7" TFT touch screen with 800×480 resolution
- Live view and video playback
- Video wall control
- 4-axis joystick
- Macro command operation
- Up to 255 analog domes by RS-485 connection
- Compatible with Hikvision IP cameras, DVR/NVR, decoder, matrix

DS-1005KI

USB Keyboard



- USB HID protocol
- Power supply and communication by USB port directly;
- PTZ control: set and call the preset, patrol and pattern
- DVR/NVR menu control
- Compatible with client software and platform software;

DS-1200KI

Network Keyboard



- 128x64 LED dot matrix screen
- PTZ and TV wall control
- 4-axis joystick
- System upgrade and import / export of configuration files by USB-flash disk
- Network access and configuration by Web browser support

DS-1006KI

RS-485 Keyboard



- 128x64 LED dot matrix screen
- PTZ and TV wall control
- 4-axis joystick
- System upgrade and import / export of configuration files by USB-flash disk
- RS-485 serial port

ENCODER & MOBILE RECORDER



ENCODERS

DS-6708/16HQHI-SATA

HD1080P Encoder



- 8/16-ch video Input, 4-ch audio input
- HD-TVI and analog cameras self-adaptive access
- H.264 & dual-stream video compression
- Full channel@1920x1080P resolution real-time recording
- Multiple network protocols
- 2 SATA interfaces, up to 6 TB for each disk
- 8/16-ch alarm in, 4-ch alarm output

NETWORK STORAGE

DS-A81024D

Network Storage System



- High-performance & easily-extensible hardware platform
- Highly reliable system design, double controller
- Support 180 -Ch(2M) record and play in IP-SAN mode,296 -Ch(2M) record and play in CVR mode
- Disk detection, repair and RAID optimization
- Low power design
- Massive storage space, 4U chassis with 14 HDs and cascade extension support

DS-A80624S

Network Storage System



- High performance with 64-bit RISC processor
- Up to 24 HDD, each disk up to 4TB capacity and cascade extension support
- Support 120 -Ch(2M) record and play in IP-SAN mode,192 -Ch(2M) record and play in CVR mode
- iSCSI/NFS/CIFS/FTP/HTTP/AFP protocols
- RAID 0, 1, 3, 5, 10, 50 and HDD hot swap supported
- Modularization and redundant power design for highest reliability

DS-M5504HMI-SD

4-Channel Mobile DVR



- Supports 4 channels of WD1 video input
- 2x SD / SDHC / SDXC card slot
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-6701/04/08/16HFI/HWI(-SATA)

Full 4CIF/960H Encoder



- 1/4/8/16-ch video&audio input
- H.264/MPEG4/MPEG2/MJPEG & dual-stream video encoding
- Full channel@ 4CIF resolution for DS-6700HFI (-SATA) and full channel@WD1(PAL:960×576,NTSC:960×480) resolution for DS-6700HWI (-SATA)
- Multiple network protocols
- One independent PoE network interfaces for DS-6701/6704HFI/HWI models
- Multiple PTZ protocols
- 1 SATA [DS-6701/04/08/16HFI/HWI-SATA]

DS-A82024D

Network Storage System



- High-performance & easily-extensible hardware platform
- Highly reliable system design, double controller
- Support 256 -Ch(2M) record and play in IP-SAN mode,448 -Ch(2M) record and play in CVR mode
- Disk detection, repair and RAID optimization
- Low power design
- Massive storage space, 4U chassis with 14 HDs and cascade extension support

DS-6600HFI-JX

ATCA Standard Encoder



- Up to 64-ch video&audio input
- H.264/MPEG4/MPEG2/MJPEG & dual-stream video encoding
- 16 slots available for audio/video output modules (DS-6604HFI-B)
- Each DS-6604HFI-B module provides 4-ch audio/video inputs
- Full channel@4CIF resolution real-time recording
- Standard rack-mounted chassis structure (6U 19")
- Pluggable modular design provides high flexibility

DS-A81016S

Network Storage System



- High performance with 64-bit RISC processor
- Up to 16 HDD, each disk up to 4TB capacity and cascade extension support
- Support 180 -Ch(2M) record and play in IP-SAN mode,296 -Ch(2M) record and play in CVR mode
- iSCSI/NFS/CIFS/FTP/HTTP/AFP protocols
- RAID 0, 1, 3, 5, 10, 50 and HDD hot swap supported
- Modularization and redundant power design for highest reliability

MOBILE RECORDERS

DS-MP3516-RS/GW

On-board Network Recorder



- 16 channels video/audio input
- Support up to 6 x 2.5-inch HDDs/SSDs
- 1-ch CVBS output, 1-ch VGA output
- Support Wi-Fi connection
- Support 3G connection *only for GW model
- 2 x Ethernet ports with M12 plug
- Built-in G-sensor
- Wide power range protection
- Super capacitor for power-off protection
- Patented anti-vibration design

DS-M5504HNI

4-Channel Mobile NVR



- Supports 4 channels of 1080P IP video input
- 4-channel POE interface
- Pluggable disk box with vibration damping technology
- 2x pluggable 2.5-inch HDDs / SSDs
- 1x SD/SDHC card slot
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-M5504HMI

4-Channel Mobile DVR



- Supports 4 channels of WD1 video input
- Pluggable disk box with vibration damping technology
- 1x 2.5-inch HDD/SSD
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-MP7504

HD-TVI Mobile DVR



- Supports 4 channels of 720P video input
- 4-ch POE interface
- Pluggable disk box with vibration damping technology
- 2x pluggable 2.5-inch HDDs / SSDs
- Pluggable 3G/4G model (optional)
- Built-in Wi-Fi/GPS (optional)
- Built-in G-sensor
- EN50155 certification

MONITOR

MONITOR

DS-D5019QE
19" LCD Monitor



- LED backlit with 1366×768 resolution
- View angle: 90°(H)/65°(V)
- Inputs: VGA
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5019QE-B
19" LCD Monitor



- LED backlit with 1366×768 resolution
- View angle: 90°(H)/65°(V)
- Inputs: VGA, HDMI
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5022FC
22" LCD Monitor



- LED backlit technology with full HD 1920×1080
- Wide View angle: 170°(H)/160°(V)
- Multiply inputs: HDMI, VGA, BNC, audio in
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5022QE-B
22"LCD Monitor



- LED backlit technology with full HD 1920×1080
- Wide View angle: 170°(H)/160°(V)
- Inputs: VGA, HDMI
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5032FC
32" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, S-Video, CVBS(BNC×1), audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5043FC
43" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, CVBS(BNC×1), audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5032FL
32" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5042FL
42" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5055FL
55" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, YPbPr, S-Video, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5055UL
55" LCD Monitor



- LED backlit with 3840×2160 UHD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI×2, VGA, DVI, DP, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5084UL
84" LCD Monitor



- LED backlit with 3840×2160 UHD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI×2, VGA, DP×2,USB, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

NETWORK SWITCH & DECODER

NETWORK SWITCH

DS-3D2208P

Full Managed L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×Gigabit combo ports
- 150Watts PoE budget
- QoS and flow control
- 32Gbps switching bandwidth
- VLAN support and tagging
- Spanning Tree Protocol(STP)
- Network Management: SNMP, Telnet, RMON, CLI
- Network Security: IEEE 802.1x, IP ACL, MAC ACL, VLAN ACL, and static/dynamic ARP prevention

DS-3D2228P

Full Managed L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 4×Gigabit combo ports
- 370Watts PoE budget
- QoS and flow control
- 32Gbps switching bandwidth
- VLAN support and tagging
- Spanning Tree Protocol(STP)
- Network Management: SNMP, Telnet, RMON, CLI
- Network Security: IEEE 802.1x, IP ACL, MAC ACL, VLAN ACL, and static/dynamic ARP prevention

DS-3E0105P-E

Unmanaged L2 PoE Switch



- 4×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 58Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0109P-E

Unmanaged L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0318P-E

Unmanaged L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0326P-E

Unmanaged L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000M combo port
- 370Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E1310P-E

Managed L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000Mbps combo uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug & play installation
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DS-3E1318P-E

Managed L2 PoE Switch



- 16×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000M combo uplink port
- 230Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DS-3E1326P-E

Managed L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000M combo port
- 370Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DECODER

DS-D6400HDI-T Series

High Definition Decoder



- Max. 8-ch 8MP or 32-ch 1080P decoding
- PC signal input via VGA/DVI input interface except DS-6401HDI-T
- Decoding output via DVI and BNC interface(DS-6401HDI HDMI/VGA/BNC output)
- 1/4/6/8/9/12/16 division
- H.264/MPEG4 /MPEG2/MJPEG format
- Max. 4×4 video wall control
- Window division, large screen splicing, cross-window video roaming

DS-D6901UDI

Ultra High Definition Decoder



- 2-ch 12MP or 16-ch 1080P decoding
- Decoding output via HDMI, VGA and BNC interface
- 4K resolution output via HDMI interface
- 1/4/6/8/9/12/16 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Two-way audio

DS-D6904UDI

Ultra High Definition Decoder



- 4-ch 12MP or 32-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

VMS & ACCESSORIES



DS-D6908UDI

Ultra High Definition Decoder



- 8-ch 12MP or 64-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

DS-D6910UDI

Ultra High Definition Decoder



- 10-ch 12MP or 80-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

DS-D6912UDI

Ultra High Definition Decoder



- 12-ch 12MP or 96-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

DS-D6916UDI

Ultra High Definition Decoder



- 16-ch 12MP or 128-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

iVMS & Blazer

iVMS 5200 Pro

iVMS-5200 Professional Software



- Centralized equipment and user management
- Support ANPR and ANPR based parking management
- Support business intelligence & POS integration
- Support RSM to control 5 CMS for large system **[New]**
- Maximum connected devices per CMS: 1024
- 3rd party surveillance integration via ONVIF protocol and SDK
- Mobile transportation management module

Blazer Pro 128/256/16H

VMS All-in-One Server



- Ready to use, preinstalled with Hikvision Professional VMS software and Windows 8.1;
- Up to 128/256 channels access and recording, recording band width up to 512/718 Mbps;
- 16HDD,HDD hot swap with RAID0, RAID1, RAID5, RAID10 support;
- Active directory integration for user management;
- 100 client user support;
- 3 years of Hardware warranty and software technical support with SSP.

PORTABLE CAMERA

DS-MH6171

Portable PTZ Dome



- 2 MP Full HD1080p high resolution
- 30X optical zoom, 12X digital zoom
- H.264+ optimized codec to reduce storage
- Dual SD card slots, up to 128 GB for each card
- Supports Wi-Fi, 3G, 4G wireless connection
- Interchangeable Lithium battery, up to 6-hour operating time
- Alarm I/O, RS232, RS485 interfaces
- Supports Bluetooth connection
- IP66 weather-proof protection
- Up to 195 feet [60m] IR range
- Powerful magnetic base for vehicle-roof mounting
- iVMS-4500 client for remote operation

Blazer Express

A Simple iVMS Station With Enormous Potential



- Easy and user friendly UI design for easy basic operation and daily monitoring operation
- Alarm information, real-time video, and the physical location are all displayed on one screen
- Interactive Live View E-map for system awareness and easy visual identification of events
- ANPR function makes entrance/exit management and identification of VIP or black list vehicles quick and convenient
- Point-of-sale integration displays transaction data and video on the same screen for effective customer

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM



ACCESS CONTROL

DS-K2210

Master Elevator Controller



- Connectable with up to 2 Wiegand card readers or 1 RS-485 card readers
- Up to 128 floors' permissions
- 20,000 normal cards and 50,000 events
- Multiple authentication modes: Card, Fingerprint, Card and Fingerprint, Card and Password, Employee ID and Password, Super Password and Duress Code.

DS-K2M0016A

Distributed Elevator Controller



- RS-485 communication with the master elevator controller
- Up to 8 distributed elevator controllers can be linked to the master elevator controller (DS-K2210)
- Linkage of the master elevator controller to report the event to the system.

DS-K1106M/C

Card Reader



- Support RS485 and Wiegand (w26, w34) protocol
- A group of LED indicator (green and red) for displaying power, communication, and card reading status
- Build-in buzzer for status indication.
- Supports Mifare card reading, including card No. or content reading
- Supports CPU card reading, including card serial No. and content reading

DS-K2M060

Secure Module



- Communicates with the access control terminal via RS-485 to execute the commands from the terminal including open door, close door, normally open and normally closed
- Collects the door magnetic signal, the exit button signal and the tamper-proof signal and send them to the access control terminal
- Supports tampering Alarm
- Supports RS-485 communication indicators to show the communication status

DS-K1802M/E

Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard

DS-K1802MK/EK

Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard
- With keypad

DS-K1F810-F

Fingerprint Card Issuer



- 500 dpi high-definition
- Support the function of PnP (plug and play)
- Optical fingerprint sensor designed with scratch-resistant material
- USB 2.0 communication standard for data transmission

DS-K1F180-D8E

Card Issuer



- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card and EM card)
- Supports on-line upgrade

DS-K1107E/EK
DS-K1107E/EK



- Support EM card,
- With keypad (DS-K1107EK)
- Supports RS485 and Wiegand (W26/W34) protocol,
- IP65 Standard

DS-K1107M/MK
Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1107MK)
- Supports RS485 and Wiegand (W26/W34) protocol,
- IP65 Standard

DS-K1200EF/MF
Fingerprint Card Reader



- Support fingerprint Mifare 1/EM card
- Supports RS485 protocol,
- IP65 Standard
- 9500 Fingerprints Capacity

DS-K2M060

Secure Module



- Provide secure door control as well as I/O expansion via encrypted communication when combined with other Hikvision terminal.
- Support RS485 protocol

DS-K1T803F
Fingerprint Access Control Terminal



- Support Access Control and Time Attendance Function
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.4-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation

DS-K1T803MF/EF
Fingerprint Access Control Terminal



- Support Access Control and Time Attendance Function
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.4-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation
- Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc

DS-K1A801F
Fingerprint Time Attendance Terminal



- Support Time Attendance Function, Forming Reports Automatically
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.8-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation(Adding Person & Card & Fingerprints Locally)

DS-K1A801MF/EF
Fingerprint Time Attendance Terminal



- Support Time Attendance Function, Forming Reports Automatically
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.8-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation(Adding Person & Card & Fingerprints Locally)
- Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM



DS-K2801

Single-door Access Controller



DS-K2802

Double-door Access Controller



DS-K2804

Four-door Access Controller



DS-K1T801M/E

Time & Attendance and Access Control Terminal



- Accessible Card Reader: 2 Wiegand readers
- Input interface: 1 Door Magnetic, 1 Door Switch, 1 Case Input
- Output interface: 1 Door Switch Relay, 1 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

- Accessible Card Reader: 4 Wiegand readers
- Input interface: 2 Door Magnetic, 2 Door Switch, 2 Case Input
- Output interface: 2 Door Switch Relay, 2 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

- Accessible Card Reader: 4 Wiegand readers
- Input interface: 4 Door Magnetic, 4 Door Switch, 4 Case Input
- Output interface: 4 Door Switch Relay, 4 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

- 12 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- Max. 3000 card number settings
- Supports door-open button

DS-K1T802M/E

Time & Attendance and Access Control Terminal



DS-K1801MK/EK

Card Reader



DS-K1801M/E

Card Reader



- 128x64 Dot Matrix STN Screen
- 12 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- Supports door-open button
- Storage with 3,000 cards information and 10,000 access control events

- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard
- With keypad

- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard

- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card, CPU, PSAM, and EM card)
- Supports on-line upgrade

DS-K2601

Single door Access Controller



DS-K2602

Double-door Access Controller



DS-K2604

Four door Access Controller



- Accessible Card Reader: 2 Wiegand readers & 2 RS485 readers
- Input interface: 4 Alarm Input, 1 Door Magnetic, 1 Door Switch, 2 Case Input, 1 Tamper-proof
- Output interface: 1 Door Switch Relay, 1 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

- Accessible Card Reader: 4 Wiegand readers & 4 RS485 readers
- Input interface: 4 Alarm Input, 2 Door Magnetic, 2 Door Switch, 4 Case Input, 1 Tamper-proof
- Output interface: 2 Door Switch Relay, 2 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

- Accessible Card Reader: 4 Wiegand readers & 8 RS485 readers
- Input interface: 4 Alarm Input, 4 Door Magnetic, 4 Door Switch, 8 Case Input, 1 Tamper-proof
- Output interface: 4 Door Switch Relay, 4 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

DS-K1T105M/[E]-C]

Standalone Access Control Terminal



DS-K1T200MF/EF(-C)

Standalone Access Control Terminal



DS-K1101M(K)

Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1101MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 120 Gang Box Only

DS-K1102M(K)

Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1102MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box

DS-K1102E(K)

Card Reader



- Support EM card,
- With keypad (DS-K1102EK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM



DS-K1104M(K)

Vandal Proof Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1104MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box
- Vandal Proof

DS-K1F800-F

Fingerprint Card Issuer



- 500 dpi high-definition
- Support the function of PnP(plugin and play)
- Optical fingerprint sensor designed with scratch-resistant material
- USB 2.0 communication standard for data transmission

IC S50

Mifare 1 Non-contacting IC Card



DS-K4T100

Electric Bolt



- Support Thrust of 800Kg;

- Polished and Brushed Stainless Steel
- Working Current: 900mA(Startup Current), 100mA(Standby)
- DC12V

DS-K4H250S

Magnetic Lock



- Single -door Control
- Supports static linear thrust of 300kg
- Working Current: DC12V(500 mA) / 24VAC(250 mA)

DS-K4H250D

Magnetic Lock



- Double-door Control
- Supports static linear thrust of 2x300kg
- Working Current: 12V/500mA × 2 24V/250mA × 2

DS-K4T100-U1/2

Accessories of Electric Bolt



- Aluminum alloy material
- Suitable for fully frameless glass door
- The door opens both sides at the angle of 180°

DS-K4H250-LZ/U

Accessories of Magnetic Lock



- Adopts aldural material with the surface sandblast
- The shell is hard anodizing electroplating operated

DS-K7P01/02

Exit Button



- Aluminum alloy panel with sandblast, metal button
- Already passed 500 thousand times aging test
- NO/NC/COM Contact
- 3A@36VDC Max

DS-K7P03/04

Exit Button



- Infrared Sensor
- Panel: aluminum panel
- Already passed 1 million times aging test
- NO/NC/COM Contact
- 1A@30VDC, 0.5A@125VAC

DS-K7P05/06

Exit Button



- Infrared Sensor
- Brushed stainless steel panel, metal button
- Already passed 500 thousand times aging test
- NO/NC/COM Contact
- 3A@36VDC Max

DS-K7PEB

Emergency Break Glass



- Suitable for exit door and emergency door
- Fireproof material, sandblast finished
- NO/NC/COM Contact
- 3A@36VDC Max

INTRUSION ALARM

DS-19A08-F/Kx(G)

8 Zone Network Security Control Panel



- PTSN, 10/100Mbps Ethernet
- LED screen (DS-19A08-F/K1)
- LCD screen (DS-19A08-F/K2)
- 1 relay output
- 14.3 VDC

DS-19S08-04F/Kx(Gx)

8 Zone Video Security Control Panel



- 4-ch 960H analog video input
- PTZ control
- LED screen (DS-19S08-04F/K1)
- LCD screen (DS-19S08-04F/K2)
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19S08N-04F/Kx(Gx)

8 Zone Video Security Control Panel



- Support 4-ch IPC video input, Max 25 Mbps
- PTZ Control
- LED screen (DS-19S08N-04F/K1)
- LCD screen (DS-19S08N-04F/K2)
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19A00-BN

8/16 Zone Video Control Panel



- PTSN, 10/100Mbps Ethernet
- 4 relay output, 220 VAC

ACCESS CONTROL INTRUSION ALARM & VIDEO INTERCOM



DS-19S00-04S(Gx)

8/16 Zone Video Security Control Panel



- 4-ch 960H analog video input
- PTZ Control
- 1-ch VGA output, 1-ch HDMI output
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19S00N-04S(Gx)

8/16 Zone Video Security Control Panel



- Support 4-ch IPC video input, support dual-stream
- PTZ Control
- 1-ch VGA output, 1-ch HDMI output
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-1T21FZ

Dual-technology Detector



- CLOAK WISETM arithmetic
- Tempering-proof bracket
- Sealing optical system
- The IR and microwave working distance is 15m X 15m

DS-1T070R

Shock Detector



- The zinc-aluminum alloy enclosure is antistatic and anti-interference
- The sensitivity is adjustable
- Ceramics sensor, with high temperature & humidity adaptation and corrosion resistance
- Function of low battery and tampering alarm

DS-19K00-B(X)

LED Alarm Keypad



DS-19K00-BL

LCD Alarm Keypad



DS-19M00-RO

Trigger Extension Module



VIDEO INTERCOM

DS-KB6003-WIP

Doorbell



- Supports remote control via wireless network(the keypad with model of RF)
- Prompts alarm with the indicators and audio alert
- Operates on the security control panel through programming
- LED display, RS485 interface

- Supports remote control via wireless network(the keypad with model of RF)
- Prompts alarm with the indicators and audio alert
- Operates on the security control panel through programming
- LCD display, RS485 interface

- RS-485 trigger extension module
- 8 DIP address
- 4/8-ch trigger Output

- Video intercom function, supporting communication with the mobile App directly
- IP 54 standard
- 1080P camera,180°field of view
- Supports connecting to the mechanical doorbell

DS-KB2421-IM

Video Intercom
Door Station



- Intercom communication with indoor station
- Self-adaptive IR supplement (with photoresistor)
- Pinhole camera with 720 x 576
- Unlock controlling
- Anti-oxidant zinc alloy
- Vandal-resistant (IK7)
- Surface mounting
- IP65

DS-KB8112-IM

vandal-proof villa door station



- HD video surveillance with WDR wide angle and high performance CMOS, up to 720P @ 30 fps
- Support Web remote access and OSD display
- Support ISAPI and ONVIF
- IK 9 and IP 66
- Access control function
- Motion detection

DS-KAD606-P

Distributor



- Suitable for indoor station and villa door station
- 8 x 10/100Mbps ports(6-ch network cable powering and 2-ch cascading LAN interfaces)
- Support 24V DC power supply

DS-KAD606-N

Distributor



- Built-in 24 VDC voltage-stabilized switching mode power supply
- 8 interfaces of RJ-45, including six adaptive 10/100 Mbps LAN interfaces

DS-KB2411-IM

Door Station



- Pinhole Camera with 720*576 @ 25 fps
- Video Intercom Communication
- Support Two Door Stations Cascading in Intercom System
- Unlocking Controlling
- Self-adaptive IR Supplement

DS-KH2220

Indoor Station



- 7-inch LCD Screen
- Video Intercom Communication
- Support Three Indoor Stations Cascading in Intercom System
- Remote Unlocking
- Monitoring Door Station and External Analog Camera

DS-KD8102-V

Plastic Door Station



- 3.5-inch Colorful TFT LCD, display resolution: 480 * 320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M/1000M Self-adaptive Ethernet
- 8-ch alarm input, 4-ch alarm output
- IR detection
- Visible Light Supplement

DS-KD8002-VM

Metal Door Station



- 3.5-inch Colorful TFT LCD, display resolution: 480 * 320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M/1000M Self-adaptive Ethernet
- 8-ch alarm input, 4-ch alarm output
- Visible Light Supplement

DS-KV81/2/402-IM
Metal Villa Door Station



- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M Self-adaptive Ethernet
- 4-ch alarm input, 1-ch alarm output
- IP 65 and IR Supplement
- 1/2/4-ch Indoor station access

DS-KV8102-IP/VP
Plastic Villa Door Station



- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M Self-adaptive Ethernet
- 4-ch alarm input, 1-ch alarm output
- IP 65
- 1-ch Indoor station access
- Visible Light Supplement(-VP), IR Supplement(-IP)

DS-KH8300/DS-KH8301-WT
Indoor Station



- 7-inch Colorful TFT LCD, display resolution: 1024 * 600
- 10M/100M Self-adaptive Ethernet
- Camera resolution: 640 * 480, Mechanical Switch, Wi-Fi 802.11b/g/n, support SD card (DS-KH8301-WT)
- 8-ch alarm input
- Power Over Network Cable/ 12 VDC

DS-KH6310(-W)
Indoor Station



- 7-inch Colorful TFT LCD, display resolution: 800 * 480
- 10M/100M Self-adaptive Ethernet
- Wi-Fi 802.11b/g/n (-W)
- 8-ch alarm input
- Power Over Network Cable/ 12 VDC

DS-KAD606/612
Distributor



- Built-in voltage-stabilized power
- Suitable for indoor monitor station and villa door station
- 8 x 100Mbps ports(6-ch network cable powering and 2-ch cascading LAN interfaces) (DS-KAD606)
- 16 x 100Mbps ports(12-ch network cable powering and 4-ch cascading LAN interfaces) (DS-KAD612)

DS-KM8301
Master Station



- 7-Inch Colorful TFT LCD, display resolution: 1024 * 600
- Capacitive Touch Screen, Touch Key, Physical Key
- 10M/100M/1000M Self-Adaptive Ethernet
- SIP services
- 2 RS-485, 4 On-Off Input, 2 On-Off Output, 2 Relay Output,

DS-KAW50-1
Power Supply



- Power supply for Door station and Villa Door Station
- Output: 12 VDC, 4.2A

DS-KAW50-1N
Power Supply



- Input Voltage:100-240VAC
- Output Voltage:12VDC
- Output Current: 4.17A
- Output Power: 50W
- Short circuit protection, over load protection, and over power voltage protection

DS-KAB01
Protective Shield



- Stainless steel material
- Convenient design available for villa door station wall mounting
- Avoid of being directly exposed to the sun
- Rain shield and mounted box are separated.

DS-KAB02
Protective Shield



- Stainless steel material
- Convenient design available for villa door station wall mounting
- Avoid of being directly exposed to the sun

COMPRESSION CARDS

DS-4304HFHI-E
HD1080P Compression Card




- 4-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@1920×1080P resolution real-time recording
- HDMI output at up to 1920×1080P resolution
- PCI-Ex1 2.0 standard
- OSD, LOGO and mask area settings

DS-4308/16HWI-E
Full 960H Compression Card



- 8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@WD1(PAL:960×576,NTSC:960×480) resolution
- real-time recording
- PCI-Ex1 2.0 standard
- OSD,LOGO and MASK overlay

DS-4304/08/16HFVI-E
Full 4CIF Compression Card



- 4/8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@4CIF resolution real-time recording
- PCI-Ex1 2.0 standard
- OSD,LOGO and MASK overlay

HIKVISION®

First Choice for Security Professionals





Products Quick Guide 2017 H2



پارس ارتباط افزار
تنها نماینده رسمی هایک ویژن در ایران

نماینده شرکت پارس ارتباط:



پارس ارتباط افزار

تهران، خیابان شهید بهشتی، خیابان سرافراز، کوچه سوم، پلاک ۱۲

تلفن: ۰۱۸ ۹۳۹۵ - ۰۱

ایمیل: info@pars-e.com

www.hikvision.com www.pars-e.com

[@hikvision_iran](https://twitter.com/hikvision_iran) [@parsertebatchannel](https://twitter.com/parsertebatchannel)

