

IPC-E1F4D-I30 4.0mm

4MP Mini Fixed Bullet Network Camera



قابلیت های کلیدی

- پشتیبانی از پروتکل ONVIF
- دمای کارکرد -30 تا +60 درجه سانتیگراد
- مقاومت در برابر نفوذ آب و گرد و غبار IP67
- پایه قابل تنظیم 3 حالت
- Ultra 256, H.265, H.264, MJPEG
- پشتیبانی از ROI
- قابلیت روز و شب
- IR هوشمند 30 تا 50 متر
- کاهنده نویز دیجیتال 3D
- شیشه ضد بازتاب نور مادون قرمز

Specifications

sensor	1/3", 4.0 megapixel, progressive scan, CMOS					HLC	Supported
Lens	4.0mm@F2.0					BLC	Supported
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)	OSD	Up to 4 OSDs
	4.0	90	36	18	9	Privacy Mask	Up to 4 areas
Angle of View (H)	78.9°					ROI	Up to 2 areas
Angle of View (V)	39.6°					Motion Detection	Up to 4 areas
Angle of View (O)	97.0°					Smart Features	intrusion, Human body detection
Adjustment angle	Pan: 0° - 360°	Tilt: 0° - 90°		Rotate: 0° - 360°		Intrusion	Enter and loiter in a pre-defined virtual region
	Shutter						Protocols
Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on					Compatible Integration	ONVIF (Profile S, Profile T), API
Digital noise reduction	2D/3D DNR					Network	10/100M Base-TX Ethernet
Day/Night	IR-cut filter with auto switch (ICR)					Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5W
S/N	>52dB					Dimensions (L x W x H)	167.3 x 62.9 x 62.7mm (6.6" x 2.5" x 2.5")
IR Range	30-50m IR range					Weight	0.45kg (0.99lb)
WDR	100dB					Working Environment	-30°C - 60°C (-22°F - 140°F), Humidity: ≤95% RH (non-condensing)
Video Compression	Ultra 265, H.265, H.264, MJPEG					Ingress Protection	IP67
H.264 code profile	Baseline profile, Main Profile					Reset Button	Supported
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps;						
	Sub Stream: 720P (1280*720), Max 20fps;						
	Third Stream: D1 (720*576), Max 20fps						

Dimensions

